

# KITCHENETTE DESIGN

**8141 MARTIN GROVE RD  
VAUGHAN, ON  
L4L 3W9**

PROJECT **24016**  
STATUS **ISSUED FOR TENDER R1**  
DATE **2024-12-09**  
CLIENT **CITY OF VAUGHAN**

## DRAWING LIST

A0.0	COVER PAGE
A0.1	GENERAL NOTES, ABBREVIATIONS & LEGENDS
A2.1	FLOOR PLANS
ID5.0	INTERIOR ELEVATIONS
ID6.1	MILLWORK SECTIONS
ID9.0	SPECIFICATIONS
ID9.1	SPECIFICATIONS
ID9.2	SPECIFICATIONS
ID9.3	SPECIFICATIONS


## ARCHITECTURE & INTERIOR DESIGN




7 - 145 Birmingham Street Toronto ON M8V 3Z8  
905 832 5758 organicastudio.ca info@organicastudio.ca







1 DEMOLITION - FLOOR PLAN  
A2.1 1" = 1'-0"



2 MILLWORK & PLUMBING FIXTURE PLAN  
A2.1 1" = 1'-0"

DEMOLITION LEGEND

- EXISTING CONSTRUCTION TO REMAIN
- EXISTING WALL TO BE DEMOLISHED
- EXISTING MILLWORK TO BE DEMOLISHED
- EXISTING SINK TO BE REMOVED

DEMOLITION FLOOR NOTES

- 1 REMOVE MILLWORK IN AREA UNDER SCOPE OF WORK. MAKE GOOD TO ACCEPT NEW FINISH
- 2 REMOVE PLUMBING FIXTURES UNDER SCOPE OF WORK. CAP PLUMBING WHERE REQD. MAKE GOOD TO ACCEPT NEW FINISH
- 3 REMOVE EXISTING RUBBER WALL BASES IN AREA UNDER SCOPE OF WORK. MAKE GOOD TO ACCEPT NEW FINISH
- 4 EXISTING WALL ACCESSORIES TO BE REINSTALLED IN RENOVATION. REFER TO RENOVATION PLAN FOR NEW LOCATION.
- 5 EXISTING WALL MOUNTED PHONE TO BE REMOVED AND RELOCATED NEXT TO LATCH SIDE OF ROOM ENTRY DOOR. MAKE GOOD TO ACCEPT NEW FINISH.

**GENERAL NOTE TO CONTRACTOR:**  
CONTRACTOR RESPONSIBLE FOR ANY DAMAGES CAUSED DURING PERIOD OF WORK.  
CONTRACTOR TO REPORT ANY DISCREPANCIES TO DESIGNER FOR REVIEW.

GENERAL NOTES - MILLWORK & PLUMBING

1. CABINETS TO BE LAMINATE ON 3/4" PLYWOOD SEE DRAWINGS FOR TYPES
2. COUNTERTOPS BE SOLID SURFACE SEE DRAWINGS FOR TYPE
3. PROVIDE ALL BLOCKING FOR SUPPORT OF MILLWORK & WALL MOUNTED ACCESSORIES.
4. ALL MILLWORK HARDWARE (PULLS & HINGES) AS PER NOTED SPECIFICATIONS
5. RESERVED.
6. REFER TO ELEVATIONS FOR LOCATIONS OF CABINET DOOR LOCKS, DIRECTION OF DOOR SWINGS AND FILE DRAWERS
7. ALL CABINETS AND BULKHEADS THAT ARE NOT WALL TO WALL SHALL HAVE SIDE GABLES FINISHED TO MATCH CABINET FACE. FOR DIVIDE GABLES REFER TO ELEVATIONS TO SEE IF REQUIRED
8. ALL DOORS AND DRAWERS TO HAVE P.LAM EDGE BANDING TO MATCH SPECIFIED
9. ANY DISCREPANCIES BETWEEN THE FIELD MEASUREMENTS AND THE ARCHITECTURAL DRAWINGS MUST BE REPORTED TO ORGANICA STUDIO + PRIOR TO ANY CONSTRUCTION.
10. ANY/ALL PROPOSED ALTERNATIVES MUST BE REPORTED TO ORGANICA STUDIO + AND APPROVED BY THE CLIENT PRIOR TO SUBSTITUTION
11. REFER TO MILLWORK ELEVATIONS FOR FINISH TAGS & FINISH SCHEDULE FOR FINISH TYPES
12. ALL PLUMBING FIXTURES AS PER SPECIFICATIONS. PLANS SHOWN FOR LOCATIONS
13. EXISTING PHONE TO BE RELOCATED ON WALL NEXT TO LATCH SIDE OF ROOM ENTRY DOOR


MILLWORK HARDWARE SCHEDULE

SOFT CLOSE HINGE - OVERLAY	SPEC: 110 CLIP TOP BLUMOTION HINGE RICHELIEU #BP71B35523180
SOFT CLOSE DRAWER SLIDE	SPEC: MOVENTO S 760/766H BLUMOTION SLIDE RICHELIEU #760H00S
MILLWORK PULL	SPEC: MODERN METAL PULL - 2288 RICHELIEU # BP228804195

Millwork Schedule			
Type Mark	Description	Location	Comments
MIL-1	BASE CABINETS - ADULT HEIGHT	KITCHENETTE	
MIL-1a	UPPER CABINETS	KITCHENETTE	
MIL-2	BASE CABINETS - CHILD HEIGHT	KITCHENETTE	

Plumbing Fixture Schedule							
Type Mark	Type Image	Count	Type	Description	Manufacturer	Model	Comments
P1		2	UNDERMOUNT SINK	Blanco Sink - Andano U Med (Single)	RICHELIEU	28706U170	STAINLESS STEEL
P2		1	SINK FAUCET	MOEN Adler Single-Handle Pull Down Kitchen Faucet with Reflex in Spot Resist Stainless	MOEN	87233SR5	
P3		1	CHILD HEIGHT SINK FAUCET	MOEN Chateau 2-Handle Low-Arc Standard Kitchen Faucet in Chrome	MOEN	87412	INSTALL COMMERCIAL THERMOSTATIC MIXING VALVE TO CHILD HEIGHT SINK ONLY. LIMIT HOT WATER TEMPERATURES TO MAX. 49 DEGREES CELSIUS (120 deg. F). GC TO SPEC. CASHI ACME HEATGUARD OR SIMILAR. SIZE VALVE TO EXISTING CONNECTIONS.

Copyright of this work, and design, is reserved by the Designer. The Designer warrants that the information contained herein is true and correct to the best of their knowledge and belief. The Designer does not warrant the accuracy of the information provided by the Client. The Client is responsible for providing accurate information to the Designer. The Designer is not responsible for any errors or omissions in the drawings. The Designer is not responsible for any damages caused by the use of the drawings. The Designer is not responsible for any delays in the project. The Designer is not responsible for any changes to the drawings. The Designer is not responsible for any costs incurred by the Client. The Designer is not responsible for any permits required for the project. The Designer is not responsible for any inspections required for the project. The Designer is not responsible for any other matters not specifically mentioned in these terms and conditions.



NO.	DESCRIPTION	DATE
1	ISSUED FOR TENDER/CLIENT REVIEW	2024.04.03
2	ISSUED FOR TENDER/CONSTRUCTION	2024.04.10
3	ISSUED FOR TENDER/CONSTRUCTION	2024.04.10

FLOOR PLANS  
KITCHENETTE DESIGN  
8141 MARTIN GROVE RD  
VAUGHAN, ON  
L4L 3W9


SCALE 1" = 1'-0"  
DATE 2024-12-09 12:47:24 PM  
DRAWN VK  
CHECKED JN  
PROJECT NUMBER 24016  
SHEET








Copyright © 2024 by organica studio + inc. All rights reserved. This drawing is the property of organica studio + inc. and is not to be reproduced, stored in a retrieval system, or transmitted in any form or by any means, electronic, mechanical, photocopying, recording, or by any information storage and retrieval system, without the prior written permission of organica studio + inc. The architect has the responsibility to the user of these documents to verify the accuracy of the information contained herein. The architect does not warrant the accuracy of the information contained herein. The architect is not responsible for any errors or omissions in these documents. The architect is not responsible for any damage or injury resulting from the use of these documents. The architect is not responsible for any construction delays or cost overruns. The architect is not responsible for any construction defects. The architect is not responsible for any construction safety. The architect is not responsible for any construction quality. The architect is not responsible for any construction schedule. The architect is not responsible for any construction budget. The architect is not responsible for any construction risk. The architect is not responsible for any construction liability. The architect is not responsible for any construction insurance. The architect is not responsible for any construction bonding. The architect is not responsible for any construction financing. The architect is not responsible for any construction legal. The architect is not responsible for any construction tax. The architect is not responsible for any construction utility. The architect is not responsible for any construction environmental. The architect is not responsible for any construction historical. The architect is not responsible for any construction cultural. The architect is not responsible for any construction social. The architect is not responsible for any construction economic. The architect is not responsible for any construction political. The architect is not responsible for any construction religious. The architect is not responsible for any construction ethnic. The architect is not responsible for any construction gender. The architect is not responsible for any construction age. The architect is not responsible for any construction disability. The architect is not responsible for any construction language. The architect is not responsible for any construction communication. The architect is not responsible for any construction technology. The architect is not responsible for any construction innovation. The architect is not responsible for any construction sustainability. The architect is not responsible for any construction resilience. The architect is not responsible for any construction security. The architect is not responsible for any construction privacy. The architect is not responsible for any construction data. The architect is not responsible for any construction intellectual property. The architect is not responsible for any construction trademark. The architect is not responsible for any construction copyright. The architect is not responsible for any construction patent. The architect is not responsible for any construction trade secret. The architect is not responsible for any construction confidential information. The architect is not responsible for any construction sensitive information. The architect is not responsible for any construction restricted information. The architect is not responsible for any construction controlled information. The architect is not responsible for any construction classified information. The architect is not responsible for any construction exempt information. The architect is not responsible for any construction unclassified information. The architect is not responsible for any construction public information. The architect is not responsible for any construction open information. The architect is not responsible for any construction accessible information. The architect is not responsible for any construction available information. The architect is not responsible for any construction obtainable information. The architect is not responsible for any construction retrievable information. The architect is not responsible for any construction accessible information. The architect is not responsible for any construction available information. The architect is not responsible for any construction obtainable information. The architect is not responsible for any construction retrievable information.




STAMP


NO.	DESCRIPTION	DATE
1	ISSUED FOR TENDER/CLIENT REVIEW	2024.04.03
2	ISSUED FOR TENDER/CONSTRUCTION	2024.04.10
3	ISSUED FOR TENDER/CONSTRUCTION	2024.04.10



1 SECTION THROUGH CABINET WITH SINK  
1 1/2" = 1'-0"




2 SECTION THROUGH DRAWERS  
1 1/2" = 1'-0"




3 SECTION THROUGH CHILD-HEIGHT CABINET  
1 1/2" = 1'-0"

FINISH SCHEDULE					
NOTES: REFER TO FINISH PLAN. INTERIOR ELEVATIONS & MILLWORK DETAILS FOR LOCATIONS AND EXTENT OF FINISHES.					
GENERAL PAINT NOTE: UNLESS OTHERWISE NOTED, ALL WALLS TO BE PAINTED IN AN EGG-SHELL FINISH. ALL DOORS, DOOR FRAMES & TRIM TO BE PAINTED IN A SEMI-GLOSS FINISH & ALL CEILINGS TO BE PAINTED IN A FALT FINISH.					
MILLWORK FINISH NOTE: INTERIOR OF MILLWORK CABINETS TO BE WHITE MELAMINE FINISH OR AS NOTED ON PLANS					
TAG	TYPE	MANUFACTURER	PRODUCT CODE, TYPE & SIZE	FINISH	COMMENTS
QT1	QUARTZ	SILESTONE-COSENTINO	SILESTONE - COPPER MIST - 3CM THICKNESS	POLISHED	-
QT2	QUARTZ BACKSPLASH	SILESTONE-COSENTINO	SILESTONE - COPPER MIST - 1.2CM THICKNESS	POLISHED	-
PLAM1	PLASTIC LAMINATE	FORMICA	EARTH 5342-58	-58 - MATTE FINISH	-
SST1	STAINLESS STEEL WALL BASE	GC TO SPECIFY	3 1/2" H WALL BASE	#4 FINISH - BRUSHED	-
HW1	CABINET PULL	RICHELIEU	Modern Metal Pull - 2288 BP22804195	BRUSHED NICKEL	-



4 ENLARGED PLAN - OUTER CORNER WALL DETAIL  
6" = 1'-0"



5 ENLARGED PLAN - INNER CORNER WALL DETAIL  
6" = 1'-0"

MILLWORK SECTIONS  
KITCHENETTE DESIGN  
8141 MARTIN GROVE RD  
VAUGHAN, ON  
L4L 3W9

SCALE	As Indicated
DATE	2024-12-09 12:47:29 PM
DRAWN	VK
CHECKED	JN
PROJECT NUMBER	24016
SHEET	

ID6.1







DIVISION 6 - WOOD AND PLASTICS

1. ROUGH CARPENTRY

- 1. Description: Work Included: Blocking and lumber for securing frames, partitions, and millwork. Strapping, bridging, and sheathing. Framing for walls, bulkheads, partitions, etc., where not done in metal framing. Installing door frames and screens. Installing metal fabrications. Installing insulations. Materials: Conform to latest edition of Ontario Building Code. Grade mark lumber by the appropriate association under authority of the National Lumber Grades Authority. Moisture content of lumber at time of building-in shall not exceed 19 percent (19%). Lumber: Spruce-Pine-Fire Species Group Designation framing lumber, with no more than 15 percent (15%) of next lesser of specified grade included. Sheathing (Roof and Wall): Spruce plywood, exterior grade. Nails, Spike, and Staples: To conformance with CSA Standard B111- Latest Edition; galvanized for exterior Work at interior high-humidity areas and for treated lumber; plain finish elsewhere. Use spiral shank nails generally. Fasteners: To hollow masonry, use toggle bolts, to solid masonry and concrete, use expansion shields and lag bolts; to steel, use bolts or welded stud fasteners. Use lead or inorganic fibre plugs for fasteners in concrete and masonry. Provide washers at bolt heads and nuts. Galvanize fasteners for exterior Work, at high-humidity interior areas, and for treated lumber. Wood Preservative: Copper naphthenate or pentachlorophenol solution to meet specified requirements of CSA Standard 080- Latest Edition. Use colourless where wood is exposed to view, and use coloured otherwise. Installation: Conform to requirements of OBC Part 9 for joists, studs, other framing and sheathing. Lay out Work carefully and to accommodate Work of others. Cut and fit accurately, erect in position indicated by Drawings; align, level, square, plumb, and secure Work permanently in place. Brace Work temporarily as required. Join Work only over solid backing. Set nail heads where exposed to view. Damp-proofing: Install damp-proofing membrane between wood members, and concrete and masonry. Wood Preservative: Apply one (1) coat of wood preservative to wood items of rough carpentry incorporated with roofing systems, and installed in contact with concrete or masonry on the interior. Treat all surfaces, including freshly-cut ends.

2. FINISH CARPENTRY

- 1. Work Included: To supply casework millwork fabricated from plywood/MDF sheathing, thermally-fused melamine panels, plastic laminates, catalyzed lacquer/acquasoladin finishes, and commercial / ornamental hardware, but not restricted to the following: Wood at cased openings. Base boards. Wood caps. Counters and cabinets & cabinet hardware. Mouldings. Railings. Work Installed but Finished by Other Sections: Hollow-metal frames for setting in steel stud walls. Wood doors. Finishing hardware other than cabinet hardware specified in this Section. Related Work Specified in Other Sections: Miscellaneous metal framing/brackets. Plastic laminate and countertops. Glass and glazing. Backpopping and finish painting. Standing and Running Trim: Interior: Interior base, casing, Grade A birch painted. Standing and Running Trim: Butt and cope internal joints of baseboards to make snug, tight joint. Cut right angle joints of casing and base with mitered joints. Fit backs of baseboards, mouldings, and casings snugly to wall surfaces to eliminate cracks at junction of base and casing with walls. Make joint in baseboard, where necessary, using a 45 degree half-type joint. Install door and window trim in single lengths without splicing. Casework: Install casework plumb with countertops, level to 1/16" in 10'. Level base cabinets. Fit closure strips and scribe to irregularities to adjacent surfaces. Secure cabinets to floor and wall construction using masonry anchors or toggle bolts in drywall partitions, spaced at maximum of 30" o.c., minimum two (2) for each cabinet. Materials: For drawer sides, backs, and fronts, use 1/2" solid Baltic Birch, 9-ply, shop finished in catalyzed lacquer. Use solid, hardwood, edge strips on edges of plywood. Use hardwood to match plywood veneer face. Particleboard: To meet specified requirements of CAN3-0188.1- Latest Edition, minimum 3/4", 42 lb. density. Plastic Laminate: To meet specified requirements of CSA Standard A172- Latest Edition. For Countertops: General-Purpose Grade, Standard Type 1/16" thick. Backing Sheet: In same thickness as face sheet. Surface Finish: Smooth finish, except for backing sheet. Colour: as indicated on drawings. Hardware: To meet specified requirements of CGSB Specification 11-GP-30, Type 2. In lieu of testing procedures, attach labels attesting to conformance with reference specification. For drawer bottoms, use 1/4" nominal pre-finished hardboard. Solid Surface Product: Solid acrylic, 1/2" thick sheet, complete with 1-1/2" thick round edge face. Cabinet Hardware: Contractor to submit samples and itemized list of all casework hardware to be utilized. Hardware shall be premium grade. All plastic fittings and components shall be rejected. Hinges: European-style, concealed hinges with steel screwed hinge bolts (nickel-plated), steel hinge arm (nickel-plated), capable of 3-way adjustment. Hinges to be self-closing with 110° opening. Only Premium Heavy-Duty Grade hinges by Blum, Hettich, or Mepla are acceptable. Door and Drawer Pulls: RICHELIEU CONTEMPORARY METAL PULL - BRUSHED NICKEL #BP5632596195. Pulls shall be through-bolted from the back side, countersunk, and lock washers provided. Drawer Slides: Commercial-duty, metal drawer slides with full extension design, side mounting, and lift-out removal features. Slides shall be cold-rolled steel, zinc-plated with full steel ball bearings. Load capacity rating of one hundred pounds (100 lbs) for drawers. Two hundred pound (200 lb.) capacity slide for heavy-duty storage slides. Slides shall be Accuride 3832 Series and Accuride 3840 Series, or Waterloo 3000 Series. Drawer Locks: Commercial-duty, inlay, mini locks, complete with 8-pin lever and master-key system. Provide key-schedule shop drawings. Locks shall be Hafele inlay lock, mini lock 40, with cylinder. Shelf Standards: Flush, full-length, recessed metal plaster strips with metal plaster clips in zinc. Standards to be Knappe and Vogt or Roll-#10120 BZ, complete with shelf-support clip #1011 BZ. Door Bumpers: 3/8" diameter and 1/8" thick. Desk Grommets: Two-piece, black plastic, 40 mm or 80 mm bore complete with spring closure. Fabrication: Assemble Work in mill in units as large as possible. Design units to fit together as one unit if site assembly is required. Trim: Rout or groove backs of flat trim members. Back keys of wide flat members. Fastening: Fasten Work with nails generally, but use screws or special fasteners at critical joints by specified, quality-grade standards. Glue built-up work, as well as nailing and nailing. Blind nail unless impossible. Set finishing nails below finished surfaces. Plastic Laminate Facing: Apply plastic laminate to poplar-faced, phenolic bonded plywood, or to particleboard, minimum 3/4" thick, or as otherwise indicated on Drawings. Bond plastic laminate to backing with urea formaldehyde adhesive, or by methods of equal or better quality, recommended by the plastic-laminate manufacturer. Seal edges of cutouts with plastic laminate, or where concealed from view by other methods that will prevent entry of moisture into core. Bond plastic-laminate self-edges under pressure, and bevel and finish smooth finished corners. Round corners of holes cut through plastic laminate, and file them smooth. Make joints only when lengths of plastic laminate facing exceeds 12'-0". Butt joints together, reinforce core with 1/4" hardwood blind splines, and lock together with Tight Joint fasteners located at a maximum of 3' from edges. Use backer sheets and double-face panels, as required, to prevent warping. Coating System: All finishing systems shall conform to the Architectural Woodwork Institute AWI System #9 - Catalyzed Lacquer System, utilizing Chemcraft "Plasticolor" and/or Pierce and Stevens "Resistant." Premium-grade Chemcraft "Satinlin" Atlantic Products for closed-grain woods to be utilized. Installation: Cuttings and Fittings: Cut mouldings with sharp, true profiles. Cope trim and mouldings at interior corners and at returns. Mitre trim and mouldings at exterior corners. Glue and lock shop mitres that are over four inches (4") from heel to point. Scribe and join Work accurately together and to other Work, to fit tightly and with flat, smooth surfaces. Install trim or filler panels to close gaps. Fastening: Fasten Work with nails generally, but use screws or special fasteners at critical joints where strain, usage, and excessive shrinkage is anticipated, and where specified quality-grade standards require. Blind nail unless impossible. Set finishing nails below finished surface to receive putty. Installation of Hollow-Metal Frames: Set in place for building in. Anchor frames to floor as provided for by anchor clips. Brace frames in place to prevent displacement until permanently anchored. Remove spreaders at floor after frames are anchored. Installation of Doors: Install wood doors after finishing of walls. Install hollow-metal doors. Fit wood doors with 3/32" clearance at jambs and heads, and 3/8" over finished flooring. Trim hinge-side of wood doors to fit, and bevel latch edges as required. Ensure that top and bottom edges of wood doors are primed after they are cut to fit. Install grilles in wood doors, supplied as specified in other Sections. Undercut wood doors where indicated on Door Schedule. Installation of Finishing Hardware: Install finishing hardware. Make cuts in wood doors neatly. Accurately locate and adjust hardware to meet manufacturer's instructions. Use special tools and jigs as recommended. Install hardware, and trim square and plumb to doors.

DIVISION 7 - THERMAL AND MOISTURE PROTECTION

1. BUILDING INSULATION

- 1. Description: Work Included: New sound batt insulation for acoustic applications in walls. R-20 Batt insulation to be installed above ceiling where indicated. (Keep a minimum of 6" away from light fixtures). Materials: Glass Fibre Batts: To meet specified requirements of CSA Standard A101- Latest Edition, Type 1A, with a thermal resistance, R-value as noted on Drawings.

2. JOINT SEALANTS

- 1. Description: Work Included: Perimeter joints of exterior and interior hollow-metal door and screen frames, and of other metal-door and louver frames. Interior and exterior exposed joints, between dissimilar materials not concealed from view. Full length of exterior door saddles. Joints at top of all floor bases, counters, and cabinets. Quarry tile control joints in field panel seams and perimeter. Perimeter of power-door accessories as required. Warranty: Defective work shall include, but not be restricted to, joint leakage, hardening, cracking, crumbling, melting, bubbling, shrinkage, running, change of colour, loss of adhesion, loss of cohesion, or staining of adjoining or adjacent work or surfaces. Replacement shall include removal of defective materials, preparation and application of new material, and the repair and making good of damaged adjacent work. Materials: Sealants: Colours of sealants will be selected from manufacturer's standard range, to match abutting materials. Acrylic Solvent Release, One (1) Part, Sealant: To meet specified requirements of CGSB Specification 19-GP-5M. Silicone Sealant: One (1) Part Sealant: To meet specified requirements of CGSB Specification CAN2-19.13- Latest Edition. Two (2) Parts Polyepoxide Urethane Sealant: To meet specified requirements of CGSB Specification 19-GP-24M. Dymeric by the Tremco Manufacturing Company (Canada) Limited. Butyl sealants and tape, as recommended for copper roofing. Primer: Specifically designed for use with sealant compounds on surfaces encountered, and as specified by the compound manufacturer, to ensure adhesion of compound, and to prevent staining of substrate materials. Sealant Backing (Bedding Material): Extruded, foamed, closed-cell, round, polyethylene rod, 25 percent (25%) wider than joint width, and manufactured especially for the purpose. Void Filler: Loose glass fibre. Preparation: Remove by brushing, scrubbing, scraping, or grinding loose, all mortar, dust, oil, grease, oxidation, mill scale, coatings, and all other materials affecting bond of compounds, from surfaces to which sealant compounds must be applied to painted surfaces. Application: Prime surfaces to receive sealants, as required by substrate and manufacturer's specifications, to ensure positive and permanent adhesion, and to prevent staining. Pack joints tightly with sealant backing at depth specified for sealant. Fill other voids with filler. Caulk joints in site-painted materials after adjacent surfaces have been primed. Match compound to paint colour. Do not allow sealants to cover or spot surfaces outside of joints. Use masking tape protection to protect coating of adjacent surfaces, if necessary. Clearing: Remove sealant smears and droppings and masking tape immediately on completion of caulking. Caulking Schedule: Sealant Type 1: Dymeric Sealant or Duelflex by Stenson. Use at all locations, except where another is specified. Sealant Type 2: Mono 555 by Tremco or Acryflex by Stenson. Use at exterior joints between window and door frames and masonry. Sealant Type 3: One (1) Part Silicone Sealant. Use to seal polyethylene sheet lap joints. Sealant Type 4: Tremco Acoustical Sealant to be utilized on drywall systems for reducing acoustical sound transmission. Sealant Type 5: Butyl Tape, as recommended by copper manufacturer.

DIVISION 8 - DOORS AND WINDOWS

1. DOORS AND FRAMES

- 1. Description: Work Included: To supply and install doors and frames, as follows: Doors as scheduled. Frames as scheduled. Related work performed by other Sections: Door and hardware installations. Painting. Joint sealant. Supply of finish hardware. Building-in of frames into steel stud walls. Materials: Steel Sheet: Cold-rolled, stretcher-levelled, to meet specified requirements of ASTM Specification A366- Latest Edition or SAE Specification 1010; galvanized steel, commercial quality, to meet specified requirements of ASTM Specification A526- Latest Edition. Galvanizing: Wipod-coated sheet, zinc-wiping coating, 0.25 oz./ft.2. Organized accessories: zinc coating to meet specified requirements of CSA Standard G164- Latest Edition. Zinc-Rich Paint: To meet specified requirements of CGSB Specification 1-GP-181M. Rubber Bumpers: Single stud type. Fabrication: Prepare frames for specified hardware with mortises and reinforcement. Drill and tap to template information. Incorporate steel reinforcement of 16 ga. for locks, strikes, and flush bolts; and of 10 ga. for hinges, push-pulls, and panic devices. Doors: Fabricate doors with top and bottom channels flush and filled solid, extending full width of door, and welded to both faces. Frames: Cut mitres and joints accurately and weld continuously on inside of frame profile. Grind welded corners and joints to flat plane, fill with metallic paste filler, and sand to uniform smooth finish. Frame Installation: Set frames plumb, square, level, and at correct elevation. Secure anchorages and connections to adjacent construction. Door Installation: Install doors and hardware in accordance with hardware templates and manufacturer's instructions. Finish Repair: Touch up with primer all galvanized finishes damaged during installation. Sealants: Caulk edges of door frames to drywall surface. Colour to match frame, or approved equal.

WOOD DOORS

- 1. Description: Work Included: To supply wood doors as shown or specified. Quality Assurance: Ensure that fire-rated doors, together with specified frames, hardware, and installation, meet requirements of ULC, and attach ULC labels for specified rating. Environmental Requirements: Install doors only in areas that have dried out, and where no further installation of damp materials is contemplated. Warranty: Defective Work shall include, but not be restricted to surface blemishes, showing of core grain lines, splitting, delamination, sagging, deterioration of core, and warping and twisting in excess of deformation allowed by CSA Standard 0132-2. Latest Edition. Materials: Cores of flush doors: To meet specified requirements of CSA Standard 0132-2. Latest Edition. For solid-core doors: Wood and solid particle board with minimum 450 KG/M3 density. Wood-Veneer Facing: 3-ply, to meet specified requirements of CSA Standard 0132-2. Latest Edition. wood veneer factory stained, (Ballargeon 8500 ME). Fabrication: All doors shall be 1-3/4" thick, solid-core construction. Incorporate solid wood blocking at locations where hinges, locksets, closures, and similar hardware is installed and applied. Indicate top and hinge side on each door. Installation: Fit wood doors with 3/32" clearance at jambs and heads, and 3/8" over finished flooring or threshold. Trim hinge side of wood doors to fit, and bevel latch as required. Ensure that top and bottom edges of wood doors are primed after they are cut to fit. Install grilles, and undercut wood doors, where required.

FINISH HARDWARE

- 1. Description: Work Included: To supply finish hardware for all doors having set numbers on floor plans as scheduled and specified. Work Specified in Other Sections: To make provisions for hardware in pressed-steel frames. Rubber door bumpers. Hardware Not Included in this Section is Specified Under Work of the Following Sections: Cabinet hardware as specified. Hardware Specified in this Section is Supplied Only, and is Installed as Part of the Work of Other Sections Listed as Follows: hardware. Submittals: Schedule: Submit Finish Hardware Schedule. Identify all doors individually, to Door and Hardware Institute procedures, clearly showing hardware legend numbers used in specification. Keying Schedule: Submit Keying Schedule for review. Templates: Submit templates to Contractor for use by installers and fabricators as required for proper location and installation of hardware. Maintenance and Operating Instructions: Submit maintenance, operating, and installation instructions for installation purposes, and for incorporation in Project Data Book. Products: Work on same materials shall have consistent colour and finish throughout Project. All product finishes shall match when viewed approximately two (2) feet apart, and three (3) feet away, on the same plane, and under the same environment. All products shall be finished to Builders Hardware Manufacturers Association Product Standards. Furnish products with all necessary screws, bolts, sex bolts, expansion shields, toggle bolts, or other hardware fastening of suitable size and type to anchor the hardware in position for heavy use and long life. Material and finish of fastener shall harmonize with the hardware item. Keying: All locks to be keyed to a Master Key System as per landlord's standards. Coordinate Master Keying with aluminum door supplies. Supply four (4) master keys. Supply two (2) keys per lock. Prepare Keying Schedule in conjunction with Owner's representative, and submit to Architect for approval. Tag keys to each applicable opening before turning over to Owner.

4. GLAZING

- 1. Description: Work Included: To complete glass and glazing as shown or specified. Materials: Glass: Heat-Treated Glass: Clear tempered glass, 1/4", to meet specified requirements of CAN2-12.1- Latest Edition, Type 2, Class Transparent. One-Way Mirror Glazing: 1/4" thick as noted on drawings. Glazing Accessories: Setting Blocks: Neoprene, of durometer hardness of Shore "A" 70 to 80. Spacer Shims: Neoprene, of durometer hardness of Shore "A" 40 to 50. Glazing Sealants: One (1) Part Polysulphide Glazing Sealant: To meet specified requirements of CGSB Specification 19-GP-13M, in glazing hardness grade. Glazing Tape: Eternaflex by Gibson-Homans Co., Parflex by Parr Sealants, PC Butyl-Lock by Products Research and Chemical Corp., or Tremco 440 by the Tremco Manufacturing Company (Canada) Ltd. Mastic Compound: To meet specified requirements of CGSB Specification 19-GP-2M. Glazing Compound: To meet specified requirements of CGSB Specification 19-GP-6M. One (1) Part Acrylic Glazing Sealant: To meet specified requirements of CGSB Specification 19-GP-5M, in glazing hardness grade. One (1) Part Silicone Glazing Sealant: To meet specified requirements of CGSB Specification 19-GP-9MA, in glazing hardness grade.

DIVISION 9 - FINISHES

1. GYPSUM BOARD

- 1. Description: Work Included: To complete gypsum wallboard systems as shown or specified, but not restricted to the following: Gypsum wallboard partitions, ceilings, bulkheads, ducts, and pipe enclosures. Sound attenuation blanket. Caulking at fire-rated construction. Setting pressed-steel door frames and screens in gypsum wallboard assemblies. Installation of access panels in gypsum wallboard walls and ceilings. Quality Assurance: Requirements of Regulatory Agencies: Install fire separations and fire protection exactly as specified in Underwriters' Laboratories test design specification that validates the specified rating. Environmental Requirements: Install Work only in areas closed and protected against weather, and maintained between 10°C and 21°C. In cold weather, ensure that heat is introduced in sufficient time, before Work commences, to bring surrounding materials up to these temperatures, and that it is maintained until materials installed in this Section have cured. Do not install Work in any area unless satisfied that Work in place has dried out, and that no further installation of damp materials is contemplated. Materials: Gypsum Board: CSA A82 27- Latest Edition. Joint Material: Standard Gypsum Wallboard: With tapered edges, 1/2" thickness for walls and ceilings. Joint Reinforcing Tape: 2" x 0.012" thick, perforated paper, with chamfered edges. Joint Compounds: Latex, resin base, possessing good adhesion, mixed with fresh, unadulterated water, having no detrimental effect on compounds. Accessories: Incorporate accessories with flanges suitable for board thickness and joint finishing. Corner Beads: 25 ga. steel, wiped coated, as CGC Dur-A-Bead. Casing Beads: 25 ga. steel, wiped coated, channel shaped, as CGC No. 200A. Control Joint: Crimped roll-formed zinc, as CGC No. 093, with flanges for tape reinforcement, or two (2) casing beads, set with gap for movement, and backed with flexible air seal membrane. Fastenings and Ties: Screws: Phillips head, drywall screws, with corrosion-resistant finish, for wood framing; #6 x 1-1/4" for single-thickness board fastening, and #7 x 1-5/8" for double-thickness board fastening. Furring Strips: Carrying Channels: 1-1/2" thick, cold-rolled steel, prime painted. Furring Channels: 3/4" thick, cold-rolled steel, prime painted, hat type with knurled face. Ceiling Hangers: #9 zinc-coated, annealed, steel wire. Sealant: Acoustical Sealant: Acoustical Sealant as manufactured by Saint Gobain (Green Glue) or Tremco Manufacturing Company (Canada) Ltd. Insulation: Sound attenuation batts as manufactured by Roxul, Owens Corning or CertainTeed. Installation: R-Value as indicated on the drawings manufactured by Roxul or Owens Corning or CertainTeed. General: Coordinate the Work of this Section with that of other Sections. Do not apply drywall in close proximity to hot pipes or heating ducts. Install materials with minimum of joints. Tightly butt joints, without force, and neatly align them. Coordinate Work with Rough Carpentry Section to ensure that proper wood blocking for support of items secured to Work of this Section is installed and anchored adequately to prevent damage to Work of this Section. Consider such items as plumbing fixtures, cabinets, grabrails, handrails, and similar items, which in use, will subject wallboard to strain, and ensure that their own support has been provided. Framing and furring shown on Drawings is indicative, but do not regard it as exact or complete. Frame openings on every side with suitable sections. Provide clearances required at mechanical and electrical services, such as grilles, diffusers, access panels, and lighting fixtures, only after verification of requirements in each case. Attach to framing adequate steel reinforcing members to support the load of, and to withstand the withdrawal and shear forces imposed by, items installed upon the Work of this Section. Include in Work, bulkheads over doors, frames, screens, and changes in ceiling levels; furred beams; and pipe spaces, all as indicated on Drawings. Coordinate Work with Rough Carpentry Section to ensure that proper wood blocking for support of items secured to Work of this Section is installed and anchored adequately to prevent damage to Work of this Section. Consider such items as plumbing fixtures, cabinets, grabrails, handrails, and similar items, which in use, will subject wallboard to strain, and ensure that their own support has been provided. Framing and furring shown on Drawings is indicative, but do not regard it as exact or complete. Frame openings on every side with suitable sections. Provide clearances required at mechanical and electrical services, such as grilles, diffusers, access panels, and lighting fixtures, only after verification of requirements in each case. Attach to framing adequate steel reinforcing members to support the load of, and to withstand the withdrawal and shear forces imposed by, items installed upon the Work of this Section. Include in Work, bulkheads over doors, frames, screens, and changes in ceiling levels; furred beams; and pipe spaces; all as indicated on Drawings.

Adjustment and Cleaning

- 1. Remove droppings and excess of joint compound from Work of others, and from Work of this Section, before it sets. Make good to cut-outs for services and other Work; fill in defective joints, holes, and other depressions with joint compound. Make good defective Work, and ensure that surfaces are smooth, evenly textured, and within specified tolerances to receive finish treatments. Clean off beads, casings, and other metal trim, and leave all surfaces ready for specified finishes.

RESILIENT FLOORING

- 1. Description: Work Included: To complete interior VCT,LVT & Heterogeneous Sheet Flooring and rubber base as shown or specified. This section shall be responsible for caulking tile areas. References: CSA A126.1- Latest Edition, Vinyl Composition Floor Tile. CAN/CSA - A126.5- Latest Edition, Resilient Wall Base. CAN/CSGB-25.20- Latest Edition, Surface Sealer Floors. CAN/CSGB-25.21- Latest Edition, Detergent-Resistant Floor Polish. Quality Assurance: All work is to be performed by qualified tradesmen in strict accordance with the requirements of the National Floor Covering Association Specification Standards Manual, and the manufacturer's recommendations applicable to the type and condition of Maintenance Data & Materials: Provide maintenance data for each type of resilient tile flooring for incorporation into Operation and Maintenance Manuals. Deliver to Owner upon completion of work, and as the Owner directs, five percent (5%) of each type, pattern, and colour of flooring material, complete with adhesive required for this project, for maintenance use. Maintenance materials to be from same production run as installed materials. Clearly identify each box of floor material and each container of adhesive. Store where directed by Owner. Warranty: Provide a one (1) year extended warranty for the Work of this Specification Section beyond the expiry date of the standard one (1) year warranty stated in the General Requirements of Contract. Any and all defects in workmanship and materials shall be repaired, without cost to the Owner. Environmental Requirements: Maintain air temperature and structural base temperature at flooring installation area between 21°C and 28°C (70°F and 78°F) for seventy-two (72) hours before, during, and for forty-eight(48) hours after installation. Maintain a minimum temperature of 13°C following the above-noted period. Ensure that adequate ventilation is provided during the installation period and during the curing of adhesives. Seal off return air diffusers as directed by Architect. Examine concrete floor surfaces and ensure that the undulations are within the tolerance of 1/8 inch in 10 ft. (3 mm in 3 metres). Ensure that concrete floors, on grade, or suspended floors (18 inches) are well vented, dry (maximum 2.5% moisture content or less than 75% RH) and exhibit negative alkalinity carbonization or dusting. Ensure no additives have been used in the concrete which could affect adhesion when laying.

organica studio + inc. architecture | interiors | design | research




Table with 2 columns: NO. and DESCRIPTION. Row 1: 1. ISSUED FOR TENDER CLIENT REVIEW. Row 2: 2. ISSUED FOR TENDER CONSTRUCTION. Row 3: 3. ISSUED FOR TENDER BIDDING.

SPECIFICATIONS KITCHENETTE DESIGN. SCALE 1"=1'-0". DATE 2024-12-09 12:47:29 PM. DRAWN VK. CHECKED JN. PROJECT NUMBER 24016. SHEET ID9.1

FILE NAME: X:\Opendoc\Polym\2024\24016 - 8141 Martin Grove Rd. - 8141 Martin Grove Rd. - 8141 Martin Grove Rd. PROJ DATE: 2024-12-09 12:47:29 PM







