



STAFF WASHROOM



BOYS WASHROOM



GIRLS WASHROOM

HWDSB

P02125 - Lake Avenue Elementary School

Washrooms & Changerooms Renovations

157 Lake Ave N, Hamilton ON



E & M  
Consulting Engineers Inc.



DRAWING LIST

ARCHITECTURAL DRAWINGS

- SHEET
- A0.01 COVER PAGE  
A1.01 SITE LOCATION, OBC MATRIX, GENERAL NOTES, LEGENDS, SCHEDULES  
A1.02 KEY PLAN & STANDARDS  
A1.03 DEMOLITION PLAN & NOTES  
A1.04 PROPOSED PLAN, CEILING PLAN, LEGENDS  
A2.01 INTERIOR ELEVATIONS, SECTIONS, SECTION DETAILS, SCHEDULES, DOOR & DOOR FRAME TYPE

MECHANICAL DRAWINGS

- M0-00 MECHANICAL LEGEND & DRAWING LIST  
M1-00 PLUMBING SYSTEMS - DEMOLITIONPLAN  
M1-01 HVAC SYSTEMS - DEMOLITION PLAN  
M2-00 PLUMBING SYSTEMS- NEW ENLARGED PLAN  
M2-01 HVAC SYSTEMS- NEW ENLARGED PLAN  
M3-00 DETAIL  
M4-00 MECHANICAL SPECIFICATIONS  
ME1-00 MECHANICAL & ELECTRICAL SCHEDULES

ELECTRICAL DRAWINGS

- E0-00 ELECTRICAL LEGEND & DRAWING LIST  
E1-01 ENLARGED PLANS DEMO - ELECTRICAL  
E2-01 ENLARGED PLANS NEW - ELECTRICAL  
E3-00 ELECTRICAL SPECIFICATIONS  
ME1-00 MECHANICAL & ELECTRICAL SCHEDULES

STRUCTURAL DRAWINGS

- S1.0 GENERAL NOTES  
S2.0 FRAMING PLAN WASHROOMS & CHANGEROOMS  
S3.0 MASONRY SCHEDULES & TYPICAL DETAILS


project number

24-28

DRAWING NO.

A0.01







**SITE LOCATION**  
SCALE: N.T.S.

**PARTITION SCHEDULE**


NEW PARTITIONS TO THE UNDERSIDE OF EXISTING STRUCTURAL SLAB ABOVE UNLESS NOTED OTHERWISE



P1 • +/- 3800MM HEIGHT 140MM CONCRETE BLOCK




P2 • +/- 3800MM HEIGHT 90MM CONCRETE BLOCK




P3 • +/- 3800MM HEIGHT 190MM CONCRETE BLOCK

**CEILING SCHEDULE**



ACT1 • 610 x 1220 ACOUSTIC CEILING TILES




GB1 • 64 STEEL STUD FRAMING @ 400MM O.C.  
• 13 GYPSUM BOARD

**REFLECTED CEILING PLAN LEGEND**


REFER TO ELECTRICAL AND MECHANICAL DRAWINGS FOR DETAILED FIXTURE INFORMATION.




305 X 1220 (1'X4') LED FLAT  
PANEL LIGHTING FIXTURE



NEW 610 X 1220 ACOUSTIC  
CEILING TILES IN SUSPENDED  
PREFINISHED METAL GRID



NEW GYPSUM BOARD CEILING



NEW DIFFUSER

- NOTE:
1. LIGHT FIXTURES TO BE CENTRED WITHIN ROOMS UNLESS DIMENSIONED OTHERWISE, TYPICAL
  2. DIMENSIONS ARE TAKEN TO THE CENTRE OF LIGHT FIXTURES, TYPICAL

**Name of Practice:**  
AMRA J Architects Inc.  
63 Stowbridge Cres.  
Ancaster, ON  
L9G 3E1  
[info@aja.design](mailto:info@aja.design)  
905-920-5121

**Name of Project:**  
P02125 Lake Avenue Elementary School Washroom & Changeroom Renovations

**Location:**  
157 Lake Avenue North, Hamilton, ON, L8E 1L5

**Date:** 11/20/2024

Ontario Building Code Data Matrix Part 11 – Renovation of Existing Building					Building Code Reference <sup>1</sup>	
11.00	Building Code Version:	O_Reg_332/12		Last Amendment	O_Reg_191/14	
11.01	Project Type:	<div><input type="checkbox"/> Addition    <input checked="" type="checkbox"/> Renovation    <input type="checkbox"/> Addition and renovation</div> <div><input type="checkbox"/> Change of use</div> <div>Description:    Interior Renovation of Existing Changerooms and Shower Rooms</div>				[A] 1.1.2.
11.02	Major Occupancy Classification:	Occupancy	Use			3.1.2.1.(1)
		A-2	Elementary School			
11.03	Superimposed Major Occupancies:	<div><input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> <div>Description: </div>				3.2.2.7.
11.04	Building Area (m²)	Description:		Existing	New	Total
	<small>Insert additional lines as needed</small>	Existing School		5,480	0	5,480
11.05	Building Height	1    Storeys above grade		Existing	(m) Above grade	
		0    Storeys below grade				
11.06	Number of Streets/ Firefighter access	Existing_street(s)				3.2.2.10. & 3.2.5.
11.07	Building Size	<div><input type="checkbox"/> Small    <input type="checkbox"/> Medium    <input checked="" type="checkbox"/> Large    <input type="checkbox"/> &gt; Large</div>				T.11.2.1.1.B-N.
11.08	Existing Building Classification:	Change in Major Occupancy: <input type="checkbox"/> Yes <input checked="" type="checkbox"/> Not Applicable (no change of major occupancy)				11.2.1.1.
		Construction Index: -				T.11.2.1.1A
		Hazard Index: -				T.11.2.1.1B to N
		Importance Category : <input type="checkbox"/> Low <input type="checkbox"/> Normal <input type="checkbox"/> High <input type="checkbox"/> Post-disaster				4.2.1.(3), 5.2.2.1.(2)
11.09	Renovation type:	<div><input checked="" type="checkbox"/> Basic Renovation    <input type="checkbox"/> Extensive Renovation</div>				11.3.3.1, 11.3.3.2.
11.10	Occupant Load	Floor_Level/Area	Occupancy Type	Based On	Occupant Load (Persons)	
	<small>Insert additional lines as needed</small>	1 storey – 5,480	A-2	persons	810	
11.11	Plumbing Fixture Requirements	Ratio:    30 males per fixture, 26 females per fixture				3.7.4.
		Floor_Level/Area	Occupant Load	OBC Reference	Fixtures Required	Fixtures Provided
		1	405 M	3.7.4.3.(14)	14	22
	<small>Insert additional lines as needed</small>	1	405 F	3.7.4.3.(14)	16	19
						(18 Ex. 4 New)
						(15 Ex. 4 New)
11.12	Barrier-free Design:	<div><input checked="" type="checkbox"/> Yes</div> <div><input type="checkbox"/> No</div>				11.3.3.2.(2)
11.13	Reduction in Performance Level:	Structural: <div><input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> <div>By Increase in occupant load: <input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> <div>By change of major occupancy: <input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> <div>Plumbing: <input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> <div>Sewage-systems: <input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> <div>Extension of combustible construction: <input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div>				11.4.2.1, 11.4.2.2, 11.4.2.3, 11.4.2.4, 11.4.2.5, 11.4.2.6.
11.14	Compensating Construction:	<div><input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> <div>Structural: <div><input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> -</div> <div>Increase in occupant load: <input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> - <div>Change of major occupancy: <input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> - <div>Plumbing: <input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> - <div>Sewage systems: <input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> - <div>Extension of combustible construction: <div><input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> -</div>				11.4.3.1, 11.4.3.2, 11.4.3.3, 11.4.3.4, 11.4.3.5, 11.4.3.6, 11.4.3.7.
11.15	Compliance Alternatives Proposed:	<div><input checked="" type="checkbox"/> No    <input type="checkbox"/> Yes</div> -				11.5.1.
11.16	Notes:	<div>The scope of work is renovation of the existing change rooms and shower rooms to provide additional washrooms.</div> <div>The total area of renovation is 159 Sq. M.</div> <div>There is no change in occupant load and occupancy classification.</div>				11.5.1.
	<small>Insert additional lines as needed</small>					

<sup>1</sup> All references are to Division B of the OBC unless preceded by (A) for Division A and (C) for Division C.

**SYMBOL LEGEND**

- 0 STRUCTURAL GRID
- ELEVATION NAME ELEVATION REFERENCE
- 1 A01 SECTION REFERENCE
- 1 A100 DETAIL REFERENCE
- 2 A100 3 EXTERIOR ELEVATION REFERENCE
- 1-B A100 1-C 1-D INTERIOR ELEVATION REFERENCE
- EL SPOT ELEVATION
- ? DEMOLITION / CONSTRUCTION TAG
- ROOM NAME 101 ROOM TAG
- D100 DOOR TAG
- W1 WALL TAG
- C1 XXX CEILING TAG
- W1 WINDOW / SCREEN TAG
- 1i FLOOR TAG
- R1 ROOF TAG
- # REVISION TAG

**ABBREVIATION LEGEND**

**STANDARDS**

A.F.F. ABOVE FINISHED FLOOR  
c/w COMPLETE WITH  
DN DOWN  
EL ELEVATION  
EX EXISTING  
EXP EXPOSED  
FIN FINISHED  
FTG FOOTING  
G.C. GENERAL CONTRACTOR  
GL GRID LINE  
GR GUARDRAIL  
HR HANDRAIL  
H.D.G. HOT DIPPED GALVANIZED  
N.I.C. NOT IN CONTRACT  
N.T.S. NOT TO SCALE  
SIM SIMILAR  
STRU. STRUCTURE  
T/ TYPICAL  
u/s UNDERSIDE

**MATERIAL**

ACT ACOUSTICAL CEILING TILE  
CAR CARPET  
CMU CONCRETE MASONRY UNIT  
CONC CONCRETE  
GB GYPSUM BOARD  
GW GEORGIAN WIRE  
HM HOLLOW METAL  
INT INTEGRAL  
PT PAINT  
RB RUBBER BASE  
SC SOLID CORE  
SHT SHEET  
S.S. STAINLESS STEEL  
ST STAIN  
TG TEMPERED GLASS  
VCT VINYL COMPOSITE TILE

**WASHROOM ABBREVIATIONS**

CH COAT HOOK  
CT # CERAMIC TILE  
(NUMBER SUFFIX DENOTES COLOUR OF TILE, REFER TO LEGEND)  
HD HAND DRYER  
(SEE ELECTRICAL DWGS)  
PTD PAPER TOWEL DISPENSER  
SD SOAP DISPENSER  
TPD TOILET PAPER DISPENSER  
GB1 HORIZONTAL GRAB BAR  
GB2 L-SHAPED GRAB BAR  
GB3 VERTICAL GRAB BAR  
ND NAPKIN DISPOSAL  
MR MIRROR  
TD TRASH DISPOSAL  
PS PRIVACY SCREEN  
SH SHELF  
WB WATER BOTTLE FILLER  
ADO AUTOMATIC DOOR OPERATOR  
FD FLOOR DRAIN (REFER TO MECH)  
EPCB EPOXY COVE BASE C/W CAP

**GENERAL NOTES & SPECIFICATIONS**

THE PROJECT SCOPE INCLUDES PARTIAL RENOVATION OF THE EXISTING SCHOOL AT 157 LAKE AVE N, HAMILTON ON, AS REQUIRED TO PROVIDE MORE STUDENTS WASHROOMS. THE GENERAL CONTRACTOR SHALL BE AWARE THAT 157 LAKE AVE NORTH IS AN OCCUPIED SCHOOL, AND THAT ALL WORK IN THE CORRIDORS AND LOBBIES WILL BE UNDERTAKEN AFTER SCHOOL HOURS IN ORDER TO MINIMIZE DISRUPTION TO STUDENTS AND STAFF.

THE CONTRACTOR SHALL NOTE THAT THE APPROX. TOTAL AREA OF WORK IS 140 SQ. M. (70 SQ. M FOR THE BASE BID AND 70 SQ. M FOR THE ALTERNATIVE COST 1). THE CONTRACTOR SHALL REFER TO ALL DRAWINGS INCLUDING STRUCTURAL, MECHANICAL, ELECTRICAL, ARCHITECTURAL & THE GENERAL NOTES FOR THE FULL SCOPE OF WORK.

THE PROJECT SCOPE INCLUDES PARTIAL INTERIOR RENOVATIONS IN THE EXISTING GIRLS CHANGEROOM & BOYS CHANGEROOM TO ADD MORE STUDENTS WASHROOM AND TWO NEW SINGLE USE WASHROOMS AS REQUIRED.

THE GENERAL CONTRACTOR SHALL MAINTAIN AT ALL TIMES DURING CONSTRUCTION A MINIMUM OF TWO PATHS OF EXIT, AND SHALL CONDUCT CONSTRUCTION IN A MANNER SUCH THAT THERE ARE MINIMAL TO NO DISTURBANCE TO THE DAY-TO-DAY OPERATION OF THE SCHOOL.

ALL WORK TO BE CARRIED OUT IN ACCORDANCE WITH THE LATEST EDITION OF THE LOCAL, PROVINCIAL AND FEDERAL CONSTRUCTION AND BUILDING CODES, THE NATIONAL FIRE CODE, THE OCCUPATIONAL HEALTH AND SAFETY ACT, AND ANY OTHER AUTHORITIES HAVING JURISDICTION.

THE GENERAL CONTRACTOR SHALL COMPLY WITH ALL THE REQUIREMENTS WITH RESPECT TO CONSTRUCTION PROCEDURES, INSURANCE, SECURITY, BUILDING ACCESS, LIFE SAFETY & FIRE REGULATIONS, SECURITY CLEARANCES OF EMPLOYEES, HOISTING, GARBAGE REMOVAL, ETC., AS SET OUT BY THE SCHOOL BOARD/CLIENT AND INSTRUCTIONS TO BIDDERS.

THE CONTRACTOR SHALL READ THE DRAWINGS PROVIDED IN CONJUNCTION WITH SPECIFICATIONS & INSTRUCTIONS ON THE BID DOCUMENTS. ANY DISCREPANCIES OR OMISSIONS ON ANY DRAWINGS OR SPECIFICATIONS ARE TO BE REPORTED TO THE CONSULTANT PRIOR TO COMMENCEMENT OF WORK.

THE GENERAL CONTRACTOR IS RECOMMENDED TO FAMILIARIZE THEMSELVES WITH EXISTING SITE CONDITIONS DURING DESIGNATED SITE VISIT DATE OR OTHERWISE OBTAIN INFORMATION REQUIRED TO SUBMIT A FIRM QUOTATION. CONTRACTORS WILL NOT BE ALLOWED TO VISIT THE SITE PRIOR TO OR AFTER THE DESIGNATED SITE VISIT DATE.

ALL DIMENSIONS ARE CLEAR UNLESS OTHERWISE NOTED. CONTRACTOR TO FIELD VERIFY ALL DIMENSIONS AND ELEVATIONS PRIOR TO CONSTRUCTION AND REPORT DISCREPANCIES TO CONSULTANT PRIOR TO MAKING MODIFICATIONS TO SUIT EXISTING SITE CONDITIONS.

ALL MATERIALS SPECIFIED ARE TO BE INSTALLED, FINISHED & SEALED IN ACCORDANCE WITH THE MANUFACTURER'S RECOMMENDATIONS & SPECIFICATIONS.

ALL MATERIALS SHALL BE AS SPECIFIED. CONTRACTOR MUST OBTAIN WRITTEN APPROVAL FROM ARCHITECT FOR ANY MATERIAL OR FINISH SUBSTITUTES OR ALTERNATIVES.

ALL MATERIALS AS SUPPLIED AND INSTALLED IN THIS PROJECT MUST MEET THE SMOKE/FLAME SPREAD RATING AS SPECIFIED IN THE BUILDING CODE.

THE CONTRACTOR SHALL ENSURE ALL AREAS ARE SEALED AGAINST DUST & SECURED WITH SAFETY WALLS/SHOARDING. DAMAGES TO EXISTING MATERIALS, WINDOWS, FURNISHINGS, EQUIPMENT, BASE BUILDING FINISHES WITHIN AND OUTSIDE THE "AREA OF WORK" WILL BE THE FULL RESPONSIBILITY OF THE CONTRACTOR TO REPLACE WITHOUT ADDITIONAL COSTS.

THE "AREA OF WORK" IS DEFINED AS THE IMMEDIATE AREAS WHERE DEMOLITION AND NEW CONSTRUCTION OCCURS BUT MAY NOT BE COMPLETELY LIMITED TO THE AREA DEFINED WITHIN.

THE CONTRACTOR IS RESPONSIBLE FOR THE SUPPLY AND INSTALLATION OF ANY MATERIALS NOT SPECIFICALLY INDICATED BUT REASONABLY IMPLIED AND NECESSARY FOR COMPLETION OF WORK WITH NO ADDITIONAL COSTS UNDER HIS OR HER CONTRACT.

TO MINIMIZE DUST TRAVEL, ALL SUPPLY AIR DIFFUSERS & EXHAUST AIR GRILLED TO BE SEALED IN AREAS OF DEMOLITION AND CONSTRUCTION.

THE CONTRACTOR SHALL PATCH AND REPAIR AND/OR SKIM COAT AT DAMAGES, PUNCTURES, AND OTHER IRREGULARITIES ON EXISTING WALLS, FLOORS, AND CEILINGS, WHERE DAMAGES ARE EXISTING OR CAUSED BY DEMOLITION. THE CONTRACTOR SHALL ENSURE A SMOOTH AND EVEN SURFACE TO THE SATISFACTION OF THE ARCHITECT, IN PREPARATION FOR NEW FINISH APPLICATIONS AS SPECIFIED.

THE CONTRACTOR IS TO COORDINATE ANY WATER/ELECTRICITY SHUTOFF WITH THE OWNER AT LEAST 72 HOURS IN ADVANCE TO WORK COMMENCING.

IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO DESIGN ALL SHORING AND TEMPORARY BRACING AS PER O REG 213/91 AND THE CONTRACTOR SHALL RETAIN AN ENGINEER AS REQUIRED. ANY NEW OPENINGS WITHIN THE EXISTING BLOCK WALLS WILL REQUIRE TEMPORARY SHORING.

**DEMOLITION**

DEMOLISH AND REMOVE ALL WALLS, FLOORING, CEILINGS, DOORS C/W DOOR FRAMES, TOILET PARTITIONS, WASHROOM & SHOWER ACCESSORIES, SINKS, AND COUNTERTOPS AS INDICATED ON THE DEMOLITION DRAWINGS. REPAIR AND RESTORE ALL AFFECTED EXISTING SURFACES.

**NEW CONSTRUCTION**

THE NEW CONSTRUCTION SCOPE INCLUDES RENOVATING EXISTING BOYS AND GIRLS CHANGEROOM TO CREATE A GROUP WASHROOM WITH BARRIER-FREE STALLS, 2 NEW SINGLE USE WASHROOMS, AND TO ADD A STORAGE ROOM AS SHOWN ON THE PROPOSED FLOOR PLANS. THE GENERAL CONTRACTOR SHALL FIELD-VERIFY ALL DIMENSIONS BEFORE THE START OF CONSTRUCTION AND TO INFORM ARCHITECT FOR ANY DISCREPANCIES BEFORE THE START OF THE CONSTRUCTION.


INSTALL 3M™ CRYSTAL GLASS FINISHES, 772SSE-324 FILM ON EXISTING WINDOW SCREENS AS SHOWN IN THE PLANS. CONTRACTOR TO SITE VERIFY SIZE OF EXISTING SCREENS.

**DRAWING LEGEND**

- EXISTING
- AREA OF WORK
- GYPSUM BOARD PARTITIONS
- MASONRY
- BRICK
- EXISTING WALL TO REMAIN
- EXISTING TO BE DEMOLISHED
- DOORS TO BE DEMOLISHED
- EXISTING DOORS TO REMAIN
- NEW DOORS

DO NOT SCALE DRAWING. DIMENSIONS ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON-SITE.

ALL DRAWINGS, SPECIFICATIONS, AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE ARCHITECT AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS, AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE ARCHITECT'S WRITTEN PERMISSION.




2	ISSUED FOR TENDER	25/03/25
0	ISSUED FOR BUILDING PERMIT	25/02/28

No.	DESCRIPTION	DATE
-----	-------------	------

REVISIONS

SEAL:

**HWDSB**



project title:

P02125 - Lake Avenue Elementary School Washrooms & Changerooms Renovations


drawing title:

SITE LOCATION, OBC MATRIX, GENERAL NOTES, LEGENDS, SCHEDULES


drawn: RMC date: 11/2024	scale: As indicated project number: 24-28
-----------------------------------	--

checked: AJ date: 12/2024	DRAWING NO: <b>A1.01</b>	<b>2</b> Revision
------------------------------------	-----------------------------	----------------------







TYP. BF URINAL STALL PLAN DETAIL



**TYPICAL WASHROOM STALL PLAN DETAIL**  
SCALE: 1:20




**TYPICAL BF STALL PLAN DETAIL** 3  
SCALE: 1:20 A1.02



**TYPICAL WASHROOM FIXTURES MOUNTING HEIGHT**

SCALE: 1:20

2  
A1.02




**KEY PLAN**  
SCALE: 1:300

1  
A1.02

DO NOT SCALE DRAWING. DIMENSIONS ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE			
ALL DRAWINGS, SPECIFICATIONS, AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE ARCHITECT AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS, AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE ARCHITECT'S WRITTEN PERMISSION			
2	ISSUED FOR TENDER	25/03/25	
0	ISSUED FOR BUILDING PERMIT	25/02/28	
No.	DESCRIPTION	DATE	
REVISIONS			
SEAL:			
project title:			
<p>P02125 - Lake Avenue Elementary School Washrooms &amp; Changerooms Renovations</p>			
drawing title:			
<p>KEY PLAN &amp; STANDARDS</p>			
drawn:	scale:		
RMC	As indicated		
date:	project number:		
02/19/25	24-28		
checked:	DRAWING NO.		Revision
AJ	A1.02		2
date:	Revision		
12/20/24			



DEMOLITION NOTES	
Number	Description
①	REMOVE EXISTING MASONRY WALLS & DOORS CW/ DOOR FRAME AS APPLICABLE.
②	REMOVE AND SALVAGE EXISTING WALL MTD BENCHES & EXISTING  SHELVES CW/ HOOKS. COORDINATE WITH CLIENT FOR THE STORAGE AND REINSTALLATION.
③	MAKE WALL OPENING AS REQUIRED FOR THE ENTRANCE TO THE NEW GROUP WASHROOMS/ NEW DOOR. REFER TO STRUCTURAL DESIGN FOR NEW LINTEL.
④	REMOVE ALL EXISTING PLUMBING FIXTURES C/W WASHROOM PARTITIONS & SALVAGE ALL EXISTING ACCESSORIES INCLUDING BUT NOT LIMITED TO SOAP DISPENSERS, PAPER TOWEL DISPENSERS, GRAB BARS, AND NAPKIN DISPOSAL. REFER TO MECHANICAL DWGS FOR THE PLUMBING DEMOLITION.
⑤	REMOVE EXISTING VCT FLOORING AND RUBBER BASE.
⑥	REMOVE EXISTING ACT CW/ EXISTING LIGHTS & DIFFUSERS. COORDINATE WITH MECHANICAL AND ELECTRICAL DEMOLITION.
⑦	REMOVE EXISTING GB CEILING C/W EXISTING LIGHT FIXTURES.
⑧	REMOVE EXISTING WALL TILES C/W EXISTING SHOWER FIXTURES AS APPLICABLE. CAREFUL NOT TO DAMAGE EXISTING MASONRY WALL AFFECTED AND MAKE GOOD FOR PAINT FINISH.
⑨	REMOVE EXISTING FLOOR TILES.
⑩	CAREFULLY REMOVE EXISTING DOOR & FRAME AND PREPARE OPENING FOR MASONRY INFILL.
⑪	REMOVE EXISTING DRINKING FOUNTAIN.
⑫	CAREFULLY REMOVE EXISTING DOOR & FRAME. CAREFUL NOT TO DAMEGE EXISTING WALL AND OTHER ADJACENT SURFACES.
⑬	AT THE AREA OF WHICH EXISTING PIPES HAS BEEN REMOVED, PATCH AND REPAIR EXISTING FLOORING AS REQUIRED. (REFER TO MECHANICAL DWGS)
⑭	SALVAGE EXISTING CEILING TILE/ CEILING TILES AS REQUIRED FOR THE REMOVAL OF EXISTING PIPE. (REFER TO MECHANICAL DWGS) CORRDINATE WITH THE CLIENT FOR THE STORAGE AND REINSTALLATION.
⑮	CAREFULLY REMOVE EXISTING BULKHEAD.
⑯	CAREFULLY REMOVE EXISTING VCT BASE AND PREPARE AREA TO RECEIVE NEW VCT BASE.
⑰	REVIEW MECHANICAL DESIGN FOR THE EXTENT OF OPENINGS TO BE FILLED AFTER REMOVAL OF EXISTING SERVICES AND SIZE/LOCATION OF NEW OPENINGS



DEMOLITION PLAN  
SCALE: 1 : 50

1  
A1.02

DO NOT SCALE DRAWING. DIMENSIONS ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON-SITE.

ALL DRAWINGS, SPECIFICATIONS, AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE ARCHITECT AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS, AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE ARCHITECT'S WRITTEN PERMISSION.

2	ISSUED FOR TENDER	25/03/25
0	ISSUED FOR BUILDING PERMIT	25/02/28
No.	DESCRIPTION	DATE

REVISIONS

SEAL:

**HWDSB**


**AMRA J**  
ARCHITECTS INC.

project title:  
P02125 - Lake Avenue Elementary School Washrooms & Changerooms Renovations

drawing title:  
DEMOLITION PLAN & NOTES

drawn: RMC	scale: As indicated
date: 02/18/25	project number: 24-28
checked: AJ	DRAWING NO: A1.03
date: 12/2024	Revision: 2






PROPOSED REFLECTED CEILING  
SCALE: 1 : 50

2

A2.0



PROPOSED NEW FLOOR PLAN  
SCALE: 1:50

1

A1


SEE MECHANICAL AND ELECTRICAL DRAWINGS AND COORDINATE  
ANY DISCREPANCIES BEFORE CONSTRUCTION

AT REMOVED LOUVERS, INFILL EXISTING OPENING USING:  
140 mm BLOCK  
75 mm CLOSED CELL SPRAY FOAM (R18)  
AIR SPACE  
90 mm FACE BRICK (REUSE BRICK FROM NEW LOUVER OPENING)

ACCESS PANEL AP

DO NOT SCALE DRAWING. DIMENSIONS ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE.

ALL DRAWINGS, SPECIFICATIONS, AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE ARCHITECT AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS, AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE ARCHITECT'S WRITTEN PERMISSION.



2	ISSUED FOR TENDER	25/03/25
0	ISSUED FOR BUILDING PERMIT	25/02/28
No.	DESCRIPTION	DATE

SEAL

**HWDSB**



project title	
---------------	--


P02125 - Lake Avenue Elementary  
School  
Washrooms & Changerooms  
Renovations

drawing title:  
PROPOSED PLAN, CEILING PLAN  
LEGENDS

drawn: <b>RMC</b>	scale: <b>As indicated</b>	
date: <b>11/14/24</b>	project number: <b>24-28</b>	
checked: <b>AJA</b>	<b>DRAWING NO:</b> <b>A1.04</b>	<b>2</b>
date: <b>12/2024</b>		

Review











DOOR SCHEDULE												
DIVISION	TYPE	DOOR			FRAME							HARDWARE & REMARKS
		WIDTH	HEIGHT	THICKNESS	MATERIAL	FINISH	TYPE	MATERIAL	FINISH	GLAZING	F.R.F. (MIN)	
D138A-A	A	950	2135	45	HM	PTD	F1	HM	PTD	N/A	45	REFER TO SPEC BOOK
D138B-A	A	950	2135	45	HM	PTD	F1	HM	PTD	N/A	45	REFER TO SPEC BOOK
D138C-A	A	950	2135	45	HM	PTD	F1	HM	PTD	N/A	45	REFER TO SPEC BOOK

ROOM FINISH SCHEDULE							COMMENTS
ROOM NO.	ROOM NAME	FLOOR FINISH	BASE FINISH	WALL FINISH	FINISH	CEILING HEIGHT	
136	GIRLS CHANGEROOM	VCT	RB	PT	ACT	2700	
136A	BOYS WASHROOM	EPOXY	EPCB	PT	GB	2700	
136B	GIRLS WASHROOM	EPOXY	EPCB	PT	GB	2700	
138	BOYS CHANGEROOM	VCT	RB	PT	ACT	2700	
138A	STORAGE	VCT	RB	PT	ACT	2700	
138B	STAFF WASHROOM	EPOXY	EPCB	PT	GB	2700	
138C	STAFF WASHROOM	EPOXY	EPCB	PT	GB	2700	

REPLACE EXISTING VCT BASE IN CORRIDORS 133 & 134 TO MATCH EXISTING.



DO NOT SCALE DRAWING. DIMENSIONS ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE.

ALL DRAWINGS, SPECIFICATIONS, AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE ARCHITECT AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS, AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE ARCHITECT'S WRITTEN PERMISSION.

2	ISSUED FOR TENDER	25/03/25
0	ISSUED FOR BUILDING PERMIT	25/02/28
No.	DESCRIPTION	DATE

REVISIONS

SEAL:

**HWDSB**

**AMRA J**  
ARCHITECTS INC.









































































































































































project title:  
P02125 - Lake Avenue Elementary School Washrooms & Changerooms Renovations

drawing title:  
INTERIOR ELEVATIONS, SECTIONS, SECTION DETAILS, SCHEDULES, DOOR & DOOR FRAME TYPE

drawn: RMC date: 12/13/24	scale: As indicated project number: 24-28
checked: AJ date: 12/2024	DRAWING NO: <b>A2.01</b> Revision: <b>2</b>



## MECHANICAL LEGEND

VENTILATION LEGEND		PIPING LEGEND		PLUMBING		SPRINKLER LEGEND		MISCELLANEOUS ABBREVIATIONS		
	SOUND INSULATION		HEATING WATER SUPPLY		STORM DRAIN ABOVE GRADE (STM)		UPRIGHT SPRINKLER	EX	- EXISTING TO REMAIN.	
	SILENCER		HEATING WATER RETURN		SANITARY ABOVE GRADE (SAN)		PENDANT SPRINKLER	ER	- EXISTING TO BE RELOCATED.	
	FLEXIBLE CONNECTION		CHILLED WATER SUPPLY		STORM DRAIN BURIED (STM)		UPRIGHT SPRINKLER w/GUARD	RE	- RELOCATED DEVICE AT NEW LOCATION	
	DUCT OFFSET		CHILLED WATER RETURN		SANITARY BURIED (SAN)		PENDANT SPRINKLER w/GUARD	R	- EXISTING TO BE REMOVED	
	BALANCING DAMPER		GLYCOL WATER RETURN		WEEPING TILE		UPRIGHT HI-TEMP. SPRINKLER	N	- ITEMS TO BE REPLACED WITH NEW	
	FIRE DAMPER		GLYCOL WATER RETURN		DOMESTIC COLD WATER (DCW)		PENDANT HI-TEMP. SPRINKLER	///	- ITEMS TO BE PERMANENTLY OR TEMPORARILY DEMOLISHED. SEE DRAWING NOTES FOR DETAILS	
	SPLITTER DAMPER		EQUIPMENT CONDENSATE DRAIN LINE		DOMESTIC HOT WATER (DHW)		UPRIGHT HI-TEMP. SPRINKLER w/GUARD			
	BACKDRAFT DAMPER		NATURAL GAS		DOMESTIC HOT WATER RECIRC (DHWRC)		PENDANT HI-TEMP. SPRINKLER w/GUARD			
	MOTORIZED DAMPER		SUCTION LINE		DOMESTIC TEMPERED WATER (TW)		DRY PENDANT SPRINKLER			
	SUPPLY DUCT SECTION		LIQUID LINE		DOMESTIC TEMPERED WATER RECIRC (TWR)		DRY PENDANT SPRINKLER w/GUARD			
	RETURN DUCT SECTION		VENT LINE		GLYCOL SUPPLY		RECESSED SPRINKLER			
	SUPPLY DIFFUSER		FIRE LINE		GLYCOL RETURN		CONCEALED SPRINKLER			
	EXHAUST GRILLE		COMPRESSED AIR		CONDENSATE		HORIZONTAL SIDEWALL SPRINKLER			
	DIFFUSER DESIGNATION AND L/S		DRAIN PIPE		EXPANSION		EXTENDED COVERAGE SIDEWALL SPRINKLER			
	GRILLE DESIGNATION AND L/S		SPRINKLER PIPE		CLEANOUT(ABOVE FLOOR)		FLOW SWITCH			
	CAPPED END DUCT		PIPE ANCHOR		CLEANOUT(UNDERGROUND)		PRESSURE SWITCH OR SENSOR			
	DUCT REDUCER/ENLARGER		PIPE GUIDE OR SLEEVE		AREA DRAIN		APPROVED DOUBLE CHECK VALVE BACKFLOW PREVENTOR ASSEMBLY			
	TRANSITION  TO  ROUND		EXPANSION COMPENSATOR c/w GUIDES		FLOOR DRAIN		ELECTRICALLY MONITORED SHUT-OFF VALVE			
	CARBON MONOXIDE DETECTOR		BOTTOM TAKE-OFF		FUNNEL FLOOR DRAIN		CHECK VALVE			
	AIR FLOW		TOP TAKE-OFF		HUB DRAIN		ALARM CHECK VALVE			
	DUCT REDUCER		ELBOW UP		ROOF DRAIN		SPRINKLER RISER			
	AIR FLOW DIRECTIONS		ELBOW DOWN		FIRE EXTINGUISHER		SIAMESE FIRE DEPT. CONNECTION			
ABBREVIATIONS			VALVE - SEE SPECIFICATIONS		FIRE EXTINGUISHER c/w CABINET		WATER GONG			
EF	- EXHAUST FAN		UNION CONNECTION		SHOWER (HANDICAPPED)		FIRE LINE			
SF	- SUPPLY FAN		FLANGED CONNECTION		SHOWER		HORIZONTAL SIDEWALL SPRINKLER W/GUARD			
CF	- CEILING FAN		PLUG CAP		RUNNING TRAP	VALVE LEGEND				
WL	- WEATHER LOUVRE		FLEXIBLE CONNECTION		NON- FREEZE HOSE BIBB		VALVE - SEE SPEC			
CU	- CONDENSING UNIT		THERMOMETER		HOSE BIBB		CHECK VALVE			
FCU	- FAN COIL UNIT		PRESSURE GAUGE		PIPE REDUCER		STRAINER			
MUA	- MAKE UP AIR		AIR VENT		PUMP AND DESIGNATION		PRESSURE REDUCING VALVE (PRV)			
AC	- AIR CONDITIONING		AUTOMATIC AIR VENT		KITCHEN EQUIPMENT IDENTIFICATION		LOCK SHIELD VALVE			
ERV	- ENERGY RECOVERY VENTILATOR		FLOW SWITCH		PLUMBING RISER		2-WAY CONTROL VALVE (TCV)			
BS	- BRANCH SELECTOR		THERMOSTAT		ABBREVIATIONS		3-WAY CONTROL VALVE (TCV)			
LT	- LINT TRAP		THERMOSTAT w/GUARD		HS	- HOSE STATION		RELIEF VALVE		
VAV	- VARIABLE AIR VOLUME		HUMIDITY SENSOR		FHC	- FIRE HOSE CABINET		CIRCUIT BALANCE VALVE (CBV)		
BF	- BOOSTER FAN		FAN CONTROLLERS/SWITCHES		RWL	- RAIN WATER LEADER		PLUG VALVE		
VRF	- VARIABLE REFRIGERANT FLOW		CABINET HEATERS "CH"		WC	- WATER CLOSET		SOLENOID VALVE		
UH	- UNIT HEATER		CONTINUOUS CONVECTORS "WF"		WCH	- WATER CLOSET (HANDICAPPED)		NORMALLY CLOSED VALVE		
DS	- DUCT SUPPORT		RADIANT PANELS "RP"		L	- LAVATORY				
SD	- SMOKE DETECTOR		TEMPERATURE SENSOR		LH	- LAVATORY (HANDICAPPED)				
GEN E/A	- GENERAL EXHAUST AIR		FR-? FIRE RISER		S	- STAINLESS STEEL SINK				
SA E/A	- SANITARY EXHAUST AIR CFM		FAN COIL RISER		MS	- MOP SINK				
SA	- SUPPLY AIR		ABBREVIATIONS		HS	- HAIR SINK				
RA	- RETURN AIR		AFF	- ABOVE FINISHED FLOOR	FLRS	- FLOOR SINK				
EA	- EXHAUST AIR		GPM	- GALLONS PER MINUTE	HBT	- BATH TUB (HANDICAPPED)				
CFSD	- COMBINATION SMOKE AND FIRE DAMPER		(HP)	- HIGH PRESSURE	EEW	- EMERGENCY EYE WASH				
DG	- DOOR GRILLE		MGSV	- MASTER GAS SOLENOID VALVE	INV. ELEV.	- INVERT ELEVATION				
			EXP	- EXPANSION TANK	OBV. ELEV.	- OBVERT ELEVATION				
			GT	- GLYCOL TANK	BFP	- APPROVED BACKFLOW PREVENTOR				
			LWCO	- LOW WATER CUT OFF	TSP	- TRAP SEAL PRIMER				
			TS	- TEMPERATURE SENSOR	SEP	- SEWAGE EJECTOR PUMP				
			PS	- PRESSURE SENSOR	GINT	- GREASE INTERCEPTOR				
			SIM	- SNOW MELTING	SINT	- SOLID INTERCEPTOR				
			HE	- HEAT EXCHANGER	SP	- STORM EJECTOR PUMP				
			B	- BOILER	TD	- TRENCH DRAIN				
			DHWH	- DOMESTIC HOT WATER HEATER	HBS	- HOSE BIBB STATION				
			DHST	- DOMESTIC WATER STORAGE TANK	WM	- WATER METER				
			BAS	- BUILDING AUTOMATION SYSTEM	BFP	- BACKFLOW PREVENTOR				
			RFH	- RADIANT FLOOR HEATING	FCO	- FLOOR CLEAN OUT				
			GM	- REMOTE READING GAS METER	DCW	- DOMESTIC COLD WATER				
			CFSD	- COMBINATION FIRE AND SMOKE DAMPER	DHW	- DOMESTIC HOT WATER				
					DHWR	- DOMESTIC HOT WATER RECIRC				
					DTW	- DOMESTIC TEMPERED WATER				
					DTWR	- DOMESTIC TEMPERED WATER RECIRC				

## LIST OF DRAWINGS

M0-00	MECHANICAL LEGEND AND DRAWING LIST
M1-00	PLUMBING SYSTEM – DEMOLITION PLAN
M1-01	HVAC SYSTEM – DEMOLITION PLAN
M2-00	PLUMBING SYSTEM – NEW ENLARGED PLAN
M2-01	HVAC SYSTEM – NEW ENLARGED PLAN
M3-00	DETAILS.
M4-00	MECHANICAL SPECIFICATIONS.
ME-00	MECHANICAL AND ELECTRICAL SCHEDULE.

DO NOT SCALE DRAWING. DIMENSION ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE

ALL DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE E&M CONSULTING ENGINEERS AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE E&M CONSULTING ENGINEERS WRITTEN PERMISSION.

2	ISSUED FOR TENDER	2025-03-24
1	ISSUED FOR PERMIT	2025-02-25
B	PROGRESS SUBMISSION	2025-02-04
A	PROGRESS SUBMISSION	2025-01-10
No.	DESCRIPTION	DATE

## REVISIONS

	24098
	Seal

**E & M**  
**Consulting Engineers Inc.**  
6004 Osprey Blvd,  
Mississauga, ON, L5N 8K3  
Canada  
[www.eandmconsultingeng.com](http://www.eandmconsultingeng.com)


**HWDSB**

project title:  
HAMILTON - WENTWORTH  
DISTRICT SCHOOL BOARD  
P02125 - LAKE AVENUE  
ELEMENTARY SCHOOL  
RENOVATIONS.  
WASHROOMS & CHANGEROOMS  
RENOVATIONS

## MECHANICAL LEGEND AND DRAWING LIST

drawn:	scale:	
date:	project number: 24-21	
checked:	DRAWING NO:  M0-00	Revision
date:		





SCALE- 1:50

checked: KS date: 1/2025	DRAWING NO:  <b>M1-00</b>	
-----------------------------------	---------------------------------	--





- A). RETAIN A LOCATION SERVICE PRIOR TO EXCAVATION TO TRACE ALL SERVICES BURIED.
- C). NOT ALL DEMOLITION ITEMS HAVE BEEN SHOWN ON DRAWINGS, IT IS SUGGESTED TO VISIT JOB SITE AND EVALUATE EXTENT OF THE DEMOLITION PRIOR TO BIDDING.
- B). PRIOR TO DEMOLISHING EXISTING DIFFUSERS AND DUCTS, RETAIN A BALANCING CONTRACTOR TO OBTAIN THE CURRENT AIR FLOW INFORMATION OF EXISTING DIFFUSERS AND SUBMIT INFORMATION TO THE CONSULTANT.

- 1 DEMOLISH EXISTING UNIT HEATER COMPLETE WITH HWS/HWR PIPING AND THERMOSTAT. CAP HWS/HWR PIPES WHEN REQUIRED FOR NEW CABINET HEATERS. COORDINATE WITH THE ELECTRICAL CONTRACTOR TO REMOVE EXISTING ELECTRICAL POWER CONNECTION UP TO THE PANEL.
- 2 EXISTING PIPES TO REMAIN AS IS.
- 3 LOCATE THE EXISTING PIPE ROUTE PRIOR TO DEMOLISH AND CAP WHERE REQUIRED.
- 4 EXISTING CABINET HEATER SHALL BE REMOVED IN ITS ENTIRETY. PIPES SHALL BE REMOVED AND CAP AS NECESSARY.
- 5 REMOVE EXISTING EXHAUST GRILLE TO BE REPLACED WITH NEW. REFER THE NEW DRAWING FOR REQUIRED CHANGES.
- 6 EXISTING EXHAUST FAN AND DUCT SHALL BE REMOVED ITS ENTIRETY. ALLOW PRICE TO CAP EXISTING DUCT WHEN REQUIRED. COORDINATE WITH THE ELECTRICAL CONTRACTOR TO REMOVE EXISTING POWER CONNECTION UP TO THE PANEL.
- 7 REMOVE THE EXISTING DUCTS AS MARKED. SEE NEW DRAWINGS FOR REQUIRED CHANGES.
- 8 REMOVE THE EXISTING HOT WATER SUPPLY AND RETURN PIPES AS MARKED. SEE NEW DRAWINGS FOR REQUIRED CHANGES.
- 9 REMOVE THE EXISTING LOUVER TO BE REPLACED WITH NEW. REFER THE NEW DRAWING FOR REQUIRED CHANGES.
- 10 EXISTING DUCT TO REMAIN AS IS.
- 11 REMOVE EXISTING LOUVER. COORDINATE WITH ARCHITECTURAL AND STRUCTURAL DIVISIONS TO PATCH WINDOW OPENINGS. SEE NEW DRAWING FOR NEW LOUVER SIZES AND LOCATIONS.

DO NOT SCALE DRAWING. DIMENSION ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE

ALL DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE E&M CONSULTING ENGINEERS AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE E&M CONSULTING ENGINEERS WRITTEN PERMISSION.

2	ISSUED FOR TENDER	2025-03-24
1	ISSUED FOR PERMIT	2025-02-25
B	PROGRESS SUBMISSION	2025-02-04
A	PROGRESS SUBMISSION	2025-01-10
No.	DESCRIPTION	DATE

REVISIONS

	24098
	Seal KS

**E & M**  
**Consulting Engineers Inc.**  
6004 Osprey Blvd.  
Mississauga, ON, L5N 8K1  
Canada  
[www.eandmconsultingeng.com](http://www.eandmconsultingeng.com)

**HWDSB**

**A**

**AMRA J**  
ARCHITECTS INC.

[www.aja.design](http://www.aja.design) | [info@aja.design](mailto:info@aja.design) | 905.920.5121


project title:  
HAMILTON - WENTWORTH  
DISTRICT SCHOOL BOARD  
P02125 - LAKE AVENUE  
ELEMENTARY SCHOOL  
RENOVATIONS.  
WASHROOMS & CHANGEROOMS  
RENOVATIONS

Drawing Title:


**HVAC SYSTEM -  
DEMOLITION PLAN**

drawn: <b>MH</b>	scale: <b>AS SHOWN</b>	
date: <b>01/2025</b>	project number: <b>24-21</b>	
checked: <b>KS</b>	DRAWING NO: <b>M1-01</b>	Revision





PLUMBING SYSTEMS—NEW ENLARGED PLAN



PLUMBING GENERAL NOTES:

- A) ALL PLUMBING WORK TO CONFORM TO ONTARIO BUILDING CODE, ONTARIO WATER REGULATION ACT No. 615/64, CONSTRUCTION SAFETY ACT AND REGULATIONS OF THE CITY AND LOCAL AUTHORITIES
- B) ALL SANITARY DRAINS TO BE INSTALLED BURIED (MIN. 300mm BELOW FIN. FLOOR) AND SLOPED AS SHOWN UNLESS OTHERWISE NOTED.
- C) COORDINATE PIPE INSTALLATION WITH ELECTRICAL CONDUITS, DUCT & STRUCTURAL MEMBERS. OFFSET PIPES AS REQUIRED.
- D) CONTRACTOR TO FIELD VERIFY WORKSITE CONDITIONS.
- E) PROVIDE ACCESS DOOR FOR EACH WATER VALVE INSTALLED IN CONCEALED SPACES.
- F) DO NOT INSTALL DHW & DCW PIPES IN EXPOSED EXTERIOR OR PERIMETER WALLS.
- G) SANITARY DRAINAGE AND VENT PIPES ABOVE GRADE SHALL BE CERTIFIED TO CAN/CSA-B181.2 "PVC DRAIN, WASTE, AND VENT PIPE AND PIPE FITTINGS"
- H) DOMESTIC HOT AND COLD WATER PIPES SHALL BE TYPE "L" HARD COPPER TUBING WITH SOLDERED FITTINGS.
- I) INSULATE ALL NEW DOMESTIC WATER PIPES WITH MINIMUM 50 mm THICK INSULATION. COVER EXPOSED PIPES WITH PVC JACKETS.
- J) PRIOR TO ANY INSTALLATION SURVEY THE EXISTING SPACE AND NOTE DOWN ALL EXISTING MECHANICAL AND ELECTRICAL EQUIPMENT UNDERGROUND AND BURIED CABLES AND CONDUITS WITH THE ASSISTANCE OF A LOCATION SERVICE.

PLUMBING DRAWING NOTES (NEW)

- 1 PROVIDE COMPLETE SANITARY PLUMBING FIXTURES & PIPING AS SHOWN ON THIS DRAWING.
- 2 CONNECTED TO THE EXISTING SERVICE LINE AS SHOWN WITH REQUIRED INSULATION. PROVIDE NEW SHUTOFF VALVE IN DCW/DHW PIPE FOR NEW FIXTURES.
- 3 EXISTING DCW/DHW PIPING TO REMAIN AS IS. ALLOW PRICE FOR REPLACING PIPE INSULATION OF EXISTING PIPES WHERE DAMAGED OR MISSING WITH IN THE AREA OF NEW SCOPE.

PLUMBING FIXTURE SCHEDULE						
SYMBOL	FIXTURE DESCRIPTION	MANUFACTURER	CONNECTION SIZE			
			DCW	DHW	SANITARY	VENT
WC-1	WATER CLOSET	AMERICAN STANDARD MADERA™ FloWise® 15" HEIGHT ELONGATED with EVERCLEAN® PRESSURE-ASSISTED 6L TOILET 3451.001 ELONGATED 15" (381MM) BOWL ONLY,TOP SPUD WITH 2 BOLT CAPS.	25ø	—	75ø	40ø
	FLUSH VALVE	DELTA MODEL 811201 FLUSH VALVE FOR 1-1/2" TOP SPUD WATER CLOSET MAXIMUM 232MM(11-1/2") FROM CENTERLINE OF VALVE INLET TO TOP OF WATER CLOSET,1"IP/COPPER SWEAT INLET ADAPTOR FOR ANGLE CHECK STOP WITH PROTECTING CAP ADJUSTABLE 121MM ±11MM INLET/VALVE OUTLET CENTERS, C/W COVER TUBE AND SS WALL FLANGE.	25ø	—	—	—
	WATERCLOSET SEAT	HEAVY DUTY SOLID PLASTIC SEAT CENTOCO #500STSCC (HEAVY—DUTY, OPEN FRONT, LESS COVER FOR ELONGATED BOWL.)	—	—	—	—
WC-2	BARRIER FREE WATER CLOSET	AMERICAN STANDARD MADERA™ FloWise® 15" HEIGHT ELONGATED with EVERCLEAN® PRESSURE-ASSISTED 6L TOILET 3451.001ELONGATED 17" (431.8MM) BOWL ONLY,TOP SPUD WITH 2 BOLT CAPS.	25ø	—	75ø	40ø
	FLUSH VALVE	DELTA MODEL 811201 FLUSH VALVE FOR 1-1/2" TOP SPUD WATER CLOSET MAXIMUM 232MM(11-1/2") FROM CENTERLINE OF VALVE INLET TO TOP OF WATER CLOSET,1"IP/COPPER SWEAT INLET ADAPTOR FOR ANGLE CHECK STOP WITH PROTECTING CAP ADJUSTABLE 121MM ±11MM INLET/VALVE OUTLET CENTERS, C/W COVER TUBE AND SS WALL FLANGE.	25ø	—	—	—
	WATERCLOSET SEAT	HEAVY DUTY SOLID PLASTIC SEAT CENTOCO #500STSCC (HEAVY—DUTY, OPEN FRONT, LESS COVER FOR ELONGATED BOWL.)	—	—	—	—
LAV-1	LAVATORY	'AMERICAN STANDARD' LUCERNE™ WALL—HUNG LAVATORY MODEL No. 0355.027 FOR EXPOSED BRACKET SUPPORT, FAUCET HOLES ON 102MM (4") CENTERS	—	—	32ø	32ø
	FAUCET	DELTA MIXING METERING HANDWASH FAUCET MODEL No. 86T1153	12ø	12ø	—	—
	DRAIN AND P-TRAP	'OS&B' 19HOLE GRID p.o BODY ASSEMBLY 17 GAUGE TAILPIECE DRAIN, ZURN SEMI—CAST P—TRAPS WITH WALL BEND PRODUCT NUMBER ZB700—PC CHROME—PLATED CAST BRASS (COPPER ALLOY) BODY P—TRAP WITH CLEANOUT	—	—	32ø	—
	THERMOSTATIC MIXING VALVE	HAWS MODEL No. 9201H OR EQUIVALENT	—	—	—	—
UR-1	URINAL	'AMERICAN STANDARD' WASHBROOK® FloWise® UNIVERSAL URINAL WITH EVERCLEAN 6590.001 TOP SPUD	19ø	—	50ø	40ø
	FLUSH VALVE	SLOAN MODEL 186—0.5 FLUSHOMETER EXPOSED URINAL FLUSHOMETER FOR ¾" TOP SPUD URINALS.	19ø	—	—	—
	ACCESSORIES	DRAIN, P-TRAP, ALL ACCESSORIES AND WALL MOUNTING BRACKET.	—	—	32ø	—
WF	WASHING FOUNTAIN	BRADLEY BRADIMATE™ WASHFOUNTAINS S93—574, ONTARIO BUILDING CODE HEIGHT, INFRARED, NAVIGATOR® THERMOSTATIC MIXING ASSEMBLY (HOT & COLD SUPPLIES). 120MM/12VDC PLUG IN ADAPTER, PLUGS INTO A STANDARD GFCI PROTECTED ELECTRICAL OUTLET.	12ø	12ø	40ø	32ø
FD	FLOOR DRAIN	WATTS FD-100-C-A 125mm NICKEL BRONZE STRAINER	—	—	3ø	—
NOTES: 1. INCLUDING ALL ACCESSORIES, TRAP SEAL PRIMERS ETC. 2. POWER CONVERTERS ACTUAL QUANTITIES HAVE NOT BEEN GIVEN ACCURATELY. 3. ALL PIPING SHALL BE CONCEALED WITHIN WALLS 4. PROVIDE SHOCK STOPS ON HOT/COLD WATER SUPPLIES TO ALL FIXTURE GROUPS. 5. ALL VENTING SHALL CONFORM TO OBC PART 7. INCREASE VENT SIZING AS REQUIRED WHERE TOTAL VENT LENGTH EXCEEDS SIZES LISTED ABOVE.						

DO NOT SCALE DRAWING. DIMENSION ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE.  
ALL DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE E&M CONSULTING ENGINEERS AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE E&M CONSULTING ENGINEERS WRITTEN PERMISSION.

2	ISSUED FOR TENDER	2025—03—24
1	ISSUED FOR PERMIT	2025—02—25
B	PROGRESS SUBMISSION	2025—02—04
A	PROGRESS SUBMISSION	2025—01—10
No.	DESCRIPTION	DATE

REVISIONS	
24098	Seal KS.

**E & M**  
Consulting Engineers Inc.  
2401 Highway 104  
Markham, ON L3R 9A3  
Canada  
www.eandmconsulting.com

**HWDSB**  
**AMRA J**  
ARCHITECTS INC.  
www.aja.design | info@aja.design | 905.920.5121

Project No:  
HAMILTON - WENTWORTH  
DISTRICT SCHOOL BOARD  
P02125 - LAKE AVENUE  
ELEMENTARY SCHOOL  
RENOVATIONS  
WASHROOMS & CHANGEROOMS  
RENOVATIONS


Drawing Title:  
PLUMBING SYSTEM -  
NEW ENLARGED PLAN

drawn: MH	scale: AS SHOWN
date: 01/2025	project number: 24-21
checked: KS	DRAWING NO: M2-00
date:	Revision











NOTE:  
MAXIMUM OF FOUR URINALS PER  
SOLENOID VALVE AND CONTROL PANEL

1 TYPICAL URINAL PIPING SCHEMATIC  
NTS




NOTE:  
1. MAXIMUM OF FOUR URINALS PER SOLENOID VALVE AND CONTROL PANEL.  
2. PLUMBING CONTRACTOR TO CARRY WATER MATRIX AS A SUB CONTRACTOR.  
3. WATER MATRIX CONTACT INFO:  
PHONE: (905) 850-8080 OR 1-1800-668-4420


2 WATER MATRIX FLUSH SYSTEM WIRING DIAGRAM.  
NTS



3 FLOOR DRAIN DETAIL  
NTS




4 CLEANOUT DETAIL  
NTS



NOTES:  
1. SEE PLAN FOR PIPE SIZES.  
2. MINIMUM CONNECTION SIZE 3/4\"/>

5 CEILING MOUNTED CABINET UNIT HEATER DETAIL .  
NTS



NOTES:  
1. SEE PLAN FOR LOCATIONS.  
2. REFER THE MANUFACTURE RECOMMENDED INSTALLATION PROCEDURE.  
3. PROVIDE NEW 75X75 ANGLE IRON BETWEEN EXISTING JOISTS(OWSJ) TO SUPPORT NEW INLINE FANS. SPRING BASE ISOLATORS C/W FAN SHALL BE BOLTED TO NEW ANGLE IRON. ANGLE IRON SHALL BE PRIME & PAINTED. TYPICAL FOR ALL NEW INLINE FANS.

6 INLINE EXHAUST FAN MOUNTING DETAIL .  
NTS

DO NOT SCALE DRAWING. DIMENSION ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE.  
ALL DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE E&M CONSULTING ENGINEERS AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE E&M CONSULTING ENGINEERS WRITTEN PERMISSION.

2	ISSUED FOR TENDER	2025-03-24
1	ISSUED FOR PERMIT	2025-02-25
B	PROGRESS SUBMISSION	2025-02-04
A	PROGRESS SUBMISSION	2025-01-10

No.	DESCRIPTION	DATE
-----	-------------	------

REVISIONS

24098	Seal	KS
-------	------	----

**E & M**  
Consulting Engineers Inc.  
2401 Highway 104  
Markham, ON L3R 9K3  
Canada  
www.eandmconsulting.com

**HWDSB**

**AMRA J**  
ARCHITECTS INC.  
www.aja.design | info@aja.design | 905.920.5121

Project No:  
HAMILTON - WENTWORTH  
DISTRICT SCHOOL BOARD  
P02125 - LAKE AVENUE  
ELEMENTARY SCHOOL  
RENOVATIONS,  
WASHROOMS & CHANGEROOMS  
RENOVATIONS

Drawing Title:  
DETAIL

drawn: MH	scale: NTS
date:	project number: 24-21
checked: KS	DRAWING NO: M3-00
date: 12/2024	Revision: 0



MECHANICAL SPECIFICATIONS

A GENERAL CONDITIONS

- 1.1 GENERAL
- .1 THE WORK SHALL BE DONE IN ACCORDANCE WITH THE REQUIREMENTS OF THE ONTARIO BUILDING CODE, THE ONTARIO WATER RESOURCES ACT, THE MINISTRY OF LABOUR, THE CITY OF HAMILTON AND ALL CODES HAVING JURISDICTION, WHICH ARE TO BE CONSIDERED AN INTEGRAL PART OF THESE SPECIFICATIONS. THE GENERAL CONDITIONS OF THE ARCHITECTURAL SPECIFICATIONS ARE HEREBY MADE PART OF THESE SPECIFICATIONS.
- .2 ALL LABOUR, MATERIALS, EQUIPMENT, FEES, PERMITS AND CHARGES TO PERFORM THE OPERATIONS FOR THE COMPLETE INSTALLATION OF THE PLUMBING, PIPING, VENTILATION AND HEATING WORK, AS INDICATED ON THE DRAWINGS.
- .3 VISIT THE JOB SITE AND EXAMINE ALL EXISTING CONDITIONS WHICH AFFECT THE WORK.
- .4 PAY FOR AND OBTAIN ALL REQUIRED PERMITS, FEES, LICENCES, CERTIFICATES OF INSPECTION, ETC. PROVIDE AND SUBMIT REQUIRED DRAWINGS TO THE AUTHORITIES HAVING JURISDICTION. ALL WORK SHALL BE IN ACCORDANCE WITH LAWS AND OF THE AUTHORITIES HAVING JURISDICTION. PROVIDE THE EQUIPMENT WITH APPLICABLE CGA, CSA AND ULG LABELS.
- .5 CONFORM TO THE ONTARIO BUILDING CODE, CSA STANDARDS, MINISTRY OF ENVIRONMENT (MOE), LOCAL BY-LAWS AND AUTHORITIES HAVING JURISDICTION.
- .6 CO-ORDINATE WITH OTHER TRADES REGARDING THE LOCATIONS OF EQUIPMENT, CONTROL DEVICES, LOCATIONS, DISTRIBUTION SYSTEM, ETC.
- .7 SCHEDULE WORKING HOURS WITH THE OWNER.
- .8 THE CONTRACTOR IS TO LOCATE THE EXACT DIMENSIONS AND POSITIONS OF OPENINGS AND HOLES WHERE CUTTING MAY BE REQUIRED IN FLOORS, ROOFS, CEILINGS AND/OR WALLS FOR THE PASSAGE OF PIPES, DUCTS, ETC. WHERE CUTTING, PATCHING IS NECESSARY, IT SHALL BE DONE BY THE MECHANICAL.
- .9 CONNECTIONS INTO EXISTING SYSTEMS TO BE MADE AT TIME APPROVED BY OWNER. REQUEST WRITTEN APPROVAL OF TIME WHEN CONNECTIONS CAN BE MADE. BE RESPONSIBLE FOR DAMAGE TO EXISTING PLANT BY THIS WORK.
- .10 CLEAN INTERIOR AND EXTERIOR OF ALL SYSTEMS. VACUUM INTERIOR OF DUCTWORK AND AIR HANDLING UNITS. IN PREPARATION FOR FINAL ACCEPTANCE, CLEAN AND REFURISH ALL EQUIPMENT AND LEAVE IN OPERATING CONDITION INCLUDING REPLACEMENTS OF ALL FILTERS IN ALL SYSTEMS.
- .11 FOR ALL CONCEALED VALVES AND VOLUME DAMPERS, PROVIDE ACCESS DOORS AND ARRANGE THESE DOORS TO BE INSTALLED BY THE RESPECTIVE TRADES SUCH AS MAINTENANCE INSTRUCTIONS FROM THE MANUFACTURER.
- .12 PROVIDE MANUFACTURER RECOMMENDED SPACE FOR SERVICING, DISASSEMBLY AND REMOVAL OF EQUIPMENT AND COMPONENTS. PIPE EQUIPMENT DRAINS TO NEAREST DRAIN.
- .13 PROVIDE SCHEDULE 40 PIPE SLEEVES AT POINTS WHERE PIPES PASS THROUGH MASONRY, CONCRETE OR FIRE RATED ASSEMBLIES. SLEEVE SIZES: MINIMUM 6 MM CLEARANCE ALL AROUND, BETWEEN SLEEVE AND UNINSULATED PIPE OR BETWEEN SLEEVES AND PIPE IN FOUNDATION WALLS AND BELOW GRADE FLOORS WITH WATERPROOF FIRE RETARDANT NON-HARDENING MASTIC. WHERE SLEEVES PASS THROUGH WALLS OR FLOORS, PROVIDE SPACE FOR FIRE STOPPING. WHERE PIPES/DUCTS PASS THROUGH FIRE RATED WALLS, FLOORS AND PARTITIONS, MAINTAIN
- .14 SUPPLY TOOLS, EQUIPMENT AND PERSONNEL TO DEMONSTRATE AND INSTRUCT OPERATING AND MAINTENANCE PERSONNEL IN OPERATING, CONTROLLING, ADJUSTING, TROUBLE-SHOOTING AND SERVICING OF ALL SYSTEMS AND EQUIPMENT DURING REGULAR WORK HOURS, PRIOR TO ACCEPTANCE.
- .15 GUARANTEE IN WRITING FOR THE MATERIAL AND WORKMANSHIP INCLUDING THE MANUFACTURER'S GUARANTEE FOR THE PERIOD OF ONE (1) YEAR FROM THE DATE OF ACCEPTANCE.
- .16 CERTIFY IN WRITING FOR ALL WORK COMPLETED IN ACCORDANCE WITH THE SPECIFICATIONS AND DRAWINGS. SUBMIT AS-BUILT DRAWINGS WHERE REVISIONS
- .17 WHERE THESE STANDARDS ARE SUPERCEDED BY PUBLISHED LOCAL MUNICIPAL STANDARDS AND DESIGN CRITERIA, THE MUNICIPAL STANDARDS SHALL APPLY. THESE STANDARDS APPLY TO ALL PHASES OF THE WORK.
- 1.2 DESCRIPTION OF WORK
1. SELECTIVE DEMOLITION WORK.
2. RENOVATION OF WASH ROOM PLUMBING SYSTEMS.
3. RENOVATION OF WASH ROOM AND MUSIC ROOM HVAC SYSTEMS.
4. OTHER MISCELLANEOUS WORK AS SHOWN ON DRAWING.

1.3 SHOP DRAWINGS

- SUBMIT SHOP DRAWINGS FOR THE FOLLOWING:
- .1 HVAC EQUIPMENT INCLUDING HEATERS.
- .2 AIR GRILLE.
- .3 PLUMBING FIXTURES DESIGNATED.

1.4.1 STANDARDS OF MATERIAL AND EQUIPMENT

- MATERIAL AND EQUIPMENT ARE SPECIFICALLY DESCRIBED AND NAMED IN THIS SPECIFICATION AS EITHER BASE BID, BASE BID ALTERNATES AND ACCEPTABLE PRODUCTS.
- .2 WHERE THE TERM "ACCEPTABLE PRODUCTS" IS USED, THE BID MAY BE BASED ON ANY OF THE ACCEPTABLE PRODUCTS.
- .3 WHERE THE "BASE BID" SPECIFICATION IS USED, THE BID MUST BE BASED ON THE SPECIFIED EQUIPMENT. THE "ALTERNATE PRODUCTS" SHALL BE LISTED ON THE SUPPLEMENTARY TENDER FORM WITH THE COST SAVING (IF ANY), AND THE OWNER SHALL HAVE THE FINAL OPTION OF ACCEPTING OR REJECTING ALTERNATE EQUIPMENT.
- .4 IF THIS DIVISION STATES THE USE OF "ALTERNATE PRODUCTS", THE BIDDER SHALL HAVE MADE ALLOWANCE IN HIS SAVINGS FOR ANY STRUCTURAL OR ELECTRICAL CHANGES NECESSARY, AND SAID CHANGES SHALL BE AT THE EXPENSE OF THIS DIVISION.

1.5 INTERRUPTION OF EXISTING SERVICES

- .1 ALL INTERRUPTIONS OF EXISTING MECHANICAL SYSTEMS MUST BE APPROVED BY AND CO-ORDINATED WITH THE OWNER.
- .2 DISRUPTION OF NORMAL OPERATIONS WILL NOT BE ALLOWED. ALL INTERRUPTIONS SHALL OCCUR AFTER THE CLOSE OF NORMAL HOURS. PREMIUM TIME TO BE INCLUDED IN THE TENDER PRICE.

1.6 SLEEVES, CUTTING, PATCHING AND FIRE STOPPING

- .1 INSTALL SLEEVES AND FRAMES FOR PIPING AND SIMILAR EQUIPMENT TO BE BUILT INTO THE BUILDING AS THE CONSTRUCTION PROGRESSES. IF THESE ARE NOT INSTALLED AT THE TIME OF CONSTRUCTION, THE COST OF CUTTING AND PATCHING AT A LATER DATE, WILL BE AT THE EXPENSE OF THIS CONTRACTOR.
- .2 THE PRIME MECHANICAL CONTRACTOR IS RESPONSIBLE FOR THE CUTTING AND PATCHING OF ALL HOLES AND OPENINGS UP TO AND INCLUDING 200 mm (8") DIAMETER.
- .3 THE PRIME MECHANICAL CONTRACTOR IS TO LOCATE THE EXACT POSITIONS AND DIMENSIONS OF LARGER OPENINGS FOR CUTTING BY THE GENERAL DIVISION.
- .4 THE PRIME MECHANICAL CONTRACTOR IS RESPONSIBLE FOR THE SUPPLY AND INSTALLATION OF APPROVED FIRE STOPPING FOR ALL NEW MECHANICAL PENETRATIONS THROUGH BOTH EXISTING AND NEW FIRE SEPARATIONS. VERIFY ALL FIRE SEPARATIONS WITH THE ARCHITECTURAL DRAWINGS. FIRE STOPPING IS TO BE RATED TO MATCH AND MAINTAIN THE INTEGRITY OF THE RATED ASSEMBLY.

1.7 RECORD DRAWINGS AND EQUIPMENT MANUALS

- .1 AS THE PROJECT PROGRESSES, RECORD, ON A SET OF WHITE PRINTS, ALL ADDENDA, CHANGES TO AND DEVIATIONS FROM THE PLANS MADE DURING THE CONSTRUCTION PERIOD. ALSO, RECORD THE LOCATION OF ALL DIFFUSERS, GRILLES AND OTHER MECHANICAL EQUIPMENT.
- .2 MAKE THESE PROGRESS RECORD DRAWING WHITE PRINTS AVAILABLE TO THE CONSULTANTS FOR THEIR REVIEW AT ALL TIMES DURING THE CONSTRUCTION PERIOD.
- .3 AT THE CONCLUSION OF THE PROJECT, TRANSFER ALL RECORD DRAWING INFORMATION ONTO AUTOCAD RELEASE 2010 OR LATER TO A UNIVERSAL SERIAL BUS STICK (USB).
- .4 THE CONSULTANT SHALL PROVIDE TO THE CONTRACTOR A USB CONTAINING GRAPHIC (ELECTRONIC) REPRESENTATION OF THE DRAWINGS. A RELEASE FORM "TRANSFER OF OF FILES ON ELECTRONIC MEDIA" WILL BE PROVIDED BY THE CONSULTANT TO THE CONTRACTOR FOR SIGNING IN ORDER TO RECEIVE AND USE THE ELECTRONIC FILES.
- .5 BEFORE SUBSTANTIAL PERFORMANCE OF THE CONTRACT, COMPLY WITH THE FOLLOWING:
- .1 PROVIDE USB CONTAINING ALL UPDATED RECORD DRAWING INFORMATION AS SPECIFIED HEREIN.
- .2 PROVIDE TWO (2) SETS OF EQUIPMENT DATA SHEETS AND/OR MANUFACTURER'S MAINTENANCE MANUALS COVERING EACH SYSTEM AND ITS COMPONENTS IN ACCORDANCE WITH REQUIREMENTS OF EACH APPROPRIATE SECTION. THEY ALL SHALL BE SUBMITTED ELECTRONICALLY IN A USB.

B. BALANCING IDENTIFICATION AND START-UP

- 1 IDENTIFICATION IS TO BE CARRIED OUT BY THE RESPECTIVE TRADE WITH NAME TAGS IDENTIFYING THE USE OR SERVICE OF ALL NEW MAIN VALVES AND NEW EQUIPMENT.
- 2 CLEAN ALL NEW EQUIPMENT AND OTHER INSTALLATIONS.
- 3 PROVIDE MAINTENANCE INSTRUCTIONS IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- 4 SUBMIT TWO (2) COPIES OF MANUFACTURER'S MAINTENANCE MANUALS TO OWNER FOR ALL NEW EQUIPMENT.
- 5 PROVIDE AN ELECTRONIC COPY OF THE AIR BALANCING REPORT TO OWNER.
- 6 AIR BALANCING SHALL BE DONE BY PROFESSIONAL TESTING AND BALANCING FIRM. AIR QUANTITIES OF EACH OUTLET SHALL BE AS INDICATED ON THE DRAWINGS. THE AIR BALANCING REPORT SHALL SHOW THE QUANTITIES, VELOCITIES, AND AREA OF EACH OUTLET, TYPE AND MODEL, NUMBER OF FANS AND MOTORS INSTALLED, ACTUAL AIR DELIVERED BY THE FAN WITH TOTAL STATIC PRESSURE AND VOLTAGE DRAWN BY THE MOTORS, ADJUST AND RETEST THE SYSTEMS TO THE SATISFACTION OF THE PROJECT CO-ORDINATOR. PROVIDE AN ADDITIONAL COPY OF THE AIR BALANCING REPORT TO THE MECHANICAL CONSULTANT.
- 7 APPLICATION TOLERANCES: HVAC SYSTEMS: PLUS 5%, MINUS 5%
- 8 AIR SYSTEMS: TO TAB STANDARDS OF AABC.
- 9 THE HVAC CONTRACTOR SHALL CO-OPERATE WITH TAB AGENCY, PROVIDE REQUIRED PERSONNEL ATTENDANCE AND AT NO ADDITIONAL COST, CHANGE OR ADJUST THE SHEAVES, MOTOR AND BELTS IF NECESSARY TO ACHIEVE THE SPECIFIED AIR VOLUME.
- 10 SUBMIT THREE (3) COPIES OF TAB REPORT WITH SCHEMATICS FOR ENGINEERS APPROVAL.

C VENTILATION

- .1 VENTILATION MATERIALS
- ALL MATERIALS AND EQUIPMENT SHALL BE NEW AND FREE FROM DEFECTS, CSA APPROVED.
- .2 AIR DISTRIBUTION
- ALL DUCTWORK SHALL BE FABRICATED TO SMACNA DUCT MANUAL STANDARDS, SECTION NO. 1, AND AS FOLLOWS
- .3 MATERIAL AND THICKNESS
- DUCTWORK SHALL BE FABRICATED FROM BEST QUALITY LOCK-FORMING GALVANIZED STEEL SHEETS AS MANUFACTURED BY STELCO OR DOFASCO OF THE FOLLOWING THICKNESS:
- | SIZE OF DUCT  | GAUGE OF SHEET STEEL |
|---|----------------------|
| 300 OR LESS IN WIDTH OR DEPTH OF UP TO 200 DIAMETER | NO.26 US             |
| 325 TO 750 IN WIDTH OR DEPTH OF 225 TO 550 DIAMETER | NO.24 US             |
| 750 TO 1350 IN WIDTH OR DEPTH                       | NO.22 US             |
- .4 CONSTRUCTION
- LONGITUDINAL SEAMS SHALL BE MADE WITH PITTSBURGH LOCK OR BUTT/PUNCH SEAMS IN ALL SIZES. ALL DUCTWORK SHALL BE CROSS BROKEN OR BEADED 12" O.C. FOR RIGIDITY. DUCTS SHALL HAVE PLAIN "S" SLIPS ON THE LONG SIDES, AND DRIVE CLEATS ON THE SHORT SIDES, FOLDED OVER TO PREVENT AIR LEAKAGE. MINIMUM END JOINT SPACING IS 3000mm
- ALL BENDS OR ELBOWS SHALL BE MADE WITH A RADIUS OF NOT LESS THAN 1-1/2 TIMES THE WIDTH OF THE DUCT, WHERE IT IS NOT POSSIBLE, TURNING VANES SHALL BE USED. VANES SHALL BE OF SINGLE VANE CONSTRUCTION WITH SPACE UP TO 600 WIDTH AND 80mm SPACING OVER 600

5 HANGERS

- DUCTWORK SHALL HAVE SUBSTANTIAL HANGERS ATTACHED TO STRUCTURE WITH CONCRETE INSERTS TO SECURE THE DUCTS IN PLACE AND PREVENT VIBRATION. NO CADDY CLIPS OR PLUMBERS TAPE PERMITTED FOR HANGING DUCTS.
- HORIZONTAL DUCTWORK UP TO 725 WIDE SHALL BE SUPPORTED BY GALVANIZED 25mm 16 GAUGE OR HEAVIER HANGERS PLACED NOT OVER 1800mm APART, WITH ENDS TURNED UNDER THE DUCT. SECURE TO DUCT WITH SHEET METAL SCREWS, TWO (2) PER SIDE, AND ONE (1) IN BOTTOM.
- HORIZONTAL DUCTWORK OVER 750 mm WIDE SHALL REST ON GALVANIZED ANGLE IRON SUPPORTS OR UNISTRUT CHANNELS, WITH ROD HANGERS AT 1800mm SPACING AS FOLLOWS:
- | DUCT SIZE   | ROD | ANGLE             |
|-------------|-----|-------------------|
| 750 TO 1225 | 6mm | 40mm X 40mm X 3mm |
- .6 DUCT SEALING
- ALL JOINTS DURING MANUFACTURE OF LOW VELOCITY DUCTWORK SHALL BE SEALED WITH 3-M, HIGH VELOCITY SEALER, TOUGH BOND OR DURO DYNE S-2H.V. SEALER ON THE FACES OF THE JOINTS AND AFTER CLEATS HAVE BEEN INSTALLED.

7 BALANCING DAMPERS

- PROVIDE BALANCING DAMPERS IN DUCTWORK WHERE SHOWN AND WHERE REQUIRED FOR PROPER ADJUSTMENT OF AIR QUANTITIES. OPEN AND CLOSED POSITIONS MUST BE CLEARLY MARKED.
- .1 SPLITTER DAMPERS: SHALL BE AIRFOIL SHAPE DOUBLE THICKNESS ON GAUGE HEAVIER THAN DUCT WITH LOCKING QUADRANT ON EXTERIOR OF DUCT.
- .2 SINGLE BLADE ROUND BUTTERFLY U.S. 22 GA THICK WITH LOCKING QUADRANT.
- .3 MULTI-LEAF OPPOSED BLADE DAMPERS DESIGNED TO SMACNA DETAILS WITH LOCKING QUADRANT.
- .8 DUCT INSULATION
- COMPONENTS OF INSULATION SYSTEM TO HAVE MAXIMUM FLAME SPREAD RATING OF 25 AND MAXIMUM SMOKE DEVELOPED RATING OF 50 IN ACCORDANCE WITH CAN/ULC-S102 MATERIALS TO BE TESTED IN ACCORDANCE WITH ASTM C411.
- PROVIDE CAN/CGSB-51.10, RIGID MINERAL FIBRE BOARD; CGSB 51-GP-52MA VAPOUR BARRIER, JACKET AND FACING MATERIAL INSULATION ON RECTANGULAR DUCTING LARGER THAN 300x150 SIZE FOR SUPPLY AIR DUCTING, FROM FAN TO SUPPLY GRILLE.
- THICKNESS: ONE 25 MM LAYER ON SUPPLY AIR DUCTS. INSTALL IN ACCORDANCE WITH ANSI/NFPA 90A AND ANSI/NFPA 90B.
- PROVIDE 25mm THICKNESS MINERAL FIBRE BLANKET WITH RRRFK FACING TO CAN/CGSB-51.11 ON ROUND AND RECTANGULAR SUPPLY AIR DUCTWORK UP TO 300x150 SIZE.
- JACKETS:
- INDOOR EXPOSED: ULC LISTED PLAIN WEAVE COTTON FABRIC.
- OUTDOOR: GLASSFAB MEMBRANE FINISHED WITH TWO (2) COATS BAKELITE #110-14.
- INSULATE:
- ALL SUPPLY AIR DUCTWORK INCLUDING DUCTS IN CEILING RETURN AIR PLENUMS.
- DO NOT INSULATE:
- RETURN AIR DUCTS, ACOUSTICALLY LINED DUCTS

D PIPE AND FITTINGS -- PRODUCTS

1.1 PLUMBING & DRAINAGE

- .1 PIPE MATERIALS
- .1 SOIL, VENT AND RAINWATER LEADERS NOT BURIED 3" (80 MM) AND LARGER:
- .1 CLASS 4000 CAST IRON SHALL BE CERTIFIED TO CSA B70 -- MECHANICAL JOINT.
- .2 DRAINAGE VENTS AND WASTES 2-1/2" (65 MM) AND SMALLER:
- .1 CLASS 4000 CAST IRON SHALL BE CERTIFIED TO CAN/CSA B70-M91 -- MECHANICAL JOINT.
- .2 DRAINAGE COPPER PIPE DWV SHALL COMPLY WITH ASTM B306 -- SOLDER JOINTS.
- .3 SCHEDULE 40 GALVANIZED STEEL -- THREADED JOINTS.
- .3 ALL BURIED DRAINAGE PIPING WITHIN BUILDING:
- .1 CLASS 4000 CAST IRON SHALL BE CERTIFIED TO CAN/CSA B70-M91 -- MECHANICAL JOINT.
- .2 DWV PLASTIC PIPE ABS AND SOLVENT WELD, 4" (100 MM) AND SMALLER.
- .3 PVC SDR, 6" (150 MM) AND LARGER.
- 1.2 STEEL PIPE AND FITTINGS
- .1 SERVICE: HOT WATER HEATING.
- .2 PIPING: CONTINUOUS WELDED SCHEDULE 40 ASTM-A120 FOR SCREWED PIPING AND MECHANICAL JOINTS AND ASTM-A53 FOR WELDING.
- .3 JOINTS:
- .1 15 MM TO 65 MM CLASS 150 MI THREADED UNIONS, CLASS 150 DART PATTERN MI THREADED BRASS TO IRON GROUND SEAT.
- .4 VALVES:
- .1 ALL INSULATED VALVES SHALL HAVE EXTENDED NECKS OR SHAFTS WHERE THE THICKNESS OF THE INSULATION INTERFERES WITH THE OPERATING HANDLE.
- .2 BALL:
- .1 15 MM TO 50 MM CLASS 150 STANDARD PORT BRONZE BODY BRONZE FITTED SCREWED ENDS PTFE SEATS AND PACKING, LEVER HANDLE.
- ACCEPTABLE PRODUCTS:
- .1 CRANE 9202
- .2 JENKINS 201J
- .3 NEWMAN-HATTERSLEY 1969
- .4 VICTAULIC 726
- .5 MILWAUKEE BA-200
- .3 CHECK:
- .1 15 MM TO 65 MM CLASS 125 BRONZE BODY, SCREWED ENDS, SWING DISC, SCREW-ON CAP.
- ACCEPTABLE PRODUCTS:
- .1 CRANE 37/1707
- .2 JENKINS 4092
- .3 MILWAUKEE 509
- .4 NEWMAN-HATTERSLEY A60
- .4 STRAINERS:
- .1 15 mm TO 50 mm CAST IRON "Y" BODY PATTERN, SCREWED ENDS AND CAP WITH BRASS PLUG, STAINLESS STEEL SCREEN WITH 0.125 PERFORATIONS FOR WATER SERVICE.
- ACCEPTABLE PRODUCTS:
- .1 SARCO
- .2 ITT
- 1.3 COPPER PIPE AND FITTINGS
- .1 SERVICE: ALL DOMESTIC WATER PIPING
- .2 PIPING: PLAIN END TYPE "L" HARD DRAWN COPPER.
- .3 FITTINGS: SOLDER END WROUGHT COPPER.
- .4 JOINTS: ALL DOMESTIC HOT AND COLD POTABLE WATER PIPING SHALL BE JOINED USING 95/5 SOLDER CONTAINING NO LEAD COMPOUNDS (95% TIN/5% ANTIMONY). NON-POTABLE WATER PIPING SHALL BE JOINED USING A STANDARD 50/50 TIN/LEAD COMPOUND SOLDER.
- .5 VALVES:
- .1 BALL: 15 MM TO 65 MM FULL PORT BRASS OR BRONZE BODY, BRONZE FITTED SOLDER ENDS, PTFE SEATS AND PACKING, LEVER HANDLE.
- .2 ACCEPTABLE PRODUCTS:
- .1 CRANE F9222
- .2 JENKINS 902
- .3 APOLLO 77FLF-200
- .4 NIBCO 585-80-LF

E PLUMBING FIXTURES -- PRODUCTS

PLUMBING FIXTURES

- .1 CONNECTIONS TO FIXTURES:
- .1 TRAP AND VENT EACH FIXTURE, ACCORDING TO THE PLUMBING CODE.
- .2 SUPPLY AND INSTALL THE PLUMBING FIXTURES WITH ALL REQUIRED FITTINGS:

F PIPES AND FITTINGS -- EXECUTION

1.1 PIPING INSTALLATION

- .1 PROVIDE ALL NECESSARY PIPING INCLUDING FITTINGS AND UNIONS TO COMPLETE SYSTEMS SHOWN. CUT PIPES TRUE AND SQUARE, REAM FILE ENDS TO SMOOTH SURFACE, ALL TO PIPE MANUFACTURER'S AND ACCEPTED TRADE STANDARDS. FITTINGS SHALL BE OF EQUIVALENT BORE AS PIPE, OF EQUAL STRENGTH AND WEIGHT. INSTALL PIPING TO MANUFACTURER'S SPECIFICATIONS AND PUBLISHED DIRECTIONS. INSTALL PIPING TO CONFORM TO ONTARIO BUILDING CODE (CHAPTER 7).
- .2 INSTALL ABOVE GROUND PIPING TO CLEAR OTHER PIPING, INSULATION, OBSTRUCTIONS, ACCESS DOORS AND CONTROLS. TAKE BRANCHES OFF MAINS WITH FITTINGS AND 45° AND 90° ELBOWS. LOCATE VALVES FOR EACH OPERATION. LOCATE CLEANOUTS IN ACCESSIBLE LOCATIONS TO APPROVAL AND TO SUIT ACCESS.
- .3 DO NOT USE FERROUS PIPING, FITTINGS, BUSHINGS, NIPPLES OR PLUGS IN COPPER PIPING. PROVIDE DIELECTRIC BUSHINGS AT CONNECTIONS TO FERROUS MATERIALS OR EQUIPMENT ON WATER SYSTEMS.
- .4 SUPPLY AND INSTALL FLANGES, UNIONS OR COMPRESSION FITTINGS ON EQUIPMENT SIDE OF SHUT-OFF VALVES IN PIPING CONNECTIONS TO EQUIPMENT, TANKS AND FIXTURES SO SAME CAN BE DISCONNECTED FOR SERVICE. FLANGES AND UNIONS SHALL BE OF SAME MATERIAL AS PIPING.
- .5 CO-ORDINATE ROUTING OF PIPING WITH OTHER TRADES. PROVIDE INTERFERENCE DRAWINGS AS REQUIRED.
- .6 REFER TO MANUFACTURER'S INSTALLATION DRAWINGS.
- .7 INSTALL SYSTEMS SO THAT THEY CAN BE THOROUGHLY DRAINED AND ALL AIR ELIMINATED.
- .8 DURING WELDING OR SOLDERING PROCEDURES, PROVIDE A FIRE RETARDANT CLOTH, MAT OR BLANKET TO PROTECT THE STRUCTURE, AND ADEQUATE FIRE PROTECTION EQUIPMENT AT ALL LOCATIONS WHERE WORK IS BEING DONE.
- .9 PLUG AND/OR CAP ALL PIPE OPENINGS/FITTINGS DURING CONSTRUCTION.
- .10 CAST IRON PIPE TO HAVE ANTHER RUBBER GASKET MECHANICAL JOINTS, PC4 COLD CAULKING COMPOUND HUB AND SPIGOT JOINTS, CAULKED LEAD JOINTS WITH OAKUM AND SOFT PIG LEAD, OR BIBBY BISEAL. CONFINED SPACES TO BE MECHANICAL JOINTS.
- .11 THREADED PIPE JOINTS TO BE TRUE AND ROUND WITH FULL CUT THREADS, ENDS REAMED AND FILED WITH ALL BURRS REMOVED IRON TO IRON WITH A FILLER OF GRAPHITE AND OIL.
- .12 SOLDER JOINTS SHALL BE CAREFULLY CLEANED WITH EMERY CLOTH. USE "SILFOS" SILVER SOLDER FOR BURIED PIPING. SEE SECTION 15700 FOR TYPE OF SOLDER TO BE USE ON VARIOUS PIPING SYSTEMS.
- .13 MAKE JOINTS IN COPPER PIPING WITH 95/5 TIN/ANTIMONY SOLDER WITH NON-CORROSIVE SOLDERING FLUX. CLEAN, REAM AND THOROUGHLY TIN EACH JOINT AND REMOVE EXCESS SOLDER AND FLUX.
- .14 GRADING: UNLESS OTHERWISE NOTED, DRAINAGE AND WASTE SHALL GRADE DOWN IN THE DIRECTION OF FLOW, AS FOLLOWS:
- .1 UP TO AND INCLUDING 3" (80 MM): 1/4" IN 1 FOOT (1:50).
- .2 4" (100 MM) AND LARGER: 1/8" IN 1 FOOT (1:100).
- .15 GRADE VENT PIPING UP FROM FIXTURES SO IT IS SELF DRAINING.
- .16 IN ADDITION TO TESTS REQUIRED BY LOCAL AUTHORITIES, TEST PIPING AND DRAINS IN THE PRESENCE OF CONSULTANT AS HEREINAFTER DESCRIBED.
- .17 NOTIFY THE CONSTRUCTION MANAGER IN WRITING AT LEAST FORTY-EIGHT (48) HOURS PRIOR TO START OF TESTS. FAILURE TO DO SO MAY REQUIRE TEST TO BE RE-DONE.
- .18 PERFORM TESTS BEFORE APPLICATION OF PIPE INSULATION AND COVERING. TEST BURIED AND CONCEALED PIPING BEFORE BACKFILLING OR CONCEALING IN STRUCTURE. PROTECT EQUIPMENT AND PARTS NOT CAPABLE OF WITHSTANDING TEST PRESSURE DURING TESTS. MAKE LEAKS TIGHT WHILE SYSTEMS ARE STILL UNDER TEST. IF THIS IS IMPOSSIBLE, REMOVE AND RE-FIT DEFECTIVE PARTS. CAULKING OF THREADED JOINTS OR WELDS WILL NOT BE PERMITTED.
- .19 AFTER LEAKS HAVE BEEN REPAIRED, REPEAT TESTS AS OFTEN AS NECESSARY, AND TO ENSURE TIGHTNESS OF EACH SYSTEM.
- .20 INSTALL PIPING TO ALLOW FOR EXPANSION AND CONTRACTION COMPLETE WITH SWING JOINTS, EXPANSION LOOPS, AND ANCHORS AS NECESSARY. SILVER SOLDER EACH JOINT IN EXPANSION LOOPS WHERE USED.
- .21 PRESSURE TEST HOT WATER HEATING PIPING WITH 150 PSI (1034 KPA) FOR NOT LESS THAN FOUR (4) HOURS WITHOUT DECREASE IN PRESSURE.

1.2 PIPE HANGERS

- .1 ALL HORIZONTAL PIPING SHALL BE SUPPORTED AT LEAST EVERY 10'-0" (3000 MM), EXCEPT FOR PIPE 1-1/4" (32 MM) AND SMALLER WHERE 8'-0" (2400 MM) SPACING IS REQUIRED. PIPE HANGERS FOR COPPER PIPING SHALL BE ADJUSTABLE CLEVIS TYPE ANVIL FIG. 260 COMPLETE WITH INSULATION SHIELD SIMILAR TO ANVIL FIG. 168. HANGER ROD SHALL BE STEEL WITH COPPER NUT. CLEVIS HANGERS TO BE OUTSIDE PIPE INSULATION. BETWEEN THE SHIELD AND THE PIPE, INSTALL A SECTION OF HIGH DENSITY INSULATION EQUAL TO FOAMED GLASS (3.75 TO 5.0 LB DENSITY MATERIAL) COMPLETE WITH CONTINUOUS VAPOUR BARRIER. EXTEND HIGHER DENSITY INSULATION 2" (50 MM) BEYOND SHIELD. PIPE HANGERS AND SUPPORTS SHALL BE SECURED TO BEAMS, STEEL JOISTS, WALLS, FLOORS, ETC. DO NOT SUPPORT FROM METAL DECK.
- .2 ALL HANGERS AND RODS SHALL BE OF A SIZE AND WEIGHT TO SAFELY SUPPORT THE PIPING SYSTEM.
- .3 ALL HANGER RODS SHALL BE RUST RESISTANT GALVANIZED DIPPED.
- .4 ACCEPTABLE PRODUCTS: ANVIL, MYATT, TAYLOR

1.3 PIPING INSULATION

- .1 INSULATION SHALL CONFORM TO ASHRAE STANDARD 90.1 (LATEST EDITION).
- .2 ALL NEW PIPING AND FITTINGS SHALL BE INSULATED WITH INORGANIC GLASS FIBRES, BONDED WITH A THERMOSETTING RESIN COMPLETE WITH SELF SEALING LAP, "ASJ" ALL SERVICE JACKET AND 3" (80 MM) WIDE "ASJ" BUTT STRIPS.
- .3 DOMESTIC COLD AND HOT WATER PIPING INSULATION THICKNESS TO BE 1/2" (15 MM) FOR PIPE SIZES 1/2" TO 3" (13 MM TO 80 MM), COMPLETE WITH VAPOUR BARRIER, USING INSULATION K FACTOR .24 AT 75°F (24°C).
- .4 HOT WATER HEATING PIPING INSULATION THICKNESS TO BE 1" (25 MM) FOR PIPE SIZES 1/2" TO 3" (13 MM TO 80 MM), 1 1/2" (40 MM) THICK FOR PIPES SIZES 4" (100 MM) AND LARGER COMPLETE WITH VAPOUR BARRIER, USING INSULATION K FACTOR .24 AT 75°F (24°C).
- .5 ACCEPTABLE PRODUCTS: KNAUF, MANVILLE SCHULLER INTERNATIONAL, MANSON
- .6 ALL INSULATION SHALL BE APPLIED OVER A CLEAN, DRY SURFACE, AFTER ALL PRESSURE TESTING HAS BEEN CARRIED OUT AND REVIEWED BY THE CONSULTANT.
- .7 INSTALL INSULATION SHIELDS SUPPLIED BY MECHANICAL DIVISION.
- .8 THE INSULATION JOINTS SHALL BE BUTTED TIGHTLY. ADHERE THE VAPOUR BARRIER JACKET LAP WITH VAPOUR BARRIER ADHESIVE AND ADHERE THE 3" (80 MM) WIDE BUTT JOINT STRIPS OVER ALL END JOINTS WITH ADHESIVE TO ENSURE CONTINUOUS VAPOUR BARRIER. INSULATE ALL FITTINGS UP TO 2" (50 MM) WITH MITRE-CUT PIECES OF INSULATION AND PRESSURE-SENSITIVE, COLOUR-MATCHING TAPE. ALL EXPOSED FITTINGS 2" (50 MM) AND LARGER SHALL HAVE PRE-MOLDED "PVC" INSULATING FITTINGS COVERS.
- .9 ALL EXPOSED INSULATED PIPING AND FITTINGS SHALL BE FINISHED WITH A FIRE RETARDANT PVC JACKET.
- .10 NO ADDITIONAL FINISH NEED BE APPLIED TO CONCEALED PIPING.

G BAS SYSTEM

1. USE EXISTING BAS SYSTEM AND ADD ADDITIONAL INFRASTRUCTURE REQUIRED AS NECESSARY. CONTACT BAS SYSTEM SUPPLIER MENTION ON ME1-00 DRAWING.
2. SEE ME1-00 DRAWING FOR THE SEQUENCE OF CONTROL.
3. ALL WIRES IN CEILING SPACE SHALL BE PLENUM RATED.
4. ALL EXPOSED WIRES SHALL BE IN EMT CONDUITS.

DO NOT SCALE DRAWING. DIMENSION ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE

ALL DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE E&M CONSULTING ENGINEERS AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE E&M CONSULTING ENGINEERS WRITTEN PERMISSION.

2	ISSUED FOR TENDER	2025-03-24
1	ISSUED FOR PERMIT	2025-02-25
B	PROGRESS SUBMISSION	2025-02-04
A	PROGRESS SUBMISSION	2025-01-10

No. DESCRIPTION DATE

REVISIONS

24098	
Seal	KS

**E & M**  
**Consulting Engineers Inc.**  
4400 Highway 10  
Wentworth, ON L9A 4K1  
Canada  
www.eandmconsulting.com



www.eja.design | info@aja.design | 905.920.5121

project title: HAMILTON - WENTWORTH DISTRICT SCHOOL BOARD  
P02125 - LAKE AVENUE ELEMENTARY SCHOOL RENOVATIONS, WASHROOMS & CHANGEROOMS RENOVATIONS

Drawing Title:

SPECIFICATIONS

drawn: MH	scale: AS SHOWN
date: 01/2025	project number: 24-21
checked: KS	DRAWING NO:
date: 01/2025	M4-00
	0

Revision



UNIT HEATER SCHEDULE (HYDRONICS)															
TAG	AREA SERVED	MANUFACTURE	MODEL NUMBER	ARRANGEMENT NUMBER	DIMENSION (L X D X H)	HEATING MBH	GPM	COIL PRESSURE DROP FT. WG	AIR FLOW CFM	MOTOR HP	RPM	MOTOR AMPS	# OF FANS	POWER	ELECTRICAL WIRING INSTRUCTION
CH-1/CH-2/CH-4	R-136A/R-136B/R-138A	ENGINEERED AIR	CUH-1	24	660X711X241	16.10	1.62	1.52	185	1/25	1050	0.6	1	115/1/60	DIV. 26 TO WIRE UNIT COMPLETELY. ALL CONTROL WIRING BY MECHANICAL DIVISION. CONTROL VALVE TO BE PROVIDED BY THE BAS SUPPLIER AND WIRE TO THE FOR ON/OFF.
CH-3/CH-5	R-138/R-136	ENGINEERED AIR	CUH-3	24	660X711X241	21.45	2.17	3.57	300	1/25	1050	0.6	1	115/1/60	
NOTES															
1. EWT=180°F, ΔT= 20°F 2. THE UNIT TO BE SELECTED WITH BUILT-IN THERMOSTAT. 3. UNIT HEATER COLOR SHALL BE SELECTED BY ARCHITECT. ALLOW FOR FACTORY FINISH FINAL COAT.															

EXHAUST FAN SCHEDULE																	
TAG	AREA SERVED	MANUFACTURER AND MODEL NUMBER	VOLUME L/S (CFM)	EXTERNAL SP (PASCAL)	FAN RPM	WALL OPENING SIZE (MM)	WEIGHT WITH ACC'S (LBS)	REMARKS	WIRING FOR MECHANICAL EQUIPMENT SCHEDULE						ROOM STARTER TYPE	REMOTE CONTROL DEVICE	ELECTRICAL WIRING SCOPE
									MOTOR								
									SIZE (HP)	V/PH/HZ	MOTOR RPM	FLA (AMPS)	MCA	MOCP			
EF-1	R-136/R-136A/R-136B/R-137A/R-137B	GREENHECK SQ-130	472 (1000)	125	1140	–	91		1/3	115/1/60	1140	7.2	–	15	MAG. STARTER HOA	BAS	DIV. 26 TO PROVIDE MAGNETIC STARTER C/W HAND/OFF/AUTO SWITCH & PILOT LIGHTS AND WIRE UNIT COMPLETELY THROUGH DISCONNECT SWITCH SUPPLIED BY MECHANICAL DIVISION. ALL CONTROL WIRING TO BAS BY MECHANICAL DIVISION. BAS SHALL ENABLE/DISABLE AND MONITOR STATUS OF THE FAN. ALL STARTERS SHALL BE LOCATED IN STORAGE ROOM 138A BY THE ELECTRICAL CONTRACTOR.
EF-2	R-138A	GREENHECK SQ-90-VG	94 (200)	100	1300	–	35		1/6	115/1/60	–	2.8	–	15	MAG. STARTER HOA	BAS	
EF-3	STAFF WASHROOMS	GREENHECK SQ-90-VG	94 (200)	100	1300	–	35		1/6	115/1/60	–	2.8	–	15	MAG. STARTER HOA	BAS	
EF-4	R-138B	GREENHECK SQ-90-VG	189 (400)	100	1300	–	34		1/6	115/1/60	–	2.8	–	15	MAG. STARTER HOA	BAS	
NOTES: 1. MOTOR WITH CSA APPROVAL 2. SWITCH, NEMA-1, JUNCTION BOX MOUNTED & WIRED 3. GRAVITY OPERATED BACK DRAFT DAMPER 4. COATED WITH PERMATECTOR, CONCRETE GRAY-RAL 7023, FAN AND ATTACHED ACCESSORIES. ALUMINUM WHEEL MATERIAL 5. ISOLATORS & BRACKETS, SPRING HANGING KIT(S) FOR INDOOR FANS																	

MECHANICAL SCHEDULE – BASEBOARD ELECTRIC HEATER									
TAG	MANUFACTURER	MODEL	LOCATION	TYPE	QTY.	FINISH/ COLOUR	CAPACITY (KW)	POWER (V/ø/Hz)	ELECTRICAL WIRING SCOPE
BBH 1	OUELLET	OFM0502	STAFF WASHROOM (138B)	OFM	1	STANDARED	0.5	120V/1PH	DIV. 26 TO WIRE UNIT COMPLETELY THROUGH DISCONNECT SWITCH SUPPLIED BY MECHANICAL DIVISION.
BBH 2	OUELLET	OFM0502	STAFF WASHROOM (138B)	OFM	1	STANDARED	0.5	120V/1PH	
NOTES,  1. REFER TO SPECIFICATIONS FOR ADDITIONAL DETAILS. 2. OR APPROVED EQUIVALENT AS OUTLINED IN THE SPECIFICATIONS 3. BUILT IN THERMOSTAT 4. DISCONNECT SWITCH									

BUILDING AUTOMATION SYSTEM

INCLUDE IN PRICE TO RETAIN SCHOOL BOARDS BAS SYSTEM PROVIDER (SIEMENS CANADA- JAKE RENDULJC ACCOUNT EXECUTIVE 1577 NORTH SERVICE ROAD EAST, LBH 0H6, OAKVILLE, ON MOBILE: 905-541-7433 EMAIL: JAKE.RENDULJC@SIEMENS.COM) TO CONTROL NEW CABINET HEATERS AND EXHAUST FANS. ALL CONTROL WIRING AND CONDUITS SHALL BE INCLUDED.

BAS PROVIDER SHALL DETERMINE ADDITIONAL SUB PANELS OR ANY OTHER UPGRADES REQUIRED AND PRICE ACCORDINGLY.

BAS POINT LIST

1. CH-1,2,3,4,5 CABINET HEATERS – ON/OFF CONTROL OF THE VALVE. VALVE SHALL BE SUPPLIED BY THE BAS SUPPLIER FOR MECHANICAL CONTRACTOR TO INSTALL.
2. EF-1,2,3,4- ON/OFF/STATUS SIGNALS. SUPPLY AND INSTALL A FLOW SENSOR IN EXHAUST DUCT BY THE BAS SUPPLIER.
3. BAS SHALL ENABLE DISABLE & MONITOR STATUS OF THE FAN. ALL STARTERS SHALL BE LOCATED IN STORAGE ROOM 138A BY THE ELECTRICAL CONTRACTOR.

NOMENCLATURE (APPLICABLE ONLY FOR THIS DRAWING)	
MCA –	MINIMUM CIRCUIT AMPACITY
MFA –	MAXIMUM FUSE AMPACITY
BIS –	BUILT-IN START
TS –	THERMOSTAT
HP –	HORSEPOWER
DISC –	DISCONNECT
BAS –	BUILDING AUTOMATION SYSTEM
FRAC–	FRACTIONAL HORSEPOWER

LEGEND FOR MECHANICAL EQUIPMENT WIRING SCHEDULE	
AM – ACTUATOR MOTOR	KMSW – KEY OPERATED MOMENTARY CONTACT SWITCH
APS – AIR PROVING SWITCH	KSW/PL – KEY SWITCH(15A, 120V,SPST, LOCK TYPE C/W PILOT LIGHT)
AST – AQUASTAT	LS – LEVEL SWITCH
BAS – BUILDING AUTOMATION SYSTEM	LWCO – LOW WATER CUT OFF
BIS – BUILT IN START	MAG – MAGNETIC STARTER
C1 – EEMAC-1 TYPE DISC. SWITCH	MAN – MANUAL STARTER
C2 – EEMAC-2 TYPE DISC. SWITCH	MCA – MINIMUM CIRCUIT AMPS
C3R – EEMAC-3R TYPE DISC. SWITCH	MCC – MOTOR CONTROL CENTRE
C4 – EEMAC-4 TYPE DISC. SWITCH	MFA – MAXIMUM FUSE AMPACITY
C12 – EEMAC-12 TYPE DISC. SWITCH	MOCP – MAXIMUM OVER CURRENT PROTECTION
COMB – COMBINATION MAGNETIC STARTER	MVS – MONITORED VALVE SWITCH
CP – CONTROL PANEL	ODT – OFF DELAY TIMER
CSR – CURRENT SENSING RELAY	PB – PUSHBUTTON ON/OFF SWITCH IN STARTER COVER
CT – CONTROL TRANSFORMER	PL – PILOT LIGHT IN STARTER COVER
QWSV – COLD WATER SOLENOID VALVE	PLG – PLUG
DISC – DISCONNECT	PS – PRESSURE SWITCH
DM – DAMPER MOTOR	RPB – REMOTE STOP/START PUSHBUTTON
DMSW – DAMPER MOTOR SWITCH	RPL – REMOTE PILOT LIGHT
DVR – DOUBLE VOLTAGE RELAY	SD – SMOKE DETECTOR (DUCT TYPE)
FA – FIRE ALARM SYSTEM CONNECTION	SS – SPEED SWITCH
FL – FLOAT SWITCH	SLS & PL – SELECTOR SWITCH AND PILOT LIGHT
FLA – FULL LOAD RUNNING AMPERES	SV – SOLENOID VALVE
FPU – FIELD PROCESSOR UNIT BY DIV. 15900*	SW – HP RATED TOGGLE SWITCH
FPU/SS – START/STOP CONTROL OUTPUT FROM FPU*	T – THERMOSTAT OR TEMPERATURE SENSING UNIT
FPU/ST – MOTOR RUNNING STATUS INPUT TO FPU*	TC – TEMPERATURE CONTROLLER
FRAC – FRACTIONAL HORSEPOWER	T1 – TIMER (INTERVAL)
FS – FLOW SWITCH	T7 – TIMER (7-DAY)
GSV – GAS SOLENOID VALVE	TRS – THERMOSTAT REVERSING SWITCH
HP – HORSEPOWER	TS – THERMOSTAT
HOA – HAND/OFF/AUTO SWITCH IN STARTER COVER	TOA – TEST/OFF/AUTO SWITCH IN COVER (SPRING RETURN TEST TO OFF)
HUM – HUMIDISTAT	VM – VALVE MOTOR
HWSV – HOT WATER SOLENOID VALVE	VFD (VSD) – VARIABLE FREQUENCY (OR SPEED) DRIVE
IRS – INFRARED SENSOR	

DO NOT SCALE DRAWING. DIMENSION ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE.  
ALL DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE E&M CONSULTING ENGINEERS AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE E&M CONSULTING ENGINEERS WRITTEN PERMISSION.

2	ISSUED FOR TENDER	2025-03-24
1	ISSUED FOR PERMIT	2025-02-25
B	PROGRESS SUBMISSION	2025-02-04
A	PROGRESS SUBMISSION	2025-01-10

No.	DESCRIPTION	DATE
REVISIONS		

24098	Seal	KS
-------	------	----

**E & M**  
Consulting Engineers Inc.  
2401 Highway 104  
Markham, ON L3R 0A1  
www.eandmconsulting.com












































Project No: HAMILTON - WENTWORTH DISTRICT SCHOOL BOARD P02125 - LAKE AVENUE ELEMENTARY SCHOOL RENOVATIONS. WASHROOMS & CHANGEROOMS RENOVATIONS












































Drawing Title: MECHANICAL & ELECTRICAL SCHEDULES















































drawn: MH	scale: AS SHOWN
date: 01/2025	project number: 24-21
checked: KS	DRAWING NO:
date:	ME1-00
	Revision

















ELECTRICAL LEGEND

POWER & DISTRIBUTION SYSTEMS	
	UTILITY DISCONNECT.
	DELTA STAR POWER TRANSFORMER.
	CIRCUIT BREAKER.
	CIRCUIT BREAKER. (DRAW OUT TYPE).
	CIRCUIT BREAKER. (DRAW OUT TYPE) WITH MICROPROCESSOR BASED TRIP UNIT.
	FUSED DISCONNECT.
	NON FUSED DISCONNECT.
	HI OR LOW VOLTAGE FUSE.
	CUSTOMER OR UTILITY ENERGY METER.
	ELECTRICAL GROUND.
	LIGHTNING, ARRESTORS(03) AND GROUND.
	PANELBOARD (SURFACE MOUNT).
	PANELBOARD (RECESSED MOUNT).
	ENCLOSED BUS ASSEMBLY.
	CABLE TRAY (LADDER OR TROUGH)
RECEPTACLE/DIRECT CONNECTIONS	
	120V, 2P, 3W, 15A DUPLEX RECEPTACLE (CSA #5 SERIES).
	120V, 2P, 3W, 15A SPLIT TYPE DUPLEX RECEPTACLE.
	120V, 2P, 3W, 15/20A 1-SLOT TYPE DUPLEX RECEPTACLE. CSA#5 SERIES FOR OFFICE AND GENERAL AREAS.
	120V, 2P, 3W, 15A FOUR PLEX RECEPTACLE 2. DUPLEXES UNDER COMMON PLATE).
	120V, 2P, 3W, 15A DUPLEX RECEPTACLE WITH USB CHARGING PORT.
	120V, 2P, 3W SINGLE RECEPTACLE (CSA #5 SERIES).
	250V, 2P, 3W SINGLE RECEPTACLE (CSA #6 SERIES).
	125/250V, 3P, 4W SINGLE RECEPTACLE (CSA #14 SERIES).
	250VDC/600VAC, 3P, 4W SINGLE RECEPTACLE (CSA #L17 SERIES).
	1 PHASE, 3W DIRECT CONNECTION (L, N, G) OR (L1, L2, G).
	3 PHASE, 4W DIRECT CONNECTION (L1, L2, L3, G).
	3 PHASE, 5W DIRECT CONNECTION (L1, L2, L3, N, G).
	1 PHASE, 4W DIRECT CONNECTION (L1, L2, N, G).
	FLOOR FLUSH MOUNTED OUTLET BOX C/W THREE(3) 120V, 2P, 3W, 15A DUPLEX RECEPTACLE, TWO(2) DATA OUTLETS.
	FLOOR FLUSH MOUNTED OUTLET BOX C/W TWO(2) 120V, 2P, 3W, 15A DUPLEX RECEPTACLE
	MODULAR SYSTEM FURNITURE POWER & COMMUNICATION CABLING CONNECTION POINT OUTLET BOX. SUBSCRIPT 'f' DENOTES FLUSH MOUNTED IN FLOOR.
	FLOOR MOUNTED STATIC GROUNDING RECEPTACLE
	HAND DRYER
	THERMOSTAT.
	MAGNETIC DOOR HOLD OPEN DEVICE.
<div>NOTES</div>	1. DIRECT CONNECTION VOLTAGE INFORMATION INDICATION BY CIRCUIT No.
	2. UNLESS NOTED OTHERWISE MOUNTING HEIGHT OF ALL OUTLETS IS 455mm (18") A.F.F.
	3. UNLESS NOTED OTHERWISE (IE: 30A, 20A) ALL RECEPTACLES/DIRECT CONNECTIONS RATED FOR 15A.
MISCELLANEOUS	
	ROOM MODULAR CONTROL PANEL.
	NURSE CALL MASTER CONTROL WITH HANDSET
	NURSE CALL DOME LIGHT (WALL MOUNTED).
	NURSE CALL DOME LIGHT (CEILING MOUNTED).
	PUSH BUTTON
	BELL


KITCHEN/LAUNDRY APPLIANCES	
	15A, 120V-1Ø DUPLEX RECEPTACLE FOR DISHWASHER, LOCATED AS PER ARCHITECTURAL DRAWINGS.
	15A, 120V-1Ø DUPLEX RECEPTACLE FOR FRIDGE, LOCATED AS PER ARCHITECTURAL DRAWINGS.
	15A, 120V-1Ø DUPLEX RECEPTACLE FOR UNDER-COUNTER FRIDGE, LOCATED AS PER ARCHITECTURAL DRAWINGS.
	15A, 120V-1Ø DUPLEX RECEPTACLE FOR KITCHEN HOOD, LOCATED AS PER ARCHITECTURAL DRAWINGS.
	30A, 120V/208V-1Ø(14-30R) RECEPTACLE FOR DRYER, LOCATED AS PER ARCHITECTURAL DRAWINGS.
	15A, 120V-1Ø DUPLEX RECEPTACLE FOR WASHER, LOCATED AS PER ARCHITECTURAL DRAWINGS.
	15A, 120V-1Ø DUPLEX RECEPTACLE FOR WASHER, AND 30A, 120/280V-1Ø(14-30R) RECEPTACLE FOR DRYER. LOCATED AS PER ARCHITECTURAL DRAWINGS.
	50A, 120V/208V-1Ø(14-50R) RECEPTACLE FOR STOVE, LOCATED AS PER ARCHITECTURAL DRAWINGS.
	20A, 120V-1Ø DUPLEX RECEPTACLE FOR MICROWAVE, LOCATED AS PER ARCHITECTURAL DRAWINGS.
	20A, 120V-1Ø DIRECT CONNECTION FOR BUILT-IN OVEN, LOCATED AS PER ARCHITECTURAL DRAWINGS.
	15A, 120V/208V-1Ø DUPLEX RECEPTACLE FOR EXHAUST FAN, LOCATED AS PER ARCHITECTURAL DRAWINGS.
	40A, 120V/208V-1Ø DIRECT CONNECTION FOR BUILT-IN COOKTOP, LOCATED AS PER ARCHITECTURAL DRAWINGS.
COMMUNICATION SYSTEMS	
	COMBINATION DATA/TELEPHONE OUTLET.
	SECOND DIGIT (NUMBER 2,") INDICATES QUANTITY OF TELEPHONE CABLES AND TELEPHONE JACKS IN OUTLET.
	FIRST DIGIT (NUMBER 1,") INDICATES QUANTITY OF DATA CABLES AND DATA JACKS IN OUTLET. IF FIRST DIGIT INCLUDES A SUFFIX "T", IT INDICATES "TTLNXX" DATA CABLE AND OUTLET.
	ALL JACKS UNDER ONE(1) COMMON PLATE. REFER TO FLOOR PLANS FOR CABLE AND JACKS QUANTITIES.
	SUBSCRIPT "W" INDICATES C/W VOICE JACK FOR WALL MOUNTED TELEPHONE AT 1500mm A.F.F.
	SUBSCRIPT "P" INDICATES PAY TELEPHONE.
	DATA OUTLET - COMPUTER OR PRINTER.
	TELEPHONE - SUBSCRIPT "P" INDICATES PAY TELEPHONE.
	COMBINATION MULTI-FUNCTION COMMUNICATION OUTLET.
	WIRELESS ACCESS POINT
INTERCOM SYSTEM	
	INTERCOM MASTER STATION
	INTERCOM STATION
PAGING AND SOUND SYSTEM	
	RECESSED CEILING MOUNTED SPEAKER.
	COMBINATION WALL MOUNTED SPEAKER AND TALK-LISTEN PRIVACY SWITCH.
	SPEAKER MOUNTED IN ROOM MODULAR CONTROL PANEL.
	RECESSED WALL MOUNTED SPEAKER.
	RECESSED CEILING MOUNTED SPEAKER COMPLETE WITH HANDSFREE MIC. AND INTERCONNECTED TO WALL MOUNTED EMERGENCY PULLCORD ALARM DEVICE.
	SURFACE WALL MOUNTED SPEAKER.
	SURFACE CEILING MOUNTED SPEAKER.
	P.A. CALL SWITCH OR HANDSET.
	ADMINISTRATIVE CONSOLE UNIT OUTLET.
	LOCAL VOLUME CONTROLLER.
	AMPLIFIER.
	MICROPHONE OUTLET
TELEVISION AND AV.	
	TELEVISION OUTLET.
	AUDIO/VIDEO STATION
CLOCK SYSTEM	
	CLOCK RECEPTACLE. 120V, 15A, 1-GANG RECESSED SINGLE RECEPTACLE
MECHANICAL WIRING SYSTEMS	
	MECHANICAL EQUIPMENT/MOTOR.
	DISCONNECT SWITCH (UNFUSED). SUBSCRIPT INDICATES SIZE. SUBSCRIPT "N" INDICATES COMPLETE WITH SOLID NEUTRAL.
	DISCONNECT SWITCH (FUSED). SUBSCRIPT INDICATES FUSE RATING. SUBSCRIPT "N" INDICATES COMPLETE WITH SOLID NEUTRAL.
	MANUAL STARTER COMPLETE WITH PILOT LIGHT.
	MAGNETIC STARTER & HAND/OFF/AUTO SWITCH.
	COMBINATION MAGNETIC STARTER.
	TIME SWITCH.

FIRE ALARM SYSTEM	
	MANUAL PULL STATION C/W PROTECTIVE 9VDC BATTERY OPERATED LEXAN COVER.
	HEAT DETECTOR. COMBINATION, FIXED 57°C AND RATE OF RISE. SUBSCRIPT "X" INDICATES 88°C FIXED TEMPERATURE.
	HEAT DETECTOR. FIXED ONLY (57°C) SUBSCRIPT "X" INDICATES 88°C RATING.
	SMOKE DETECTOR. IONIZATION TYPE. SUBSCRIPT "R" INDICATES RELAY BASE.
	120V LOCAL SMOKE ALARM CEILING MOUNTED. IONIZATION TYPE.
	120V LOCAL SMOKE ALARM WITH STROBE.
	CARBON MONOXIDE.
	COMBINATION SMOKE/CARBON MONOXIDE/STROBE.
	AIR DUCT TYPE SMOKE DETECTOR.
	COMBINATION FIRE & SMOKE DAMPER
	REMOTE INDICATING LIGHT. SUBSCRIPT INDICATES FAN SYSTEM.
	FIRE ALARM HORN.
	FIRE ALARM BELL.
	FIRE ALARM STROBE
	COMBINATION FIRE HORN/STROBE LIGHT.
	SUPERVISED VALVE - SPRINKLER. SUBSCRIPT "P" DENOTES STANDPIPE.
	SPRINKLER FLOW SWITCH.
	SPRINKLER LOW PRESSURE SWITCH.
	MAGNETIC DOOR HOLD OPEN DEVICE.
	RECESSED FIRE ALARM SPEAKER (CEILING MOUNTED).
	RECESSED FIRE ALARM SPEAKER AND STROBE (CEILING MOUNTED).
	FIRE ALARM SPEAKER (WALL MOUNTED).
	FIRE ALARM SPEAKER AND STROBE (WALL MOUNTED).
	SURFACE FIRE ALARM SPEAKER (CEILING MOUNTED).
	SURFACE FIRE ALARM SPEAKER AND STROBE (CEILING MOUNTED).
	FIREFIGHTER HANDSET.
	FIRE ALARM ZONE DEMARCATON
	FIRE ALARM ZONE. NUMBER INDICATES ZONE NUMBER.
SECURITY SYSTEM	
	ELECTRIC DOOR STRIKE.
	SECURITY SYSTEM KEY PAD
	REQUEST TO EXIT BUTTON
	AUTOMATIC DOOR OPERATOR.
	DOOR ACTUATOR
	MAGNETIC DOOR LOCK.
	LOW VOLTAGE POWER SUPPLY FOR THE DOOR STRIKE.
	PUSH BUTTON.
	KEY PAD.
	SECURITY KEYSWITCH FOR ALARM SHUT OFF
	CARD READER.
	INFRA RED AUTOMATIC DOOR OPERATOR.
	EGRESS MOTION DETECTOR.
	AUDIBLE ALARM (BUZZER)
	INTRUSION ALARM WITH STROBE
	GLASS BREAK DETECTOR
	SECURITY SYSTEM MONITORING STATION
	PANIC ALARM
	MOTION DETECTOR. SUBSCRIPT "G" DENOTES GLASS BREAK
	DOOR/WINDOW CONTACT.
	CCTV CAMERA
	CEILING MOUNTED DOME CAMERA
EMERGENCY CALL ASSISTANCE	
	EMERGENCY CALL BUTTON.
	EMERGENCY CALL ASSISTANCE HORN.
	CEILING MOUNTED DOME LIGHT.
	WALL MOUNTED DOME LIGHT.
	"PUSH TO LOCK" PUSH BUTTON.
	"WAVE TO LOCK" BUTTON.

LIGHTING	
	LIGHT SWITCH
	SUBSCRIPTS: 2 - DOUBLE POLE (DPST). 3 - THREE WAY. 4 - FOUR WAY. D - DIMMER. K - KEY OPERATED. P - PILOT. S - SPEED SWITCH. LV - LOW VOLTAGE 2LVD - MULTI-ZONE/MULTI-BUTTON LOW VOLTAGE DIMMING SWITCH. NUMBER REPRESENTS NUMBER OF BUTTONS TO BE PROVIDED PLUS DIMMER.
	MULTIPLE SWITCH INSTALLATION UNDER COMMON PLATE.
	LOW VOLTAGE COMBINATION SWITCH AND OCCUPANCY SENSOR.
	LIGHTING FIXTURES. LETTER WITHIN INDICATES TYPE. CROSS HATCHING INDICATES WIRED TO EMERGENCY CIRCUIT. SUBSCRIPT "NL" INDICATES NIGHT LIGHT.
	EXIT SIGNS ARROWS INDICATE DIRECTION CEILING MOUNT, SINGLE FACE CEILING MOUNT, DOUBLE FACE WALL MOUNT, SINGLE FACE WALL MOUNT, DOUBLE FACE END WALL MOUNT, DOUBLE FACE EXIT SIGN & REMOTE HEAD COMBO
	DUAL TECHNOLOGY OCCUPANCY SENSOR LV - DENOTES LOW VOLTAGE W - DENOTES WALL MOUNT
	PHOTOCELL
	DAYLIGHT SENSOR
	WALL MOUNTED EMERGENCY LIGHTS. ARROW DENOTES AIMING DIRECTION.
	BATTERY UNIT (REFER TO LIGHTING FIXTURE SCHEDULE FOR DETAILS)
SMART BOARD/PROJECTOR REQUIREMENTS	
	15A, 120V, 1P, ISOLATED GROUND RECEPTACLE, 1 DATA OUTLET(COMPUTER) W/ 4 PORT COVER.
	15A, 120V, 1P, ISOLATED GROUND RECEPTACLE, 2 DATA OUTLET(COMPUTER) W/ 4 PORT COVER.
	4"x4" RECESSED BOX W/ BLANK COVER PLATE

MISCELLANEOUS ABBREVIATIONS/SUBSCRIPTS/SYMBOLS		
SUBSCRIPTS	A	- MOUNTING HEIGHT FOR DEVICES ABOVE COUNTER/SINK MILLWORK TO BE 1020mm FROM TOP OF DEVICE TO A.F.F. (UNLESS NOTED OTHERWISE).
	1-3	- TYPICAL NORMAL POWER CIRCUIT NUMBER EG. PANELBOARD LP-1 CIRCUIT NUMBER 3.
	E1-3	- TYPICAL ESSENTIAL POWER CIRCUIT NUMBER EG. PANELBOARD LPE-1 CIRCUIT NUMBER 3.
	1A-3	- TYPICAL CONTROL PANEL CIRCUIT NUMBER EG. PANELBOARD LP-1A CIRCUIT NUMBER 3.
	3P+N	- 3 POLE & UNSWITCHED NEUTRAL.
	AFF	- ABOVE FINISHED FLOOR.
	A	- ABOVE COUNTER
	B	- BENCH MOUNTED.
	C	- CEILING SPACE MOUNTED.
	CL	- CONTROLLED LOAD.
	D/I	- WITH DISCONNECT AND VISIBLE ISOLATION.
	EXP/EP	- EXPLOSION PROOF.
	F	- FLOOR MOUNTED.
	GF	- GROUND FAULT CIRCUIT INTERRUPTER.
	IG	- ISOLATED GROUND TYPE.
	MH	- MOUNTING HEIGHT.
	NL	- NIGHT LIGHT
	HL	- MOUNT AT 1188mm A.F.F.(TO THE BOTTOM)
	S	- SURGE SUPPRESSION TYPE DEVICE.
	T	- LOCKING TYPE (TWISTLOCK).
	V	- MOUNT IN VERTICAL FACE.
	WG	- WIREGUARD.
	WP	- WEATHERPROOF TYPE.
	Z	- MOUNT 42" (1065mm) A.F.F.
	PTZ	- PAN, TILT, ZOOM
E	- EXISTING TO REMAIN.	
ER	- EXISTING TO BE RELOCATED.	
RE	- RELOCATED DEVICE AT NEW LOCATION	
R	- EXISTING TO BE REMOVED	
N	- EXISTING TO BE REPLACED WITH NEW	
SR	- MOUNTED ON SURFACE RACEWAY	
IDENTIFICATIONS	ACB	- AIR CIRCUIT BREAKER.
	ATS	- AUTOMATIC TRANSFER SWITCH.
	AV	- AUDIO VISUAL.
	CM	- COFFEE MAKER.
	CR	- CASH REGISTER.
	CS	- COMMUNICATION STATION.
	DP	- DISTRIBUTION PANEL.
	EVR	- ELECTRONIC VOLTAGE REGULATOR.
	FR	- FRIDGE.
	GEN	- ELECTRICAL GENERATOR.
	HWD	- HOT WATER DISPENSER
	IM	- ICE MACHINE
	MCB	- MINIATURE CIRCUIT BREAKER.
	MCCB	- MOULDED CASE CIRCUIT BREAKER.
	MSB	- MAIN SWITCH BOARD (SERVICE ENTRANCE RATED).
	PC	- PHOTOCOPIER.
	PF	- POWER FACTOR CORRECTION CAPACITOR BANKS.
	PR	- PRINTER.
	SB	- SMARTBOARD.
	SP	- SPLITTER.
	SPD	- SURGE PROTECTION DEVICE
	TR	- LOW VOLTAGE TRANSFORMER.
	TV	- TELEVISION.
	TVSS	- TRANSIENT VOLTAGE SURGE SUPPRESSOR.
	UPS	- UNINTERRUPTIBLE POWER SUPPLY.
VM	- VENDING MACHINE.	
XFMR	- TRANSFORMER.	






### DRAWING NOTES

1. DISCONNECT & REMOVE ALL EXISTING FIRE ALARM DEVICES AS SHOWN, UNLESS OTHERWISE NOTED.
2. DISCONNECT & REMOVE ALL EXISTING LIGHTING & LIGHTING CONTROLS.
3. DISCONNECT & REMOVE EXISTING RECEPTACLES BACK TO SOURCE.
4. DISCONNECT & RELOCATED FIRE ALARM HORN & STROBE AS SHOWN ON NEW DRAWINGS.
5. DISCONNECT & REMOVE POWER TO HEATERS/EXHAUST FANS BACK TO SOURCE.

### GENERAL DEMO NOTES

1. THE ELECTRICAL CONTRACTOR SHALL, AS PART OF HIS WORK, PERFORM ALL RELATED DEMOLITION, MODIFICATIONS, RELOCATION OF ELECTRICAL DISTRIBUTION AND OTHER EQUIPMENT AND RELATED WORK, INCLUDING NEW WORK NECESSARY TO COMPLETE THE PROJECT.
2. IT IS SUGGESTED THAT THE ELECTRICAL CONTRACTOR ATTEND THE BID WALK-THROUGH AND VERIFY FIELD CONDITIONS TO DETERMINE THE EXTENT OF THE DEMOLITION AND NEW WORK PRIOR TO SUBMITTING BIDS.
3. THE ELECTRICAL CONTRACTOR SHALL VERIFY ALL TECHNICAL DETAILS OF EQUIPMENT TO BE REMOVED. WHERE THERE IS A DISCREPANCY WITH THE TENDER DOCUMENTS, CONTRACTOR SHALL ENGAGE CONSULTANTS FOR DIRECTIONS. ELECTRICAL CONTRACTOR SHALL MAKE A LIST OF ALL EQUIPMENT TO BE REMOVED. THIS LIST SHALL BE WITH ALL FOLLOWING INFORMATION:
  - \*\* MAKE/MODELS
  - \*\* MANUFACTURER
  - \*\* TECHNICAL DETAILS
  - \*\* LOCATIONTHIS LIST SHALL BE SUBMITTED TO THE OWNER FOR RECORD PURPOSES.
4. THE ELECTRICAL CONTRACTOR SHALL NOT DISCONNECT EQUIPMENT AND ELECTRICAL CIRCUITS IN THE RENOVATION AREA OR ANY PART OF THE BUILDING WITHOUT PRIOR NOTIFICATION AND PERMISSION FROM THE OWNER. EXTREME CARE SHALL BE TAKEN TO MINIMIZE DISTURBANCE TO THE SURROUNDING AREA.
5. ITEMS REMOVED, AND NOT SCHEDULED TO BE RELOCATED SHALL BE OFFERED TO THE OWNER FOR THEIR USE AND IF NOT ACCEPTED BY THE OWNER, THE ELECTRICAL CONTRACTOR SHALL DISPOSE OF THE MATERIAL FROM THE SITE IN ACCORDANCE WITH LOCAL REGULATIONS. THE ELECTRICAL CONTRACTOR SHALL DELIVER ITEMS ACCEPTED BY THE OWNER TO THE DESIGNATED LOCATIONS AS DIRECTED BY THE OWNER.
6. IN ALL CASES WHERE WORK IS REMOVED, THE ELECTRICAL CONTRACTOR SHALL PROVIDE ALL NECESSARY MATERIALS, EQUIPMENT AND LABOR TO SUSTAIN OPERATION OF ALL PARTS OF THE SYSTEMS CONNECTING TO OR FROM THE PART REMOVED. COMPLETING ALL WORK IN STRICT ACCORDANCE WITH APPLICABLE CODES.
7. ALL WIRING, CABLES AND FEEDERS INCLUDING BOTH CONNECTED TO DEVICES AND EQUIPMENT TO BE DEMOLISHED AND EXISTING THAT WERE ABANDONED IN PLACE SHALL BE REMOVED BACK TO THEIR SOURCES. UNLESS NOTED OTHERWISE, CONDUITS AND/OR WIRING SHALL, WHERE NECESSARY, BE RE-CIRCUIT AROUND THE REMOVED PART, KEEPING OCCUPIED PARTS OF THE BUILDING SYSTEM IN FULL SERVICE.
8. ALL EXISTING CONDUITS WHICH HAVE BEEN ABANDONED OR ARE UNUSED SHALL BE REMOVED.
9. PROVIDE BLANK METAL COVER PLATES FOR ALL JUNCTION/DEVICE BOXES NO LONGER IN USE THAT ARE EMBEDDED IN FLOOR SLAB OR MASONRY WALLS. PROVIDE PLUGS FOR ALL PANELS WHERE CONDUIT HAS BEEN REMOVED. COVER PLATES SHALL BE PAINTED TO MATCH EXISTING CONDITIONS.
10. WHERE REQUIRED COORDINATE WITH THE CONSULTANTS/OWNER FOR EXISTING PARTITIONS TO BE REMOVED TO FACILITATE WORK. DISCONNECT EXISTING BRANCH CIRCUITS SERVING DEVICES IN PARTITIONS TO BE REMOVED. MAINTAIN CONTINUITY OF CIRCUITS SERVING EXISTING DEVICES IN OTHER AREAS TO REMAIN.
11. LIGHTING FIXTURES: REMOVE LIGHTING FIXTURES AND SWITCH CONTROL WHEN THE FIXTURE TO BE REMOVED IS SERVED BY A CIRCUIT. THAT SUPPLIES FIXTURES IN OTHER AREAS THAT ARE TO REMAIN. THE ELECTRICAL CONTRACTOR SHALL MAINTAIN THE CONTINUITY OF THE CIRCUIT TO THE REMAINING FIXTURES.
12. POWER RECEPTACLES: REMOVE RECEPTACLES. WHEN THE RECEPTACLE TO BE REMOVED IS SERVED BY A CIRCUIT THAT SUPPLIES RECEPTACLES IN OTHER AREAS, THAT ARE TO REMAIN, THE ELECTRICAL CONTRACTOR SHALL MAINTAIN THE CONTINUITY OF THE CIRCUIT TO THE REMAINING RECEPTACLES.
13. FIRE ALARM SYSTEM: COORDINATE AND CONSULT WITH CURRENT F/A SYSTEM SERVICE CONTRACTOR OR THEIR QUALIFIED REPRESENTATIVE FOR ALL FIRE ALARM DEMOLITION AND MODIFICATIONS. OPERATION SHALL BE MAINTAINED OF EXISTING FIRE ALARM SYSTEM SPECIFICALLY AS IT RELATES TO ADJACENT AREAS WHICH ARE NOT INCLUDED IN THE SCOPE OF THIS PROJECT.
14. ELECTRICAL CONTRACTOR SHALL PROVIDE UPDATED TYPE WRITTEN PANEL DIRECTORIES FOR ALL PANELS AFFECTED BY THE DEMOLITION AND/OR NEW WORK. CIRCUIT BREAKERS NOT USED FOR NEW WORK SHALL BE LABELED AS SPARE.
15. FOR EXISTING DEVICES/CIRCUITRY THAT ARE INDICATED TO BE REMOVED BACK TO POINT OF ORIGIN-- THESE ITEMS ARE TO BE REMOVED BACK TO POINT OF ORIGIN UNLESS THEREWILL BE EXISTING DEVICES ON THE SAME CIRCUIT THAT ARE LOCATED OUTSIDE AREA OF WORK THAT ARE TO REMAIN. IN THAT CASE, REMOVE THE EXISTING DEVICES/CIRCUITRY IN AREA OF WORK BACK TO THESE EXISTING DEVICES TO REMAIN. ALL DEVICES/CIRCUITRY IN SURROUNDING AREAS THAT ARE TO REMAIN ARE TO BE KEPT ENERGIZED. FOR REMOVAL OF CONDUIT AND WIRING OUTSIDE OF AREA OF WORK COORDINATE AND SCHEDULE WITH OWNER PRIOR TO PERFORMING WORK.



DO NOT SCALE DRAWING. DIMENSION ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE.

ALL DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE E&M CONSULTING ENGINEERS AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE E&M CONSULTING ENGINEERS WRITTEN PERMISSION.

2	ISSUED FOR TENDER	2025-03-24
1	ISSUED FOR PERMIT	2025-02-25
B	PROGRESS SUBMISSION	2025-02-04
A	PROGRESS SUBMISSION	2025-01-10

No.	DESCRIPTION	DATE
-----	-------------	------

REVISIONS

24098

Seal

**E & M**  
**Consulting Engineers Inc.**  
2400 Dufferin Street  
Mississauga, ON L4X 1S3  
Canada  
www.eandmconsulting.com

**HWDSB**


**AMRA J**  
ARCHITECTS INC.  
www.aja.design | info@aja.design | 905.920.5121

Project Title:  
HAMILTON - WENTWORTH  
DISTRICT SCHOOL BOARD  
P02125 - LAKE AVENUE  
ELEMENTARY SCHOOL  
RENOVATIONS  
WASHROOMS & CHANGEROOMS  
RENOVATIONS

Drawing Title:  
ENLARGED PLANS DEMO -  
ELECTRICAL

drawn: MD	scale: AS SHOWN
date:	project number: 24-21
checked: MD	DRAWING NO: E1-00
date: 12/2024	0





OCCUPANCY SENSOR/SWITCH SCHEDULE		
SYMBOL	DESCRIPTION	ACCEPTABLE PRODUCTS
	LOW VOLTAGE DUAL TECHNOLOGY CEILING MOUNT OCCUPANCY SENSOR.	1. WATTSTOPPER DT-300 OR APPROVED EQUIVALENT
	LINE VOLTAGE DUAL TECHNOLOGY WALL SWITCH TYPE OCCUPANCY SENSOR WITH MANUAL ON/OFF	1. WATTSTOPPER DWS-301 OR APPROVED EQUIVALENT
	LOW VOLTAGE 1 BUTTON SWITCH	1. WATTSTOPPER LMSW-210 OR APPROVED EQUIVALENT

### LIGHTING CONTROL TYPES

NOT ALL CONTROL TYPES MAY HAVE BEEN USED. REFER TO LIGHTING DRAWINGS FOR ALL REQUIREMENTS. FOR ALL TYPES BELOW: 'UNOCCUPIED DURATION SHALL BE 5 MINUTES.

CT0 - NO CONTROL ALWAYS 'ON' 27/7

CT1 - AUTOMATIC 'ON' / AUTOMATIC 'OFF' AUTO 'OFF' BY OCCUPANCY AFTER 15 MINUTES

LIGHTING CONTROLS	
ROOM	TYPE
CHANGE ROOM	CT1
WASHROOMS	CT1
STORAGE	CT1

### GENERAL NOTES

- THIS DRAWING ILLUSTRATES INTENT AND DOES NOT REPRESENT ALL REQUIRED CONTROL COMPONENTS, FINAL WIRING METHODS OR FIXTURE MOUNTING LOCATIONS. DETERMINE THE FINAL SYSTEM INSTALLATION BASED ON THE PRODUCT MANUFACTURER'S SHOP DRAWINGS.
- OCCUPANCY SENSORS SHALL BE MOUNTED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS SO THEY ARE CAPABLE OF OPERATING PROPERLY WITHOUT FALSE 'ON' OR PREMATURE 'OFF' OPERATIONS. DUAL TECHNOLOGY OCCUPANCY SENSORS SHALL NOT BE MOUNTED WITHIN 610mm OF ANY HVAC DIFFUSERS.
- REMOTE MOUNTED POWER SUPPLIES AND CONTROL DEVICES SHALL BE MOUNTED IN ACCESSIBLE LOCATIONS OUT OF VIEW OF PUBLIC.
- CEILING SPACE IS A RETURN AIR PLENUM. ANY DEVICES LOCATED IN CEILING SPACES SHALL BE PLENUM RATED.
- ALL WIRING IN FINISHED AREAS SHALL BE RUN CONCEALED IN WALLS/CEILINGS WHERE POSSIBLE. OTHERWISE PROVIDE SURFACE RACEWAYS SUCH AS WIREMOLD OR EQUIVALENT. EMT WILL NOT BE ACCEPTED UNLESS OTHERWISE NOTED.
- ALL ROOM CONTROLLERS SHALL BE DIMMING TYPE. FINAL LIGHTING DIMMING PRE-SETS TO BE DETERMINED ON SITE WITH THE OWNER DURING COMMISSIONING.
- ALL RECEPTACLES SHALL BE TAMPER RESISTANT TYPE.
- ALL NEW LIGHTING SHALL BE RE-CONNECTED TO THE EXISTING CIRCUIT. UPDATE EXISTING PANEL SCHEDULE TO MATCH ANY CHANGES TO CIRCUITS.

### DRAWING NOTES

- PROVIDE ADA COMPLIANT HAND DRYER. WORLD DRYER SLMDRI OR APPROVED EQUAL. HAND DRYER SHALL BE POLISHED STAINLESS STEEL. COORDINATE MOUNTING HEIGHT WITH ARCHITECT. PROVIDE 15A-1P GFCI BREAKER IN PANEL AND WIRE COMPLETELY.
- RE-CONNECT NEW LIGHTING FIXTURES TO EXISTING LIGHTING CIRCUITS.
- WIRE ALL NEW PAGING SPEAKERS TO EXISTING PAGING RACK. REFER TO SPECIFICATION FOR MORE DETAILS.
- WIRE ALL NEW FIRE ALARM DEVICES TO EXISTING FIRE ALARM PANEL. VERIFY ALL DEVICES AT THE COMPLETION OF THE PROJECT AND SUBMIT REPORT TO CONSULTANT.
- PROVIDE OF RECEPTACLE FOR WASHFOUNTAIN. COORDINATE EXACT LOCATION WITH MECHANICAL DIVISION.
- COMBINATION FIRE & SMOKE DAMPER PROVIDED BY MECHANICAL DIVISION. ELECTRICAL DIVISION TO PROVIDE SMOKE DETECTOR & WIRE TO DAMPER SUCH THAT DAMPER CLOSSES WITH DETECTION OF SMOKE. COORDINATE EXACT LOCATION & REQUIREMENTS WITH MECHANICAL DIVISION. WIRE TO EXISTING FLOOR FIRE ALARM ZONE. PROVIDE REMOTE INDICATOR ON CORRIDOR CEILING NEXT TO EACH DAMPER AS SHOWN.

LIGHTING FIXTURE SCHEDULE		
TYPE	DESCRIPTION	ACCEPTABLE PRODUCTS
BU-1	EMERGENCY BATTERY UNIT - 120V INPUT/12VDC OUTPUT - 2 HEAD WITH 5W LED LAMPS EACH - 100W FOR 30 MINUTE OPERATING TIME - AUTOMATIC SELF TEST	1. LUMACELL RGS SERIES OR APPROVED EQUIVALENT
Y1,2	INDOOR REMOTE HEAD (NUMBER RELATES TO # OF HEADS) - 12VDC INPUT - METAL HOUSING - 5W LED LAMP - 1,2,3... HEADS AS SPECIFIED IN DRAWINGS - 7' MOUNTING HEIGHT	1. LUMACELL MOM SERIES OR APPROVED EQUIVALENT
R20	LED FLAT PANEL WITH THE FOLLOWING ATTRIBUTES: - 1'x4' - 29W, 3800 LUMENS, 4000K, 120V - 80+ CRI, ROUND SMOOTH DIFFUSER - DLC LISTED - 0-10V DIMMING (1%) - V-GRID CEILING MOUNT	1. SIGNIFY CFJ FLUXPANEL LED GEN 2 OR APPROVED EQUIVALENT
R21	SAME AS R20 EXCEPT THE FOLLOWING ATTRIBUTES: - DRYWALL CEILING MOUNT	1. SIGNIFY CFJ FLUXPANEL LED GEN 2 OR APPROVED EQUIVALENT

PANEL NAME: <b>EXISTING LP-K-1</b>		MOUNTING: RECESSED		PANEL LOCATION: HALL WAY		42 CIRCUIT PANELBOARD	
MAINS: 225A 120/208V 3Ø 4W		ENCLOSURE: TYPE-1		BUSSING:		SCCR=10KA	
OTHER:							
LOAD DESCRIPTION	VA	BRKR	BRKR	VA	LOAD DESCRIPTION	BRKR	BRKR
EXISTING	-	1	20A	2	EXISTING	20A	20A
EXISTING	-	3	20A	4	EXISTING	20A	20A
EXISTING	-	5	20A	6	EXISTING	20A	20A
EXISTING	-	7	15A	8	EXISTING	15A	15A
EXISTING	-	9	15A	10	EXISTING	15A	15A
EXISTING	-	11	15A	12	EXISTING	15A	15A
EXISTING	-	13	15A	14	EXISTING	15A	15A
EXISTING	-	15	15A	16	EXISTING	15A	15A
EXISTING	-	17	15A	18	EXISTING	15A	15A
EXISTING	-	19	20A	20	EXISTING	20A	20A
EXISTING	-	21	15A	22	EXISTING	15A	15A
EXISTING	-	23	15A	24	EXISTING	15A	15A
EXISTING	-	25	15A	26	EXISTING	15A	15A
EXISTING	-	27	15A	28	EXISTING	15A	15A
EXISTING	-	29	15A	30	EXISTING	15A	15A
RECEP- 136,136A,136B,138,138A	1000	31	15A	32	1000 HAND DRYER - 136A	15A	15A
BU-1, FIRE SMOKE DAMPERS	150	33	15A	34	1000 HAND DRYER - 136B	15A	15A
CH 1-5(136A,136B,138A,138,136)	345	35	15A	36	1000 HAND DRYER - 138B	15A	15A
EF-1	828	37	15A	38	1000 HAND DRYER - 138C	15A	15A
EF - 2,3	644	39	15A	40	322 EF-4	15A	15A
BASEBOARD HEATER (BBH -1,2)	1000	41	15A	42	100 WASH FOUNTAINS	15A	15A
CONNECTED LOAD (L.H.)	-				CONNECTED LOAD (R.H.)		

NOTES: BREAKERS SHOWN IN GREY ARE EXISTING. PROVIDE ALL OTHER BREAKERS.  
\* DENOTES 5mA GFCI BREAKER

DO NOT SCALE DRAWING. DIMENSION ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE.  
ALL DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE E&M CONSULTING ENGINEERS AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE E&M CONSULTING ENGINEERS WRITTEN PERMISSION.

2	ISSUED FOR TENDER	2025-03-24
1	ISSUED FOR PERMIT	2025-02-25
B	PROGRESS SUBMISSION	2025-02-04
A	PROGRESS SUBMISSION	2025-01-10

No.	DESCRIPTION	DATE
-----	-------------	------

REVISIONS	
-----------	--

24098	Seal
-------	------

**E & M**  
**Consulting Engineers Inc.**  
24098  
www.emconsultingeng.com

**HWDSB**  
**AMRA J**  
**ARCHITECTS INC.**  
www.aja.design | info@aja.design | 905.920.5121

Project No:  
HAMILTON - WENTWORTH DISTRICT SCHOOL BOARD  
P02125 - LAKE AVENUE ELEMENTARY SCHOOL RENOVATIONS, WASHROOMS & CHANGEROOMS RENOVATIONS

Drawing Title:  
ENLARGED PLANS NEW - ELECTRICAL

drawn: MD	scale: AS SHOWN
date:	project number: 24-21
checked: MD	DRAWING NO: E2-00
date:	0
08/2024	Revision







UNIT HEATER SCHEDULE (HYDRONICS)															
TAG	AREA SERVED	MANUFACTURE	MODEL NUMBER	ARRANGEMENT NUMBER	DIMENSION (L X D X H)	HEATING MBH	GPM	COIL PRESSURE DROP FT. WG	AIR FLOW CFM	MOTOR HP	RPM	MOTOR AMPS	# OF FANS	POWER	ELECTRICAL WIRING INSTRUCTION
CH-1/CH-2/CH-4	R-136A/R-136B/R-138A	ENGINEERED AIR	CUH-1	24	660X711X241	16.10	1.62	1.52	185	1/25	1050	0.6	1	115/1/60	DIV. 26 TO WIRE UNIT COMPLETELY. ALL CONTROL WIRING BY MECHANICAL DIVISION. CONTROL VALVE TO BE PROVIDED BY THE BAS SUPPLIER AND WIRE TO THE FOR ON/OFF.
CH-3/CH-5	R-138/R-136	ENGINEERED AIR	CUH-3	24	660X711X241	21.45	2.17	3.57	300	1/25	1050	0.6	1	115/1/60	
NOTES															
1. EWT=180°F, ΔT= 20°F 2. THE UNIT TO BE SELECTED WITH BUILT-IN THERMOSTAT. 3. UNIT HEATER COLOR SHALL BE SELECTED BY ARCHITECT. ALLOW FOR FACTORY FINISH FINAL COAT.															

EXHAUST FAN SCHEDULE																	
TAG	AREA SERVED	MANUFACTURER AND MODEL NUMBER	VOLUME L/S (CFM)	EXTERNAL SP (PASCAL)	FAN RPM	WALL OPENING SIZE (MM)	WEIGHT WITH ACC'S (LBS)	REMARKS	WIRING FOR MECHANICAL EQUIPMENT SCHEDULE						ROOM STARTER TYPE	REMOTE CONTROL DEVICE	ELECTRICAL WIRING SCOPE
									MOTOR								
									SIZE (HP)	V/PH/HZ	MOTOR RPM	FLA (AMPS)	MCA	MOCP			
EF-1	R-136/R-136A/R-136B/R-137A/R-137B	GREENHECK SQ-130	472 (1000)	125	1140	–	91		1/3	115/1/60	1140	7.2	–	15	MAG. STARTER HOA	BAS	DIV. 26 TO PROVIDE MAGNETIC STARTER C/W HAND/OFF/AUTO SWITCH & PILOT LIGHTS AND WIRE UNIT COMPLETELY THROUGH DISCONNECT SWITCH SUPPLIED BY MECHANICAL DIVISION. ALL CONTROL WIRING TO BAS BY MECHANICAL DIVISION. BAS SHALL ENABLE/DISABLE AND MONITOR STATUS OF THE FAN. ALL STARTERS SHALL BE LOCATED IN STORAGE ROOM 138A BY THE ELECTRICAL CONTRACTOR.
EF-2	R-138A	GREENHECK SQ-90-VG	94 (200)	100	1300	–	35		1/6	115/1/60	–	2.8	–	15	MAG. STARTER HOA	BAS	
EF-3	STAFF WASHROOMS	GREENHECK SQ-90-VG	94 (200)	100	1300	–	35		1/6	115/1/60	–	2.8	–	15	MAG. STARTER HOA	BAS	
EF-4	R-138B	GREENHECK SQ-90-VG	189 (400)	100	1300	–	34		1/6	115/1/60	–	2.8	–	15	MAG. STARTER HOA	BAS	
NOTES: 1. MOTOR WITH CSA APPROVAL 2. SWITCH, NEMA-1, JUNCTION BOX MOUNTED & WIRED 3. GRAVITY OPERATED BACK DRAFT DAMPER 4. COATED WITH PERMATECTOR, CONCRETE GRAY-RAL 7023, FAN AND ATTACHED ACCESSORIES. ALUMINUM WHEEL MATERIAL 5. ISOLATORS & BRACKETS, SPRING HANGING KIT(S) FOR INDOOR FANS																	

MECHANICAL SCHEDULE – BASEBOARD ELECTRIC HEATER									
TAG	MANUFACTURER	MODEL	LOCATION	TYPE	QTY.	FINISH/ COLOUR	CAPACITY (KW)	POWER (V/ø/Hz)	ELECTRICAL WIRING SCOPE
BBH 1	OUELLET	OFM0502	STAFF WASHROOM (138B)	OFM	1	STANDARED	0.5	120V/1PH	DIV. 26 TO WIRE UNIT COMPLETELY THROUGH DISCONNECT SWITCH SUPPLIED BY MECHANICAL DIVISION.
BBH 2	OUELLET	OFM0502	STAFF WASHROOM (138B)	OFM	1	STANDARED	0.5	120V/1PH	
NOTES,  1. REFER TO SPECIFICATIONS FOR ADDITIONAL DETAILS. 2. OR APPROVED EQUIVALENT AS OUTLINED IN THE SPECIFICATIONS 3. BUILT IN THERMOSTAT 4. DISCONNECT SWITCH									

BUILDING AUTOMATION SYSTEM

INCLUDE IN PRICE TO RETAIN SCHOOL BOARDS BAS SYSTEM PROVIDER (SIEMENS CANADA- JAKE RENDULJC ACCOUNT EXECUTIVE 1577 NORTH SERVICE ROAD EAST, LBH 0H6, OAKVILLE, ON MOBILE: 905-541-7433 EMAIL: JAKE.RENDULJC@SIEMENS.COM) TO CONTROL NEW CABINET HEATERS AND EXHAUST FANS. ALL CONTROL WIRING AND CONDUITS SHALL BE INCLUDED.

BAS PROVIDER SHALL DETERMINE ADDITIONAL SUB PANELS OR ANY OTHER UPGRADES REQUIRED AND PRICE ACCORDINGLY.

BAS POINT LIST

1. CH-1,2,3,4,5 CABINET HEATERS – ON/OFF CONTROL OF THE VALVE. VALVE SHALL BE SUPPLIED BY THE BAS SUPPLIER FOR MECHANICAL CONTRACTOR TO INSTALL.
2. EF-1,2,3,4- ON/OFF/STATUS SIGNALS. SUPPLY AND INSTALL A FLOW SENSOR IN EXHAUST DUCT BY THE BAS SUPPLIER.
3. BAS SHALL ENABLE DISABLE & MONITOR STATUS OF THE FAN. ALL STARTERS SHALL BE LOCATED IN STORAGE ROOM 138A BY THE ELECTRICAL CONTRACTOR.

NOMENCLATURE (APPLICABLE ONLY FOR THIS DRAWING)	
MCA –	MINIMUM CIRCUIT AMPACITY
MFA –	MAXIMUM FUSE AMPACITY
BIS –	BUILT-IN START
TS –	THERMOSTAT
HP –	HORSEPOWER
DISC –	DISCONNECT
BAS –	BUILDING AUTOMATION SYSTEM
FRAC–	FRACTIONAL HORSEPOWER

LEGEND FOR MECHANICAL EQUIPMENT WIRING SCHEDULE	
AM – ACTUATOR MOTOR	KMSW – KEY OPERATED MOMENTARY CONTACT SWITCH
APS – AIR PROVING SWITCH	KSW/PL – KEY SWITCH(15A, 120V,SPST, LOCK TYPE C/W PILOT LIGHT)
AST – AQUASTAT	LS – LEVEL SWITCH
BAS – BUILDING AUTOMATION SYSTEM	LWCO – LOW WATER CUT OFF
BIS – BUILT IN START	MAG – MAGNETIC STARTER
C1 – EEMAC-1 TYPE DISC. SWITCH	MAN – MANUAL STARTER
C2 – EEMAC-2 TYPE DISC. SWITCH	MCA – MINIMUM CIRCUIT AMPS
C3R – EEMAC-3R TYPE DISC. SWITCH	MCC – MOTOR CONTROL CENTRE
C4 – EEMAC-4 TYPE DISC. SWITCH	MFA – MAXIMUM FUSE AMPACITY
C12 – EEMAC-12 TYPE DISC. SWITCH	MOCP – MAXIMUM OVER CURRENT PROTECTION
COMB – COMBINATION MAGNETIC STARTER	MVS – MONITORED VALVE SWITCH
CP – CONTROL PANEL	ODT – OFF DELAY TIMER
CSR – CURRENT SENSING RELAY	PB – PUSHBUTTON ON/OFF SWITCH IN STARTER COVER
CT – CONTROL TRANSFORMER	PL – PILOT LIGHT IN STARTER COVER
QWSV – COLD WATER SOLENOID VALVE	PLG – PLUG
DISC – DISCONNECT	PS – PRESSURE SWITCH
DM – DAMPER MOTOR	RPB – REMOTE STOP/START PUSHBUTTON
DMSW – DAMPER MOTOR SWITCH	RPL – REMOTE PILOT LIGHT
DVR – DOUBLE VOLTAGE RELAY	SD – SMOKE DETECTOR (DUCT TYPE)
FA – FIRE ALARM SYSTEM CONNECTION	SS – SPEED SWITCH
FL – FLOAT SWITCH	SLS & PL – SELECTOR SWITCH AND PILOT LIGHT
FLA – FULL LOAD RUNNING AMPERES	SV – SOLENOID VALVE
FPU – FIELD PROCESSOR UNIT BY DIV. 15900*	SW – HP RATED TOGGLE SWITCH
FPU/SS – START/STOP CONTROL OUTPUT FROM FPU*	T – THERMOSTAT OR TEMPERATURE SENSING UNIT
FPU/ST – MOTOR RUNNING STATUS INPUT TO FPU*	TC – TEMPERATURE CONTROLLER
FRAC – FRACTIONAL HORSEPOWER	T1 – TIMER (INTERVAL)
FS – FLOW SWITCH	T7 – TIMER (7-DAY)
GSV – GAS SOLENOID VALVE	TRS – THERMOSTAT REVERSING SWITCH
HP – HORSEPOWER	TS – THERMOSTAT
HOA – HAND/OFF/AUTO SWITCH IN STARTER COVER	TOA – TEST/OFF/AUTO SWITCH IN COVER (SPRING RETURN TEST TO OFF)
HUM – HUMIDISTAT	VM – VALVE MOTOR
HWSV – HOT WATER SOLENOID VALVE	VFD (VSD) – VARIABLE FREQUENCY (OR SPEED) DRIVE
IRS – INFRARED SENSOR	

DO NOT SCALE DRAWING. DIMENSION ARE TO BE CHECKED AND VERIFIED BY THE CONTRACTOR ON SITE.  
ALL DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS ARE THE COPYRIGHT PROPERTY OF THE E&M CONSULTING ENGINEERS AND MUST BE RETURNED UPON REQUEST. REPRODUCTION OF DRAWINGS, SPECIFICATIONS AND RELATED DOCUMENTS IN WHOLE OR IN PART IS STRICTLY FORBIDDEN WITHOUT THE E&M CONSULTING ENGINEERS WRITTEN PERMISSION.

2	ISSUED FOR TENDER	2025-03-24
1	ISSUED FOR PERMIT	2025-02-25
B	PROGRESS SUBMISSION	2025-02-04
A	PROGRESS SUBMISSION	2025-01-10

No.	DESCRIPTION	DATE
REVISIONS		

24098	Seal	KS
-------	------	----

**E & M**  
Consulting Engineers Inc.  
2401 Highway 104  
Markham, ON L3R 0A1  
www.eandmconsulting.com



Project No: HAMILTON - WENTWORTH DISTRICT SCHOOL BOARD P02125 - LAKE AVENUE ELEMENTARY SCHOOL RENOVATIONS. WASHROOMS & CHANGEROOMS RENOVATIONS

Drawing Title: MECHANICAL & ELECTRICAL SCHEDULES

drawn: MH	scale: AS SHOWN
date: 01/2025	project number: 24-21
checked: KS	DRAWING NO:
date:	ME1-00
	Revision



N01	GENERAL NOTES
	<div><div><div>1. CONFORM TO THE REQUIREMENTS OF THE LATEST ONTARIO BUILDING CODE (OBC) INCLUDING ALL THE LATEST STANDARDS REFERENCED THEREIN, AND ANY APPLICABLE ACTS OF AUTHORITY HAVING JURISDICTION. THE LATEST VERSION OF ALL STANDARDS AND CODES LISTED BELOW SHALL BE USED.</div><div>2. READ STRUCTURAL DRAWINGS IN CONJUNCTION WITH ALL OTHER SPECIFICATIONS AND CONTRACT DOCUMENTS.</div><div>3. WHERE DISCREPANCIES EXIST BETWEEN CONTRACT DOCUMENTS, INCLUDING DRAWINGS AND APPLICABLE CODES AND ACTS, THE MOST STRINGENT SHALL GOVERN. CONTRACTOR SHALL CHECK ALL DIMENSIONS ON WORKING DRAWINGS AND REPORT ANY DISCREPANCIES TO THE ENGINEER BEFORE PROCEEDING WITH THE WORK.</div><div>4. THESE DESIGN DOCUMENTS ARE PREPARED SOLELY FOR THE USE BY THE PARTY WITH WHOM THE DESIGN PROFESSIONAL HAS ENTERED INTO A CONTRACT AND THERE ARE NO REPRESENTATIONS OF ANY KIND MADE BY THE DESIGN PROFESSIONAL TO ANY PARTY WITH WHOM THE DESIGN PROFESSIONAL HAS NOT ENTERED INTO A CONTRACT.</div><div>5. THE USE OF THESE DRAWINGS IS LIMITED TO THAT IDENTIFIED IN THE REVISION COLUMN. DO NOT CONSTRUCT FROM THESE DRAWINGS UNLESS MARKED 'ISSUED FOR CONSTRUCTION' BY MTE CONSULTANTS.</div><div>6. UNDER NO CIRCUMSTANCES ARE THESE DRAWINGS TO BE SCALED, INCLUDING FOR PREPARATION OF SHOP DRAWINGS, CONSTRUCTION LAYOUT, OR BIDDING PURPOSES. ERRORS MADE BY PERSONS SCALING THESE DRAWINGS SHALL NOT BE THE RESPONSIBILITY OF MTE CONSULTANTS.</div><div>7. SEE ARCHITECTURAL, MECHANICAL AND ELECTRICAL DRAWINGS FOR LOCATIONS AND SIZES OF FITS, BASES, HOUSE KEEPING PADS, SUMPS, TRENCHES, DEPRESSIONS, GROOVES, CURBS, CHAMFERS AND SLOPES NOT SHOWN ON STRUCTURAL DRAWINGS.</div><div>8. BEFORE PROCEEDING WITH WORK, THE CONTRACTOR SHALL VISIT THE SITE AND BECOME FAMILIARIZED WITH ALL CHARACTERISTICS AFFECTING NEW AND EXISTING CONSTRUCTION. ANY CHANGES, ALTERATIONS OR REVISIONS MUST BE REPORTED TO THE ENGINEER BEFORE PROCEEDING WITH THE WORK.</div><div>9. SUBSTITUTIONS FROM SPECIFIED PRODUCTS AND MATERIALS MUST BE APPROVED IN WRITING BY THE ENGINEER PRIOR TO ORDERING OF MATERIALS. THE CONTRACTOR SHALL REIMBURSE ALL CONSULTANTS FOR ADDITIONAL COSTS INCURRED AS A RESULT OF REVIEWING ANY CHANGES MADE TO THE CONTRACT DOCUMENTS.</div><div>10. ALL WORK IS TO BE PERFORMED IN ACCORDANCE WITH THE OCCUPATIONAL HEALTH AND SAFETY ACT AND REGULATIONS FOR CONSTRUCTION PROJECTS - O REG. 213/91.</div><div>11. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO DESIGN ALL SHORING AND TEMPORARY BRACING PER O.REG 213/91 AND THE CONTRACTOR SHALL RETAIN AN ENGINEER AS REQUIRED.</div><div>12. THE CONTRACTOR SHALL RETAIN AN INDEPENDENT INSPECTION AND TESTING COMPANY TO ENSURE THAT ALL WORK IS DONE IN ACCORDANCE WITH THE DRAWINGS AND SPECIFICATIONS. REQUIRED TESTING SHALL BE AS PER THE TESTING AND INSPECTION TABLE BELOW.</div><div>13. MTE CONSULTANTS WILL PROVIDE GENERAL REVIEW OF CONSTRUCTION IN ACCORDANCE WITH THE PERFORMANCE STANDARDS OF THE ASSOCIATION OF PROFESSIONAL ENGINEERS OF ONTARIO BY MEANS OF A RATIONAL SAMPLING PROCEDURE TO DETERMINE WHETHER THE CONSTRUCTION OF THAT WORK SHOWN ON THE MTE DRAWINGS IS IN GENERAL CONFORMITY WITH THE PLANS, SKETCHES, DRAWINGS, AND SPECIFICATIONS FORMING PART OF THE CONTRACT DOCUMENTS PREPARED BY "MTE". THE CONTRACTOR IS SOLELY RESPONSIBLE FOR QUALITY CONTROL AND THE PERFORMANCE OF THE WORK IN ACCORDANCE WITH THE CONTRACT. "MTE" SHALL NOT BE RESPONSIBLE FOR THE ACTS OR OMISSIONS OF THE CONTRACTOR, SUB-CONTRACTOR, OR ANY OTHER PERSON PERFORMING ANY OF THE WORK OR FOR THE FAILURE OF ANY OF THEM TO CARRY OUT THE WORK IN ACCORDANCE WITH THE CONTRACT DOCUMENTS.</div><div>14. IT IS THE RESPONSIBILITY OF BOTH THE OWNER AND THE CONTRACTOR TO NOTIFY THE ENGINEER OF CONSTRUCTION PROGRESS SO THE ENGINEER CAN COMPLETE GENERAL REVIEWS. THE CONTRACTOR SHALL PROVIDE THE ENGINEER WITH A CONSTRUCTION SCHEDULE PRIOR TO STARTING THE WORK. GENERALLY, REVIEWS BY THE ENGINEER WILL BE REQUIRED FOR REBAR PRIOR TO CONCRETE PLACEMENT, FOOTING AND FOUNDATIONS PRIOR TO BACKFILLING, AND ABOVE GRADE FRAMING PRIOR TO INSTALLATION OF INTERIOR FINISHES.</div></div></div>

N02

TESTING AND INSPECTION

THE FOLLOWING ITEMS REQUIRE TESTING OR INSPECTION BY A CERTIFIED INDEPENDENT TESTING OR INSPECTION AGENCY UNLESS NOTED OTHERWISE. THE AGENCY SHALL SEND COPIES OF ALL STRUCTURAL TESTING AND INSPECTION REPORTS TO THE ENGINEER FOR REVIEW.

ITEM	REQ'D	COMMENTS
SOIL BEARING CAPACITY	NO	
SOIL COMPACTION	NO	
REINFORCING STEEL PLACEMENT	NO	
CONC. COMPRESSIVE TESTS	NO	
CONCRETE SLUMP	NO	
STRUCTURAL STEEL BOLTING	NO	
STRUCTURAL STEEL WELDING	NO	
MORTAR CUBES	YES	

N03		REQUIRED SUBMITTALS	
THE FOLLOWING ITEMS SHALL BE SUBMITTED TO THE ENGINEER FOR REVIEW PRIOR TO FABRICATION.			
ITEM	REQ'D SUBMITTAL?	ENGINEER'S STAMP REQ'D?	NOTES
REBAR SHOP DRAWINGS	NO	NO	
CONCRETE MIX DESIGNS	NO	NO	
MASONRY GROUT MIX DESIGN	YES	NO	
BLOCK MILL REPORT	YES	NO	
STRUCTURAL STEEL SHOP DRAWINGS	YES	YES	FOR CONNECTIONS ONLY
MISCELLANEOUS STEEL SHOP DRAWINGS	NO	NO	STAMP FOR STAIRS, LADDERS AND GUARDS
STEEL DECK SHOP DRAWINGS	NO	NO	
COLD FORMED STEEL FRAMING SHOP DWGS.	NO	NO	
FALL ARREST ANCHORS	NO	NO	

N08	STRUCTURAL STEEL
	<div><div><div>1. ALL STRUCTURAL STEEL AND CONNECTIONS SHALL BE FABRICATED AND ERECTED IN ACCORDANCE WITH THE LATEST CSA STANDARD S16</div><div>2. STRUCTURAL STEEL SHALL CONFORM TO CAN/CSA-G40.20 FOR GENERAL REQUIREMENTS, AND CAN/CSA-G40.21 FOR QUALITY<div>a. GRADE 350W CLASS C FOR H.S.S.</div><div>b. GRADE 350W FOR W SHAPES, S SHAPES, AND TEES.</div><div>c. ALL OTHER MISCELLANEOUS METAL SHALL BE MINIMUM GRADE 300W (U.N.O.)</div></div></div><div><div>3. BOLTED CONNECTIONS SHALL USE ASTM A325 BOLTS. ALL BOLTS, NUTS AND WASHERS SHALL CONFORM TO THE REQUIREMENTS OF ASTM A325 EXCEPT THAT ANCHOR BOLTS SHALL BE FABRICATED FROM STEEL ROD CONFORMING TO CSA STANDARD G40.21 OR ASTM F1554 WITH A MINIMUM YIELD STRENGTH OF 250 MPa.</div><div>4. STEEL COATINGS - UNLESS NOTED OTHERWISE ALL STRUCTURAL STEEL SHALL BE CLEANED AND PREPARED TO A MINIMUM LEVEL OF SSPC SP-3 AND IN ACCORDANCE WITH CSA STANDARD S16:<div>a. ALL INTERIOR STEEL THAT IS TO BE PROTECTED BY A SPRAY APPLIED CEMENTITIOUS FIRE PROOFING SHALL BE CLEANED AND REMAIN UNCOATED STEEL.</div><div>b. ALL OTHER INTERIOR STRUCTURAL STEEL SHALL BE SHOP PRIME PAINTED AS PER CSA/CAN-S-116. SHOP PRIMER SHALL CONFORM TO CISCO/CPMA 1-73A.</div><div>c. ALL STEEL EXPOSED TO WEATHER IS TO BE HOT DIP GALVANIZED IN ACCORDANCE TO CAN/CSA-G164. TOUCH UP OF WELDS, CUTS OR SCRATCHES TO GALVANIZING SHALL BE DONE WITH A MINIMUM OF 3 COATS OF ZINC RICH PAINT.</div></div></div><div><div>5. WELDING OF STRUCTURAL STEEL SHALL CONFORM TO THE REQUIREMENTS OF CSA STANDARD W59 AND SHALL BE UNDERTAKEN BY A FABRICATOR AND ERECTOR FULLY APPROVED BY THE CANADIAN WELDING BUREAU TO THE REQUIREMENTS OF CSA STANDARD W47, DIVISION 1 AND DIVISION 2. FABRICATOR TO SUPPLY CERTIFICATION OF FUSION WELDING, AND WELDING MAY ONLY BE CARRIED OUT IN ACCORDANCE WITH OWNER'S SAFETY REGULATIONS REGARDING WELDING.</div><div>6. FABRICATOR SHALL DESIGN CONNECTIONS AND THE LIKE IN ACCORDANCE WITH THE 2012 OBC FOR THE FORCES SHOWN ON THE DRAWINGS. WHERE FORCES ARE NOT NOTED ON THE DRAWINGS, BEAM REACTIONS SHALL BE TAKEN AS ONE-HALF OF THE TOTAL UNIFORMLY DISTRIBUTED FACTORED LOADS NOTED ON THE BEAM LOAD TABLES OF PART FIVE OF CISCO'S HANDBOOK OF STEEL CONSTRUCTION, LATEST EDITION. PROVIDED NO POINT LOADS ACT ON THE BEAM, ALL WELDS SHALL BE 5 mm (3/16") MIN. FILLET. ALL BOLTS SHALL BE MIN. M20 (3/4") DIAMETER AND PROVIDE MIN. (2) BOLTS PER CONNECTION.</div><div>7. WHERE MOMENT CONNECTIONS ARE CALLED FOR BUT VALUES ARE NOT INDICATED, DESIGN CONNECTIONS FOR FULL MOMENT CAPACITY OF THE SMALLER MEMBER JOINED.</div><div>8. SPLICES SHALL BE DESIGNED TO DEVELOP THE FULL CAPACITY OF THE MEMBER AT THE POINT OF THE SPLICE. MEMBERS SHALL NOT BE SPLICED AT POINTS OF MAXIMUM STRESS. NO SPLICES SHALL BE MADE UNLESS SHOWN ON THE DRAWINGS OR REVIEWED AND APPROVED BY THE ENGINEER.</div><div>9. MOMENT FRAME AND X-BRACE CONNECTIONS SHALL HAVE ASTM A325 FRICTION TYPE M20 (3/4") MINIMUM DIAMETER BOLTS (U.N.O.).</div><div>10. SHAPE AND SIZE GUSSET PLATES TO CLEAR ARCHITECTURAL FINISHES AND MECHANICAL DUCTS AND PIPES AND ELEVATOR SHAFTS.</div><div>11. SHOP DRAWINGS OF STRUCTURAL STEEL SHALL BE SUBMITTED TO THE ENGINEER FOR REVIEW BEFORE FABRICATION.</div><div>12. ALL BEAMS CANTILEVERED OR CONTINUOUS OVER A COLUMN OR OTHER SUPPORT, AND BEAMS SUPPORTING POINTS OF CONCENTRATED LOAD, SHALL HAVE A MIN. OF 2-10 mm (3/8") STIFFENERS EACH SIDE OF WEB UNLESS OTHERWISE NOTED.</div><div>13. TOP OF COLUMNS WHICH ARE NOT BRACED BY JOISTS OR BEAMS SHALL BE BRACED DIAGONALLY TO THE ROOF OR FLOOR BY A MINIMUM OF 4-L76 x 76 x 6.4 mm (L3 x 3 x 1/4") ANGLES FOR INTERIOR COLUMNS; A MINIMUM 2-L76 x 76 x 6.4 mm (L3 x 3 x 1/4") ANGLES FOR EXTERIOR COLUMNS. BRACING SHALL BE BETWEEN TOP OF COLUMN AND TOP CHORD OF JOISTS.</div><div>14. COLUMN BASE PLATES AND BEAM BEARING PLATES SHALL BE GROUTED WITH 40 mm (1.5") NON-SHRINK 40 MPa GROUT.</div><div>15. ALL COLUMNS BUILT INTO MASONRY WALLS SHALL HAVE ADJUSTABLE ANCHORS AT MINIMUM 400 mm (16") O.C.</div><div>16. STEEL BEAMS AND LINTELS SHALL HAVE 200 mm (8") MINIMUM END BEARING ON MASONRY AND 65 mm (2 1/2") MINIMUM BEARING ON STEEL UNLESS INDICATED OTHERWISE.</div><div>17. FOR ALL BEAMS AND LINTELS ON STEEL BEARING PLATES.<div>a. BEARING PLATES ARE TO BE CENTRED BELOW ALL BEAMS OR LINTELS U.N.O. ON THE DRAWINGS.</div><div>b. WELD TO BEARING PLATE WITH A MINIMUM 50 mm x 5 mm (2" x 3/16") FILLET ON BOTH SIDES OF BEAM.</div></div><div>18. WHERE BACK-TO-BACK ANGLES ARE USED AS LINTELS OR SUPPORTS. STITCH WELD TOGETHER AT A MAXIMUM SPACING OF 300mm (12") O.C.</div><div>19. ALL ROOF OPENINGS TO BE REINFORCED BY FRAMES COMPRISED OF C130x10 (C5x6.7) CHANNEL MEMBERS UNLESS NOTED OTHERWISE. MAXIMUM SPAN 2250 mm (7'-6").</div><div>20. SUPPORT AT COLUMNS AND IRREGULARITIES:<div>a. INSTALL L76 x 76 x 6.4 mm (L3 x 3 x 1/4") ANGLE SEATS FOR STEEL DECK AT CONNECTIONS, AT COLUMNS OR OTHER IRREGULARITIES, TO PROVIDE SUPPORT TO THE RIBS OF THE DECK.</div><div>b. INSTALL L102 x 102 x 7.9 mm (L4 x 4 x 5/16") ANGLE SEATS FOR PRECAST SUPPORT AT CONNECTIONS, AT COLUMNS OR OTHER IRREGULARITIES, TO PROVIDE BEARING FOR PRECAST PLANKS.</div></div><div>21. NO STRUCTURAL STEEL SHALL BE CUT IN THE FIELD UNLESS REVIEWED AND APPROVED BY THE ENGINEER.</div><div>22. MAINTAIN ERECTION BRACING UNTIL COMPLETION OF ENTIRE STRUCTURE, INCLUDING ROOF DECKS AND OTHER ELEMENTS WHICH ARE PART OF THE LATERAL LOAD RESISTING SYSTEM.</div></div></div>

N09	MASONRY
	<div><div><div>1. ALL MASONRY CONSTRUCTION SHALL CONFORM TO THE REQUIREMENTS OF CSA STANDARDS CAN/CSA-A370, CAN/CSA-A371 AND CSA S304.1.</div><div>2. ALL MASONRY UNITS OF CONCRETE SHALL CONFORM TO THE CSA STANDARD CAN/CSA-A165 AND SHALL HAVE A MINIMUM LOAD BEARING STRENGTH OF 15MPa BASED ON NET CROSS-SECTIONAL AREA.</div><div>3. REINFORCING BARS SHALL CONFORM TO THE REQUIREMENTS OF CAN/CSA G30.18 GRADE 400W FOR REINFORCING STEEL AND BE DEFORMED HI-BOND HARD GRADE WITH MINIMUM YIELD STRENGTH OF Fy = 400 MPa.</div><div>4. TYPE S MORTAR SHALL BE USED THROUGHOUT FOR LOAD BEARING BLOCK. TYPE N MORTAR SHALL BE USED FOR BRICK VENEER OR DECORATIVE NON-LOAD BEARING BLOCK.<div>LAB CURED MORTAR COMPRESSIVE STRENGTHS:<div>(JOB PREPARED MIX)<div>TYPE S: MIN. 28 DAY STRENGTH 12.0 MPa</div><div>TYPE N: MIN. 28 DAY STRENGTH 7.5 MPa</div></div>MORTAR MIX PROPORTIONS:<div>MIX ACCORDING TO TABLE 3 OR 4 OF CSA A179. MORTAR MIX SHALL BE TESTED FOR STRENGTH AND APPROVED BY THE ENGINEER PRIOR TO USE ON THE JOB.</div>GROUT: (WHERE CALLED FOR ON DRAWINGS) SHALL CONFORM TO CAN/CSA A179.<div>MIN. 28 DAY STRENGTH 20 MPa</div></div></div></div><div><div>5. ALL MASONRY WALLS SHALL BE HORIZONTALLY REINFORCED WITH NO.8 (3.7mm) STANDARD DURO-WALL TRUSS JOINT REINFORCEMENT (OR APPROVED EQUAL) AND CONTINUOUS REINFORCEMENT AT EVERY SECOND COURSE (400 mm/16").<div>a. ALL JOINT REINFORCEMENT SHALL BE HOT-DIPPED GALVANIZED.</div><div>b. REINFORCEMENT SHALL BE LAPPED A MINIMUM OF 300mm (12") AT ALL JOINTS.</div><div>c. PREFABRICATED CORNER AND TEE REINFORCEMENT SHALL BE USED AT ALL WALL INTERSECTIONS.</div><div>d. REINFORCEMENT SHALL BE INSTALLED IN THE FIRST AND SECOND BED JOINTS 200 mm (8") APART, BELOW THE TOP OF WALLS.</div><div>e. REINFORCEMENT SHALL BE INSTALLED IN THE FIRST AND SECOND BED JOINTS 200 mm (8") APART, IMMEDIATELY ABOVE LINTELS AND BELOW SILLS AND SHALL EXTEND 600 mm (2'-0") BEYOND THE JAMB.</div></div><div>6. REINFORCEMENT SHALL BE PLACED AS TO PROVIDE 16 mm (5/8") MORTAR COVER ON THE EXTERIOR FACE OF WALL AND 12 mm (1/2") COVER ON THE INTERIOR FACE OF WALL.</div><div>7. WHERE MOMENT CONNECTIONS ARE CALLED FOR BUT VALUES ARE NOT INDICATED, DESIGN CONNECTIONS FOR FULL MOMENT CAPACITY OF THE SMALLER MEMBER JOINED.</div><div>8. ALL BLOCK MASONRY UNITS SHALL BE CONSTRUCTED WITH FULL HEAD JOINTS, AND ULL BED JOINTS UNDER THE FULL BEARING AREAS OF THE FACE SHELLS, AND UNDER WEBS SURROUNDING THOSE CELLS TO BE FILLED WITH GROUT.</div><div>9. THE INTERSECTION OF ALL MASONRY WALLS SHALL BE TOOTHED OR CONTINUOUSLY REINFORCED WITH JOINT REINFORCEMENT.</div><div>10. PROVIDE A MINIMUM DEPTH OF 200 mm (8") OF 100% SOLID MASONRY UNITS, OR FULLY GROUTED UNITS, FOR SLABS OR STEEL DECK BEARING ON MASONRY, UNLESS MORE IS SHOWN ON THE DRAWINGS.</div><div>11. ALL MASONRY BENEATH CONCENTRATED LOADS (SUCH AS BEAMS, LINTELS, AND JOISTS) SHALL HAVE VOIDS FILLED WITH 20 MPA GROUT FOR A MINIMUM DEPTH OF 400 mm (16") OR 3 TIMES THE LENGTH OF BEARING (WHICHEVER IS GREATER) AND PROJECTING A MINIMUM OF 200 mm (8") OR THE LENGTH OF BEARING BEYOND EACH EDGE OF BEARING (WHICHEVER IS GREATER), UNLESS OTHERWISE NOTED OR SHOWN.</div><div>12. WHERE STEEL BEARING PLATES ARE SHOWN ON THE DRAWINGS, THEY SHALL BE ANCHORED WITH A MINIMUM OF TWO 12 mm DIA X 450 mm LONG + 50 mm (1/2" DIA x 18" LONG + 2") HOOKED ANCHOR RODS WELDED TO THE PLATES AND EMBEDDED INTO GROUT FILL AS NOTED ABOVE.</div><div>13. SEE PLANS AND SCHEDULES REGARDING LINTEL SIZES FOR MASONRY WALLS AND VENEER.</div><div>14. FOR ALL OPENINGS OR RECESSES IN MASONRY NOT SHOWN ON DRAWINGS GREATER THAN 300 mm (12") AND UP TO 1200 mm (4 FT.), INCLUDING THOSE FOR MECHANICAL OR ELECTRICAL SERVICES OR EQUIPMENT, PROVIDE ONE L80x80x6.4 (L3 1/2 X 3 1/2 X 1/4") ANGLE FOR EACH 100 mm (4") THICKNESS OF WALL.</div><div>15. MAINTAIN SUPPORT OF MASONRY LINTELS FOR A MINIMUM OF SEVEN DAYS OR UNTIL SUFFICIENT STRENGTH IS GAINED TO SAFELY SUPPORT LOADS IMPOSED.</div><div>16. FULLY GROUT BLOCK CELLS AT PARAPETS.</div><div>17. ALL MASONRY WALLS SHALL BE ADEQUATELY BRACED DURING CONSTRUCTION UNTIL ADEQUATE DIAPHRAGM ACTION CAN BE DEVELOPED BY INSTALLED FLOOR AND ROOF STRUCTURAL COMPONENTS.</div><div>18. REFER TO ARCHITECTURAL DRAWINGS FOR LOCATIONS OF MASONRY CONTROL JOINTS. SPACING OF CONTROL JOINTS IN ALL WALLS SHALL BE CONSTRUCTED AS PER PLAN, BUT SHALL NOT EXCEED 6000 mm (20'-0") O.C. ALL REINFORCING TO BE DISCONTINUOUS AT CONTROL JOINTS. CONTROL JOINTS SHALL BE CALKED WITH FOAM BACKER ROD AND SHALL NOT BE FILLED WITH MORTAR.</div><div>19. REINFORCED MASONRY:<div>a. CELLS TO BE REINFORCED SHALL BE KEPT CLEAN OF MORTAR.</div><div>b. GROUT FOR REINFORCED CELLS, BOND BEAMS, LINTELS AND CELLS CONTAINING DOWELS, ANCHOR BOLTS AND INSERTS PER NOTE #3C.</div><div>c. PROVIDE MINIMUM 2-15M VERTICALS FULL HEIGHT AT ALL WALL ENDS, CORNERS, INTERSECTIONS AND OPENINGS UNLESS OTHERWISE NOTED ON DRAWINGS.</div><div>d. PROVIDE 1-15M VERTICAL FULL HEIGHT EACH SIDE OF CONTROL JOINTS.</div><div>e. DOWELS FROM FOUNDATIONS TO MATCH VERTICAL REINFORCEMENT IN WALL.</div><div>f. PROVIDE THE FOLLOWING LAPS FOR THE REINFORCEMENT INDICATED:<div>- 10M BARS = 450 mm (18")</div><div>- 15M BARS = 600 mm (24")</div><div>- 20M BARS = 900 mm (36")</div></div></div><div>20. EMBEDDED ITEMS ARE NOT TO INTERFERE WITH THE INTEGRITY OF THE MASONRY WALL OR LOCATION OF REINFORCEMENT. PROVIDE FULLY GROUTED LINTEL BEAM FOR CONDUITS AND PIPES RUNNING HORIZONTALLY WITHIN WALL.</div></div></div>

N10	SHOP DRAWING REVIEW
	<div><div><div>1. ERECTION AND FABRICATION SHOP DRAWINGS FOR ALL BUILDING COMPONENTS AS LISTED IN THE REQUIRED SUBMITTALS TABLE AND ANY RELATED WORKS ARE TO BE SUBMITTED TO THE ENGINEER FOR APPROVAL BEFORE COMMENCING WITH FABRICATION.</div><div>2. AS PART OF THEIR FIELD SERVICES, MTE CONSULTANTS ("MTE") WILL REVIEW SHOP DRAWINGS PERTAINING TO WORK SHOWN ON MTE CONSULTANT'S DRAWINGS BY MEANS OF APPROPRIATE RATIONAL SAMPLING PROCEDURES AND COMMENT ON THE ACCURACY WITH WHICH THE CONTRACTOR PREPARED THE DRAWINGS.</div><div>3. REVIEW OF THE SHOP DRAWINGS IS FOR THE SOLE PURPOSE OF ASCERTAINING CONFORMANCE WITH THE GENERAL DESIGN CONCEPT AND IS NOT AN APPROVAL OF THE DETAIL DESIGN INHERENT IN THE SHOP DRAWINGS, RESPONSIBILITY FOR WHICH SHALL REMAIN WITH THE CONTRACTOR SUBMITTING THEM. SUCH REVIEW SHALL NOT RELIEVE THE CONTRACTOR OF THEIR RESPONSIBILITY FOR ERRORS AND OMISSIONS IN THE SHOP DRAWINGS OR FOR MEETING ALL REQUIREMENTS OF THE CONTRACT DOCUMENTS. THE CONTRACTOR IS SOLELY RESPONSIBLE FOR INFORMATION PERTAINING TO THE FABRICATION PROCESS TECHNIQUES OF CONSTRUCTION AND INSTALLATION AND FOR COORDINATION OF THE WORK OF ALL SUB-TRADES.</div><div>4. THE APPROVAL OF SHOP DRAWINGS DOES NOT RELIEVE THE CONTRACTOR FROM THE RESPONSIBILITY OF THE FITTING OF BUILDING COMPONENTS, ANY DISCREPANCIES IN THE SHOP DRAWINGS ARE THE RESPONSIBILITY OF THE CONTRACTOR.</div><div>5. ALL SHOP DRAWINGS MUST BEAR THE SEAL OF A PROFESSIONAL ENGINEER LICENSED IN ONTARIO UNLESS NOTED OTHERWISE IN THE SUBMITTALS TABLE BELOW. UNSEALED SHOP DRAWINGS WILL NOT BE REVIEWED UNLESS ALTERNATIVE ARRANGEMENTS HAVE BEEN AGREED UPON.</div></div></div>

N15	STRUCTURAL ABBREVIATIONS		
A.B ALT. ALUM. ANCH'S APPROX. ARCH. B/F B.P/L BLK. BM. BOT. BRG. BT.PL C/W C/C C.J. C.LG. COL. CONC. CONN. CONSTRN CONT. DEMO. DET. DIA. DIM. DO DP. DWG. DWL. E.F. E.J. ELEC. E.S. E.W. EA. EL. EQ. EXIST. F.F. FIN. FL. FNDN. FTG. Ga. GALV. GRD. HORIZ. H.D. H.D.G. H.E.F. H.P. HSS	ANCHOR BOLT ALTERNATE ALUMINUM ANCHORS APPROXIMATELY ARCHITECTURAL BOTTOM FACE BASE PLATE BLOCK BEAM BOTTOM BEARING BENT PLATE COMPLETE WITH CENTRE TO CENTRE CONTROL JOINT CEILING COLUMN CONCRETE CONNECTION CONSTRUCTION CONTINUOUS DEMOLITION DETAIL DIAMETER DIMENSION DIDO DEEP DRAWING DOWEL EACH FACE EXPANSION JOINT ELECTRICAL EACH SIDE EACH WAY EACH ELEVATION EQUAL EXISTING FACE TO FACE FINISHED FLOOR FOUNDATION FOOTING GAUGE GALVANIZED GRADE HORIZONTAL HEAVY DUTY HOT DIPPED GALVANIZED HORIZONTAL EACH FACE HIGH POINT HOLLOW STRUCTURAL STEEL	I.D. KILONEWTON kPa L L.L.H. L.L.V. L.P. LG. MAX. MECH MET'L MIN. MISC. m mm MPa N.I.C. N.T.S. No. O.C. O.D. O.H. OWENSJ OPENG. PARTN PL. PLATE R.C. R.D. R.O. REF. REINFC. REQ'D S.C. SECT. S.L.H. S.L.V. S.O.G. S.S. STL. STIFF. STRUCT. T/O T.L.L. T.U.L. TYP. U.N.O. U/S VERT. V.E.F. V.I.F. V.O.F. W.P. W.W.M.	INSIDE DIAMETER KILONEWTON KILOPASCAL ANGLE LONG LEG HORIZONTAL LONG LEG VERTICAL LOW POINT LONG MAXIMUM MECHANICAL METAL MINIMUM MISCELLANEOUS METRE MILLIMETRE MEGAPASCAL NOT IN CONTRACT NOT TO SCALE NUMBER ON CENTRE OUTSIDE DIAMETER OVERHEAD OWEN WEB STEEL JOIST OPENING PARTITION PLATE REINFORCED CONCRETE ROOF DRAIN ROUGH OPENING REFERENCE REINFORCED REQUIRED SAWCUT SECTION SHORT LEG HORIZONTAL SHORT LEG VERTICAL SLAB ON GRADE STAINLESS STEEL STEEL STIFFENER STRUCTURAL TOP OF TOP LOWER LAYER TOP UPPER LAYER TYPICAL UNLESS NOTED OTHERWISE UNDERSIDE VERTICAL VERTICAL EACH FACE VERTICAL INSIDE FACE VERTICAL OUTSIDE FACE WORKING POINT WELEDED WIRE MECH @ SPACED AT

NOTE TO CONTRACTOR: DO NOT SCALE DRAWINGS.
CONTRACTORS MUST CHECK AND VERIFY ALL DIMENSIONS AND REPORT ANY DISCREPANCIES TO THE ENGINEER BEFORE PROCEEDING WITH THE WORK.
ALL DRAWINGS REMAIN THE PROPERTY OF THE ENGINEER AND SHALL NOT BE REPRODUCED OR REUSED WITHOUT THE ENGINEER'S WRITTEN PERMISSION.
THE OWNER/ARCHITECT/CONTRACTOR IS ADVISED THAT M.T.E. CONSULTANTS INC. CANNOT CERTIFY ANY COMPONENT OF THE SITE WORKS NOT INSPECTED DURING CONSTRUCTION. IT IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO NOTIFY M.T.E. CONSULTANTS INC. PRIOR TO COMMENCEMENT OF CONSTRUCTION TO ARRANGE FOR INSPECTION.

ISSUED FOR TENDER	2	APR. 01, 2025
ISSUED FOR TENDER	1	MAR. 12, 2025
ISSUANCE	ID	DATE



Ph. (905) 639-2552      www.mte85.com

CLIENT  
**AMRA J ARCHITECTS INC.**

PROJECT  
**LAKE AVENUE ELEMENTARY SCHOOL**


157 LAKE AVENUE NORTH,      HAMILTON, ON

DRAWING

## GENERAL NOTES

Project Manager:	DXF	Date:	MARCH 2025
Design By:	PVD	Project No.:	60671_001
Drawn By:	NXP	Drawing No.:	
Scale:	AS NOTED		<b>S1.0</b>






- NOTES:
1. T/O SLAB EL. = (SEE ARCH. DWGS.)
  2. REFER TO ARCH. DRAWINGS FOR ALL DIMENSIONS, OPENINGS AND SLOPES NOT SHOWN ON THIS DRAWING.
  3. SEE TYPICAL SCHEDULE FOR LINTELS IN NON-LOAD BEARING CONCRETE BLOCK WALLS.
  4. MASONRY SUPPLIER TO PROVIDE BLOCK TIES FROM NEW BULLNOSE MASONRY TO EXISTING CONCRETE MASONRY WALL.
  5. IT IS THE SOLE RESPONSIBILITY OF THE CONTRACTOR TO DESIGN ALL SHORING AND TEMPORARY BRACING AS PER O.Reg 213/91 AND THE CONTRACTOR SHALL RETAIN AN ENGINEER AS REQUIRED. ANY NEW OPENINGS WITHIN THE EXISTING BLOCK WALLS WILL REQUIRE TEMPORARY SHORING.
  6. REFER TO ARCH. AND/OR MECH. DRAWINGS FOR DIMENSIONS AND LOCATIONS OF MECHANICAL UNITS.

## FRAMING PLAN

1 : 50



## TYPICAL SECTION DETAIL

FOR UNITS SUSPENDED BELOW JOISTS (N.T.S.)

### NOTE TO CONTRACTOR:

DO NOT SCALE DRAWINGS.

CONTRACTORS MUST CHECK AND VERIFY ALL DIMENSIONS AND REPORT ANY DISCREPANCIES TO THE ENGINEER BEFORE PROCEEDING WITH THE WORK.

ALL DRAWINGS REMAIN THE PROPERTY OF THE ENGINEER AND SHALL NOT BE REPRODUCED OR REUSED WITHOUT THE ENGINEER'S WRITTEN PERMISSION.

THE OWNER/ARCHITECT/CONTRACTOR IS ADVISED THAT M.T.E. CONSULTANTS INC. CANNOT CERTIFY ANY COMPONENT OF THE SITE WORKS NOT INSPECTED DURING CONSTRUCTION. IT IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO NOTIFY M.T.E. CONSULTANTS INC. PRIOR TO COMMENCEMENT OF CONSTRUCTION TO ARRANGE FOR INSPECTION.

ISSUED FOR TENDER	2	APR. 01, 2025
ISSUED FOR TENDER	1	MAR. 12, 2025
ISSUANCE	ID	DATE



Engineers, Scientists, Surveyors

Ph. (905) 639-2552

www.mte85.com

CLIENT

AMRA J ARCHITECTS INC.

PROJECT

LAKE AVENUE ELEMENTARY  
SCHOOL

157 LAKE AVENUE NORTH,

HAMILTON, ON

DRAWING

FRAMING PLAN  
WASHROOMS AND  
CHANGEROOMS

Project Manager:	DXF	Date:	MARCH 2025
Design By:	PVD	Project No.:	60671_001
Drawn By:	NXP	Drawing No.:	S2.0
Scale:	AS NOTED		




INTERIOR NON-LOAD BEARING MASONRY PARTITION WALL  
MINIMUM REINFORCEMENT


SEISMIC HAZARD INDEX	WALL THICKNESS	VERTICAL REINFORCEMENT	HORIZONTAL REINFORCEMENT
leFaSa(0.2) < 0.35	140	NO MANDATED MINIMUM	STANDARD 3.6mm LADDER TYPE EVERY 3RD BED JOINT
	190	NO MANDATED MINIMUM	STANDARD 3.6mm LADDER TYPE EVERY 3RD BED JOINT
	240	NO MANDATED MINIMUM	STANDARD 3.6mm LADDER TYPE EVERY 3RD BED JOINT
	290	NO MANDATED MINIMUM	STANDARD 3.6mm LADDER TYPE EVERY 3RD BED JOINT
0.35 < leFaSa(0.2) < 0.75	140	15M@800	STANDARD 3.6mm LADDER TYPE EVERY 2ND BED JOINT
	190	15M@1200	STANDARD 3.6mm LADDER TYPE EVERY 2ND BED JOINT
	240	15M@1200	STANDARD 3.6mm LADDER TYPE EVERY 2ND BED JOINT
	290	15M@1200	STANDARD 3.6mm LADDER TYPE EVERY 2ND BED JOINT
leFaSa(0.2) < 0.75	140	15M@800	STANDARD 3.6mm LADDER TYPE EVERY 2ND BED JOINT
	190	15M@1200	STANDARD 3.6mm LADDER TYPE EVERY BED JOINT
	240	15M@1200	STANDARD 3.6mm LADDER TYPE EVERY BED JOINT
	290	15M@1200	STANDARD 3.6mm LADDER TYPE EVERY BED JOINT

- NOTES:
- CONDITIONS WHERE THIS DETAIL IS APPLICABLE:
  - "PIN-PIN" WALLS. LATERAL SUPPORT IS REQUIRED AT THE TOP OF ALL MASONRY PARTITION WALLS. REFER TO MASONRY LATERAL SUPPORT TYPICAL DETAILS.
  - MASONRY WALL PIERS ONLY WHEN THEIR LENGTH EXCEEDS 800mm, PIERS MUST BE CONTINUOUS TO TOP OF WALL.
  - INTERIOR PARTITIONS ONLY WITH A MAXIMUM HEIGHT OF 4000mm.
  - DOES NOT APPLY TO MASONRY PARAPETS.


C14 DETAILS OF MASONRY WALL AT CONCRETE SLAB AND WALL (N.T.S.)



SECTION DETAIL OF SUPPORT FOR NON LOADBEARING MASONRY WALLS



C25 TYPICAL SECTION DETAIL AT INTERSECTING BLOCK WALLS (N.T.S.)



NON-LOAD BEARING BLOCK LINTEL SCHED.

STEEL LINTELS

WIDTH	<4'-0"	5'-0"	7'-0"	8'-0"	12'-0"	SECTION DETAIL
4"	(2) L 2 1/2x3/16 (LLV)	(2) L 2 1/2x3/16 (LLV)				
6"	(2) L 2 1/2x1/4 (LLV)	(2) L 2 1/2x1/4 (LLV)	(2) L 3 1/2x1/4 (LLV)	(2) L 3 1/2x1/4 (LLV)	(2) L 3 1/2x1/4 (LLV)	
8"	(2) L 3 1/2x3/4 (LLH)	(2) L 3 1/2x3/4 (LLH)	(2) L 3 1/2x1/4 (LLV)	(2) L 5x3 1/2x5/16 (LLV)	(2) L 5x3 1/2x5/16 (LLV)	
10"	L 4x3 1/4 (LLH) L 5x3 1/4 (LLH)	L 4x3 1/4 (LLH) L 5x3 1/4 (LLH)	L 4x3 1/2x5/16 (LLH) L 5x3 1/2x5/16 (LLH)	L 6x4x5/16 (LLV) L 5x4x5/16	L 6x4x5/16 (LLV) L 5x4x5/16	
12"	(3) L 3 1/2x3/4 (LLH)	(3) L 3 1/2x3/4 (LLH)	(3) L 3 1/2x1/4 (LLV)	(3) L 5x3 1/2x1/4 (LLV)	(3) L 5x3 1/2x1/4 (LLV)	

- NOTES:
- STRUCTURAL STEEL SHALL BE G40.12.
  - BEARING LENGTH = 6" AT EACH END.
  - CONNECT ANGLES @ 24" o/c BY WELDING or BOLTING FOR ANGLES WITH A TOTAL LENGTH OF 6'-0" OR MORE.


NON-LOAD BEARING BLOCK LINTEL SCHED.

BLOCK LINTELS

WIDTH	DEPTH	MAX CLEAR SPAN					SECTION DETAIL
		<4'-0"	5'-0"	7'-0"	8'-0"	10'-0"	
4"	d	190	390	390			
	BOT. REINF.	1-10M	1-10M	1-10M			
6"	d	190	190	390	390		
	BOT. REINF.	2-10M	2-10M	2-10M	2-10M		
8"	d	190	190	390	390	390	
	BOT. REINF.	2-10M	2-10M	2-10M	2-10M	2-10M	
10"	d	190	190	390	390	390	
	BOT. REINF.	2-10M	2-10M	2-10M	2-10M	2-10M	
12"	d	190	190	390	390	390	
	BOT. REINF.	2-10M	2-10M	2-10M	2-10M	2-10M	

- NOTES:
- BLOCK STRENGTH = 15 MPa @ 28 DAYS
  - REINFORCING STEEL TO BE GRADE 400W
  - 6" NOMINAL BEARING LENGTH (UNLESS NOTED OTHERWISE)


LATERAL SUPPORT AT TOPS OF NON-LOAD BEARING MASONRY WALLS




WALL PARALLEL TO OWSJ AND OR BEAM

MASONRY WALL THICKNESS	EACH SIDE SPACING @ 6\"/>
140 BLOCK (4'-0")	1200
190 & LARGER BLOCK	1500 (5'-0")

WALL PERPENDICULAR OWSJ AND OR BEAM




SECTION DETAIL OF SUPPORT FOR NON LOADBEARING MASONRY WALLS




PLAN DETAIL OF MASONRY WALL FACING CONCRETE (N.T.S.)

C16a DETAILS OF MASONRY WALL AT METAL DECK (N.T.S.)



TYPICAL BLOCK WALL BRACED BY PARALLEL OWSJ




TYPICAL BLOCK WALL BRACED BY PERPENDICULAR OWSJ

WALL PLATE SCHED.


TYPE	PLATE SIZE THK.xL.G.xWD.	ANCHORAGE
WPL.1	10x290x290	(2) 12mm Ø ROD w/ 300 EMBEDMENT
WPL.2	10x178x178	(2) 12mm Ø ROD w/ 300 EMBEDMENT

- NOTES:
- CONCRETE FILL SOLID (3) MASONRY COURSES MIN. BENEATH ALL BEARING PLATES.
  - PLATE DIMENSION NOTED AS "LENGTH" TO BE PARALLEL WITH BEAM WEB.
  - FIELD WELD BEAM TO BEARING PLATE w/ 2- 6.4mmx38mm LG. FILLET WELDS (EACH SIDE).



TYP. ELEVATION DETAIL @ WALL (N.T.S.)

TYP. ELEVATION DETAIL @ WALL PLATE (N.T.S.)



TYP. SECTION DETAIL @ CONT. WELD PLATE (N.T.S.)

MASONRY VENEER LINTEL SCHED.

MAX. CLEAR SPAN	SIZE	REMARKS
2100	L89x76x6.4 (LLH)	
2700	L102x102x6.4	
3050	L127x89x7.9 (LLV)	
3350	L127x89x9.5 (LLV)	
3650	L152x102x9.5 (LLV)	
3950	L152x102x11.0 (LLV)	
4250	L178x102x11.0 (LLV)	
4550	L203x102x11.0 (LLV)	

- NOTES:
- LINTEL BEARING LENGTH TO BE MIN. 150mm
  - ALL STRUCTURAL STEEL MEMBERS TO BE HOT DIPPED GALVANIZED.
  - SEE ARCHITECTURAL DRAWINGS FOR SPANS.

NOTE TO CONTRACTOR:

DO NOT SCALE DRAWINGS.

CONTRACTORS MUST CHECK AND VERIFY ALL DIMENSIONS AND REPORT ANY DISCREPANCIES TO THE ENGINEER BEFORE PROCEEDING WITH THE WORK.

ALL DRAWINGS REMAIN THE PROPERTY OF THE ENGINEER AND SHALL NOT BE REPRODUCED OR REUSED WITHOUT THE ENGINEER'S WRITTEN PERMISSION.

THE OWNER/ARCHITECT/CONTRACTOR IS ADVISED THAT M.T.E. CONSULTANTS INC. CANNOT CERTIFY ANY COMPONENT OF THE SITE WORKS NOT INSPECTED DURING CONSTRUCTION. IT IS THE RESPONSIBILITY OF THE GENERAL CONTRACTOR TO NOTIFY M.T.E. CONSULTANTS INC. PRIOR TO COMMENCEMENT OF CONSTRUCTION TO ARRANGE FOR INSPECTION.

ISSUED FOR TENDER	2	APR. 01, 2025
ISSUED FOR TENDER	1	MAR. 12, 2025
ISSUANCE	ID	DATE



Ph. (905) 639-2552

www.mte85.com

CLIENT

AMRA J ARCHITECTS INC.

PROJECT

LAKE AVENUE ELEMENTARY SCHOOL

157 LAKE AVENUE NORTH,

HAMILTON, ON

DRAWING

MASONRY SCHEDULES AND TYPICAL DETAILS

Project Manager:	DXF	Date:	MARCH 2025
Design By:	PVD	Project No.:	60671_001
Drawn By:	NXP	Drawing No.:	S3.0
Scale:	AS NOTED		